

Mathematical Foundations of Computer Science

CS 499, Shanghai Jiaotong University, Dominik Scheder

Spring 2019

10 Network Flow

- Homework assignment published on Thursday 2019-05-16
- Submit questions and first solution by Wednesday, 2019-05-22, 12:00
- Submit final solution by Wednesday, 2019-05-29.

Exercise 10.1. [From the video lecture] Recall the definition of the value of a flow: $\text{val}(f) = \sum_{v \in V} f(s, v)$. Let $S \subseteq V$ be a set of vertices that contains s but not t . Show that

$$\text{val}(f) = \sum_{u \in S, v \in V \setminus S} f(u, v) .$$

That is, the total amount of flow leaving s equals the total amount of flow going from S to $V \setminus S$. **Remark.** It sounds obvious. However, find a formal proof that works with the axiomatic definition of flows.

Exercise 10.2. Let $G = (V, E, c)$ be a flow network. Prove that flow is “transitive” in the following sense: If there is a flow from s to r of value k , and a flow from r to t of value k , then there is a flow from s to t of value k . **Hint.** The solution is extremely short. If you are trying something that needs more than 3 lines to write, you are on the wrong track.

Algorithm 1 Ford-Fulkerson Method

```
1: procedure FF( $G = (V, E), s, t, c$ )
2:   Initialize  $f$  to be the all-0-flow.
3:   while there is a path  $p$  from  $s$  to  $t$  in the residual network  $G_f$  do
4:      $c_{\min} := \min\{c_f(e) \mid e \in p\}$ 
5:     let  $f_p$  be the flow in  $G_f$  that routes  $c_{\min}$  flow along  $p$ 
6:      $f := f + f_p$ 
7:   end while
8:   // now  $f$  is a maximum flow
9:    $S := \{v \in V \mid G_f \text{ contains a path from } s \text{ to } v\}$ 
10:  //  $S$  is a minimum cut
11:  return ( $f, S$ )
12: end procedure
```

10.1 An Algorithm for Maximum Flow

Recall the algorithm for Maximum Flow presented in the video. It is usually called the Ford-Fulkerson method.


We proved in the lecture that f is a maximum flow and S is a minimum cut, by showing that upon termination of the while-loop, $\text{val}(f) = \text{cap}(S)$. The problem is that the while-loop might not terminate. In fact, there is an example with capacities in \mathbb{R} for which the while loop does not terminate, and the value of f does not even converge to the value of a maximum flow. As indicated in the video, a little twist fixes this:

Edmonds-Karp Algorithm: Execute the above Ford-Fulkerson Method, but in every iteration choose p to be a shortest s - t -path in G_f . Here, “shortest” means minimum number of edges.

In a series of exercises, you will now show that this algorithm always terminates after at most $n \cdot m$ iterations of the while loop (here $n = |V|$ and $m = |E|$).

Definition 10.3. Let (G, s, t, c) be a flow network and $k \in \mathbb{N}_0$. A k -layering is a partition of $V = V_0 \cup \dots \cup V_k$ such that (1) $s \in V_0$, (2) $t \in V_k$, (3) for every edge $(u, v) \in E$ the following holds: suppose $u \in V_i$ and $v \in V_j$. Then $j \leq i + 1$. In words, point (3) states that every edge moves at most one level forward.

The figure below illustrates this concept: for one network we show two possible layerings and something that looks like a layering but is not:



Exercise 10.4. Suppose the network (G, s, t, c) has a k -layering. Show that $\text{dist}(s, t) \geq k$. That is, every s - t -path in G has at least k edges.

Exercise 10.5. Conversely, suppose $\text{dist}(s, t) = k$. Show that (G, s, t, c) has a k -layering.

Let (G, s, t, c) be a flow network and V_0, \dots, V_k a k -layering. We call this layering *optimal* if $\text{dist}_G(s, t) = k$. Here, $\text{dist}_G(u, v)$ is the shortest-path distance from s to t (measured by number of edges). If there is no path from s to t , we set $\text{dist}_G(s, t) = \infty$. In this case, no layering is optimal. For example, the 3-layering in the above figure is optimal, but the 1-layering in the middle of the above figure is not. Let us explore how layerings and the Ford-Fulkerson Method interact.

Exercise 10.6. Let (G, s, t, c) be a flow network and V_0, V_1, \dots, V_k be an optimal layering (that is, $k = \text{dist}_G(s, t)$). Let p be a path from s to t of length k . Suppose we route some flow f along p (of some value $c_{\min} > 0$) and let (G_f, s, t, c_f) be the residual network. Show that V_0, V_1, \dots, V_k is a layering of (G_f, s, t, c_f) , too. Obviously, condition (1) and (2) in the definition of k -layerings still hold, so you only have to check condition (3).

Exercise 10.7. Show that every network (G, s, t, c) has an optimal layering, provided there is a path from s to t .

Exercise 10.8. Imagine we are in some iteration of the while-loop of the Edmonds-Karp algorithm. Let V_0, \dots, V_k be an optimal layering of (G, s, t, c) . Show that after at most m iterations of the while-loop, V_0, \dots, V_k ceases to be an optimal layering. **Remark.** Note that it is the *network* that changes from iteration to iteration of the while-loop, not the partition V_0, \dots, V_k . We consider the partition V_0, \dots, V_k to be fixed in this exercise.

Exercise 10.9. Show that the Edmonds-Karp algorithm terminates after $n \cdot m$ iterations of the while-loop. **Hint.** Initially, compute an optimal k -layering (which?). Then keep this layering as long as its optimal. Once it ceases to be optimal, compute a new optimal layering. Note that the Edmonds-Karp algorithm does not actually need to compute any layering. It's us who compute it to show that $n \cdot m$ bound on the number of iterations.

Exercise 10.10. Show that every network has a maximum flow f . That is, a flow f such that $\text{val}(f) \geq \text{val}(f')$ for every flow f' . **Remark.** This sounds obvious but it is not. In fact, there might be an infinite sequence of flows f_1, f_2, f_3, \dots of increasing value that does not reach any maximum. Use the previous exercises!