Slide 1: Problem Introduction + Impact + User Breakdown

THE PROBLEM: GROUP ORDERING IS CHAOTIC

- **The Endless Debate:** 73% of groups take 15+ minutes just to decide WHERE to order from.
- **Forgotten Preferences:** Dietary restrictions get overlooked, leading to wasted food & frustration.
- **The Budget Mismatch:** Different budgets create awkward situations, with some members overpaying
- **The Default Dictator:** One person takes over, resulting in suboptimal choices for the rest.

HYPOTHESES & ASSUMPTIONS

- **H1: Friction Reduction:** AI-mediated group ordering will reduce decision time by 70%+
- **H2: Consensus Increase:** Transparent AI reasoning will increase satisfaction from 55% to 85%+
- **H3: Business Value:** Smart group ordering will increase AOV by 25-35% vs individual orders

BUSINESS & USER IMPACT METRICS

Metric	Current State	Problem Impact
Group order abandonment	~40%	Lower Average Order Value (AOV)
Average decision time	15-25 min	Ordering from safe, repetitive choices
Member satisfaction	~55%	At least 1 member is unhappy with choice
Repeat group orders	2.3x/month	Far below potential due to friction

USER SEGMENTS BREAKDOWN

Segment	TAM Share	Pain Level	Key Scenario
Office Teams	35%	High	Daily lunches for 4-8 people with diverse tastes
Friend Groups	40%	Medium-High	Weekend hangouts, parties, movie nights
Families	20%	Medium	Dinners with generational preference gaps
PG/Hostel	5%	High	Budget-conscious students splitting food bills

Slide 2: Why GenAI?

WHY GENERATIVE AI? (TRADITIONAL VS GENAI APPROACH)

Capability	Traditional Rules-Based Systems	Generative AI Agent Approach
Preference Capture	Fixed buttons/dropdowns. Cannot parse custom details.	Natural language: 'I want something spicy but not too heavy'
Dietary Constraints	Strict binary tags (Veg/Non-veg). Ignores preferences.	Context-aware: 'No onion-garlic, but dairy cheese is okay'
Consensus Building	Standard majority vote or dictatorship. Fails to find compromise.	Intelligent optimization: weighs constraints, finds common ground
Explaining Selection	Zero explanation. Users don't trust the recommendation.	Transparent: 'Rahul gets Biryani, Priya gets Veg. Selected: Empire'
Conflict Resolution	No resolution. Leads to order abandonment.	AI mediator suggests compromises and options with reasoning

WHY TRADITIONAL APPROACHES FAIL

THE GENERATIVE AI ADVANTAGE

- **Rule-based limits:** Fails on complex phrases, like cravings, and time-of-day contexts.
- **Multi-modal understanding:** Fuses text, past orders, comfort food'
- **Filtering limits:** Collaborative filters work for individuals, not dynamic groups.
- **Natural conversation:** Each member chats naturally with AI instead of filling forms.
- **Voting friction:** Standard voting creates losers, which leads to group friction.
- **Weighted consensus:** Weighs dietary needs as hard constraints, budgets as soft ones.
- **Static form fatigue:** Surveys/forms add severe UX friction, reducing conversion.
- **Transparent Trust:** Provides clear reasoning, increasing group buy-in.

Slide 3: User Segments + Solution Overview

TARGET USER SEGMENTS

Our AI-powered Group Ordering experience completely redesigns the ordering lifecycle.

- **Office Lunch Groups (35% share):** 4-8 colleagues ordering daily. Pain: Rotating selector duties, repetitive restaurant lists. Need: Dynamic variety, speed.
- **Friend Groups (40% share):** 3-6 friends ordering on weekends. Pain: Lengthy debates, WhatsApp group spam, food FOMO. Need: Interactive, social ordering.
- **Families (20% share):** 3-5 multi-generation members. Pain: Strict health/diet vs kids' cravings.

HIGH-LEVEL SOLUTION ARCHITECTURE

1. CREATE GROUP
Host sets group name and target per-person budget.

2. COLLECT PREFERENCES
AI initiates quick natural language chat loops.

3. AI CONSENSUS
Algorithms score menu options and resolve preferences.

4. RANKED CHOICES
AI presents top 3 compatible restaurants with reasoning.

5. OPTIMIZED CART & SPLIT
Auto-calculates cart items and splits the bill.

CORE PRODUCT INSIGHT

"The best group order isn't the one everyone loves - it is the one that no one hates. AI optimizes to minimize friction rather than maximize individual bias."

Slide 4: Solution Deep Dive

CORE USER FLOW

1. Create Group [illegible]	-->	2. Add Members	-->	3. AI Collects Prefs	-->	4. AI Consensus	-->	5. Cart / Split

PRODUCT EXPERIENCE & AI INTERACTION LAYER

KEY WORKFLOWS & FEATURES

- [illegible] their cravings naturally.
- [illegible] out incompatible venues.
- [illegible] matching a kebab craving and a vegetarian craving).
- **Flexible Bill-Splitting:** Splits totals transparently, outlining individual contributions directly on the receipt.

Slide 5: Success Metrics & Business Goals

PRIMARY KEY PERFORMANCE INDICATORS (KPIS)

Metric	Current Baseline	Target (3m)	Business Impact
Group Order AOV	Rs. 650	Rs. 850 (+31%)	Higher ticket size & revenue growth
Decision Time	18 min avg	4 min avg (-78%)	Lower funnel abandonment
Order Frequency	2.3x/month	4.1x/month	Higher customer lifetime value
Member Satisfaction	55%	88%	Increased NPS and product virality
Funnel Abandonment	40%	12% (-70%)	Higher checkout conversions

SECONDARY METRICS

- **Recommendation Acceptance:** Target >75% of recommendations accepted.
- **Invite Link Conversion Rate:** Aim for >50% join-rate for group invite links.
- **Equal-Split Payment Completion:** Target split bill payments completed within 5 mins.

REVENUE GENERATION STRATEGY

- **AOV uplift:** Consolidation of individual carts into a single larger group order.
- **Sponsor Ads:** Sponsored placements for restaurants matching the AI consensus.
- **Subscription:** Include AI group features inside 'Swiggy One' to drive renewals.

Slide 6: Pitfalls + Workarounds

RISKS, MITIGATIONS & SCALABILITY SAFETY NETS

Risk Concern	Risk Level	Mitigation Strategy	Technical Workaround
AI Hallucinations	**High**	Constrain recommendations strictly to active menus.	API-bound validation schema filters out any non-menu items.
Privacy & Consent	**Medium**	Keep restriction data local; do not sell context profiles.	Data encryption at rest. Automatic logs wipe out after checkout.
Response Latency	**Medium**	Keep latency low. Streaming responses hide delays.	Pre-fetch compatibility metrics; run consensus query asynchronously.
User Trust Barriers	**Medium**	Always surface the reasoning behind recommendations.	Surfaces a 'Why this?' breakdown mapping each member's needs.
Recommendation Bias	**Medium**	Audit scoring weights to prevent brand favoritism.	Equally weights all compatible restaurants before sponsored ads.
Adoption Friction	Low	Provide single-click guest ordering via web link.	Host creates group; members join on web without app downloads.

DEFENSE-IN-DEPTH SYSTEM WORKAROUND

- **Layer 1 (AI Hard boundaries):** Strict parsing constraints ensure the AI cannot output arbitrary recommendations.
- **Layer 2 (User Overrides):** Host has final say - any AI recommendation can be overridden or changed.
- **Layer 3 (Feedback Loops):** Post-order rating logs feed back to refine restaurant suggestions.