

# **Dynamo Feasibility**

## Analysis Refinement

# Revit

## Site and Massing Study

- 1: Site/Controls
- 2: Building Massing
- 3: Design Options
- 4: Scheduling Areas
- 5: Shadow Diagrams



aussie BIM guru

# Dynamo

## Site Analysis

6: Shadow diagram setup

7: Surface Analysis Grids

8: View Analysis

9: Sun Hour Analysis

**10: Analysis Refinement**



aussie BIM guru


# Power BI

Analysis and reporting

## 11: Power BI Report




aussie BIM guru




aussie BIM guru

# Solar Analysis




aussie BIM guru





aussie BIM guru




Name	Visibility	Projection/Surface	
		Lines	Patterns
Detecors_Sun0	<input checked="" type="checkbox"/>		
Detecors_Sun1	<input checked="" type="checkbox"/>		
Detecors_Sun2	<input checked="" type="checkbox"/>		
Detecors_Sun3	<input checked="" type="checkbox"/>		
Detecors_Sun4	<input checked="" type="checkbox"/>		
Detecors_Sun5	<input checked="" type="checkbox"/>		
Detecors_Sun6	<input checked="" type="checkbox"/>		
Detecors_Sun7	<input checked="" type="checkbox"/>		

<SH By face>			
A	B	C	D
ABG_Data_SunHour	ABG_Data_Count2	ABG_Data_Area2	%
East Tower			
0	3	38 m²	0.30%
1	2	26 m²	0.20%
2	23	294 m²	2.33%
3	180	2302 m²	18.22%
	208	2660 m²	21.05%
North Tower			
0	93	1115 m²	9.41%
1	30	360 m²	3.04%
2	50	600 m²	5.06%
3	10	120 m²	1.01%
4	3	36 m²	0.30%
5	1	12 m²	0.10%
7	99	1187 m²	10.02%
	286	3429 m²	28.95%
South Tower			
0	286	3390 m²	28.95%
	286	3390 m²	28.95%
West Tower			
3	105	1259 m²	10.63%
4	103	1235 m²	10.43%
	208	2494 m²	21.05%
988	988	11973 m²	100.00%



aussie BIM guru





aussie BIM guru



aussie BIM guru

# Sun Hours – Huh?

## Sydney requirement under SEPP65

*Living rooms and private open spaces of at least 70% of apartments in a building receive a minimum of 2 hours direct sunlight between 9 am and 3 pm at mid winter in the Sydney Metropolitan Area and in the Newcastle and Wollongong local government areas. (Objective 4A-1, p.79).*

*(Also a maximum of 15% receive 0 hours)*



# Important to note

SEPP65 requires **15 minutes** of continuous exposure at minimum


**We will refine the script to  
measure 15 minute continuity**




aussie BIM guru

# Interval detection

2 True = 15 minutes



3 True = 30 minutes



aussie BIM guru



# Interval detection

N consecutive Trues

=  $N-1 * 15$  minutes of sunlight

$SUM/4$  = Sunlight hours



# Grasshopper/Rhino

Is best for detailed analysis

Great guide here;

<https://parametricmonkey.com/2015/09/07/sepp65-solar-analysis/>



aussie BIM guru

# Weather files

<https://energyplus.net/weather>

## Weather Search

### Search Results for: sydney

Your search matched 4 results.

Sydney 717070 (CWEK)
NSW Sydney 947670 (IWEK)
NSW Sydney 947680 (RMY)
NSW Mascot-Sydney Airport 947670 (RMY)

[Search again](#)

## Weather Data Download

Click on a file to download.

ddy

epw 

stat

Download All




aussie BIM guru

# Ladybug (0.2.1)

## Download from package manager

### ladybug-dynamo


Ladybug-dynamo is the ladybug plugin for Dynamo to import and visualize weather data from and EnergyPlus Weather file (EPW).




aussie BIM guru

# Custom Nodes

## Ladybug



## Zebra





# Versioning

## Need Dynamo 2.X!



aussie BIM guru

A faint, light gray background graphic consisting of a network of interconnected dots and lines, resembling a molecular structure or a complex web, extending across the right side of the slide.

# Without further ado...

## Let's get started...



aussie BIM guru

# Next: Part 11

## Power BI



aussie BIM guru

# Prepare some XCL data

Mass floor schedule



Apartment counts/\$

Sun hours by floor

Building section



aussie BIM guru



# **Dynamo Feasibility**

## Analysis Refinement