

## Spacers

For information about spacers and standoffs, see [page 3228](#).



Technical drawings and 3-D models  
available for products with this symbol.

### 18-8 Stainless Steel Unthreaded Spacers



Also called clearance spacers. They have an OD tolerance of  $\pm 0.005$ ", ID tolerance of  $+0.01$ ", and length tolerance



For technical drawings and 3-D models, click on a part number.

Screw Size	ID
No. 0	0.064"
No. 2	0.09"
No. 4	0.115"
No. 6	0.14"
No. 8	0.166"
No. 10	0.192"
No. 12	0.218"
1/4"	0.252"
5/16"	0.315"
3/8"	0.38"
1/2"	0.505"
5/8"	0.63"
3/4"	0.755"
1"	1.005"

Available Screw Sizes	Lg.		Each	
			1-9	10-Up
1/8" OD				
No. 0, No. 2	1/8"	<a href="#">92320A977</a>	\$1.86	\$1.57
No. 0, No. 2	3/16"	<a href="#">92320A978</a>	1.86	1.57
No. 0, No. 2	1/4"	<a href="#">92320A979</a>	1.86	1.57
No. 0, No. 2	5/16"	<a href="#">92320A980</a>	2.10	1.77
No. 0, No. 2	3/8"	<a href="#">92320A981</a>	2.15	1.83
3/16" OD				
No. 2, No. 4	1/8"	<a href="#">92320A194</a>	1.56	1.32
No. 2, No. 4	5/32"	<a href="#">92320A103</a>	1.63	1.38
No. 2, No. 4	3/16"	<a href="#">92320A195</a>	1.61	1.35
No. 2, No. 4	7/32"	<a href="#">92320A104</a>	1.63	1.38
No. 2, No. 4	1/4"	<a href="#">92320A196</a>	1.63	1.38
No. 2, No. 4	9/32"	<a href="#">92320A105</a>	1.63	1.38
No. 2, No. 4	5/16"	<a href="#">92320A107</a>	1.63	1.38