

## Socket Head Cap Screws

For information about hex sizes and head dimensions, see [page 3079](#).

**CAD** Technical drawings and 3-D models available for products with this symbol.

### Stainless Steel



Fully Threaded



Partially Threaded

Our stainless steel socket head cap screws have a Class 3A thread fit, a minimum Rockwell hardness of B70, and minimum tensile strength of 70,000 psi. Screw length is measured from under the head.

**Type 316 stainless steel** provides better corrosion resistance than 18-8 stainless steel and contains molybdenum, which increases corrosion resistance to chlorides and sulfates. May be mildly magnetic.

**18-8 stainless steel** offers excellent corrosion resistance and may be mildly magnetic.

Lg.	Pkg. Qty.		Per Pkg.
<b>Type 316 Stainless Steel</b>			
<b>2-56</b>			
3/16"	25	<a href="#">92185A073 *</a>	\$3.78
1/4"	25	<a href="#">92185A077 *</a>	6.98
5/16"	25	<a href="#">92185A078 *</a>	3.23
3/8"	25	<a href="#">92185A079 *</a>	7.41
7/16"	25	<a href="#">92185A081 *</a>	3.49
1/2"	25	<a href="#">92185A083 *</a>	3.63
9/16"	25	<a href="#">92185A086 *</a>	3.69
5/8"	50	<a href="#">92185A089 *</a>	7.70
3/4"	50	<a href="#">92185A092</a>	8.28
7/8"	25	<a href="#">92185A095</a>	4.40
<b>4-40</b>			
3/16"	25	<a href="#">92185A105 *</a>	8.60
1/4"	50	<a href="#">92185A106 *</a>	5.37
5/16"	50	<a href="#">92185A107 *</a>	6.01
3/8"	50	<a href="#">92185A108 *</a>	6.74
7/16"	50	<a href="#">92185A109 *</a>	7.20
1/2"	50	<a href="#">92185A110 *</a>	8.05