

Spacers

For information about spacers and standoffs, see [page 3228](#).



18-8 Stainless Steel Unthreaded Spacers



Also called clearance spacers. They have an OD tolerance of ± 0.005 ", ID tolerance of $+0.01$ ", and length tolerance

For technical drawings and 3-D models, click on a part number.

Screw Size	ID
No. 0	0.064"
No. 2	0.09"
No. 4	0.115"
No. 6	0.14"
No. 8	0.166"
No. 10	0.192"
No. 12	0.218"
1/4"	0.252"
5/16"	0.315"
3/8"	0.38"
1/2"	0.505"
5/8"	0.63"
3/4"	0.755"
1"	1.005"

Lg.	Available Screw Sizes		Each	
			1-9	10-Up
1/8" OD				
1/8"	No. 0, No. 2	92320A977	\$1.86	\$1.57
3/16"	No. 0, No. 2	92320A978	1.86	1.57
1/4"	No. 0, No. 2	92320A979	1.86	1.57
5/16"	No. 0, No. 2	92320A980	2.10	1.77
3/8"	No. 0, No. 2	92320A981	2.15	1.83
3/16" OD				
1/8"	No. 2, No. 4	92320A194	1.56	1.32
5/32"	No. 2, No. 4	92320A103	1.63	1.38
3/16"	No. 2, No. 4	92320A195	1.61	1.35
7/32"	No. 2, No. 4	92320A104	1.63	1.38
1/4"	No. 2, No. 4	92320A196	1.63	1.38
9/32"	No. 2, No. 4	92320A105	1.63	1.38
5/16"	No. 2, No. 4	92320A107	1.63	1.38