To	:									

Date: Jun. 28, 2017

Document No.: JDG010000624-02

SPECIFICATIONS

Product Name

LPM009M360A

Approval Signature
Accepted by:
Date:

Japan Display Inc.

Proposed by:

				Issued No.	JDG0100	000624		
				Revision	02			
Revision History			History	Product Name	LPM009M360A			
				Customer Part No.				
Date/Rev.	Contents of char			ge	Reasons	Remarks		
Jan.10,.2017 Rev.01	-	-	3.6 AC CHRACTERISTICS tsSI (UNIT): usec ⇒ nsec		-	LPM009M360A (200067201)		
Jun.28, 2017 Rev.02	С	P.7			Correction of mistake	LPM009M360A (200067201)		
				70				
		A						
(C): Change	 d ((A): App	ended (D): De	eleted (F): F	illed in			



1. BASIC SPECIFICATIONS	······ <i>'</i>
1.1 STRUCTURES	
1.2 BLOCK DIAGRAM	
1.3 DISPLAY ADDRESS MAP AND PIXEL LAYOUT	
1.4 I/O PINS	
2. ABSOLUTE MAXIMUM RATINGS	
3. OPERATING CONDITIONS	
3.1 POWER SUPPLY VOLTAGE AND INPUT SIGNALS	6
4. ELECTRICAL CHARACTERISTICS	
4.1 POWER CONSUMPTION	
4.2 INPUT SIGNAL CHRACTERISTICS	.
4.3 POWER ON/OFF SEQUENCE	
5. MODE	9
5.1 MODE TABLE	
5.2 Mode chart	
6. TIMING CHART AND DETAILS OF MODE	
6.1 SINGLE LINE UPDATE MODE (3BIT-DATA MODE)	
6.2 MULTIPLE LINES UPDATE MODE (3BIT-DATA MODE)	
6.3 SINGLE LINE UPDATE MODE (1BIT-DATA MODE)	
6.5 SINGLE LINE UPDATE MODE (4BIT-DATA MODE)	
6.6 MULTIPLE LINES UPDATE MODE (4BIT-DATA MODE)	
6.7 No-UPDATE MODE	
6.8 ALL CLEAR MODE	
6.9 DISPLAY BLINKING COLOR MODE	
6.10 DISPLAY COLOR INVERSION MODE 7. COM INVERSION	
7.1 EXTCOMIN SIGNAL	
8. GATE ADDRESS TABLE	2′
9. OPTICAL SPECIFICATION	22
9.1 OPTICAL CHARACTERISTICS	22
9.2 DEFINITION AND CONDITION OF OPTICAL CHARACTERISTICS	
10. INSPECTION	20
10.1 QUALITY STANDARD	26
10.2. DISPLAY APPEARANCE STANDARDS	
10.3. EXTERNAL APPEARANCE STANDARDS	
11. RELIABILITY TEST	
11.1 CONDITIONS OF RELIABILITY AND MECHANICAL TEST	
11.2 CRITERIA FOR JUDGEMENT	
12. DESIGNATION OF LOT MARK	
12.1 LOT MARK	3 ²
13. PACKING SPECIFICATIONS	32
13.1 INNER CARTON	32
12.2 MARTED CADTON	0.0



CONTENTS

14. LCD MODULE USAGE AND PRECAUTIONS	
14.1 HANDLING	
14.2 DESIGN OF APPLICATION	35
14.3 DISPLAY CHARACTERISTICS	35
14.4 KEEPING THE PRODUCTS	
14.5 DISPOSAL	36
14.6 OTHERS	36
15 OUTLINE DRAWING	37



Global LCD Panel Exchange Center

Product Number:	LPM009M360A	Revision Number: 02	Page: 1/38

i ioduct indilibet.	LI IVIOUSIVISUUA	INCVISION NUMBER OF	ı aye.	1/50

1.1 STRUCTURES

1. BASIC SPECIFICATIONS

No.	FACTOR	SPECIFICATIONS	UNIT
1	LCD structure	LTPS (Memory in Pixel type)	-
2	Outward *(1)	12.455(W) x 24.01(H) x 0.844(D) (*1-1)	mm
3	Weight	Approx. 0.5	g
4	Screen size	21.59 (0.850inch)	mm
5	Resolution	72(H) x 144(V)	dot
6	Dot pitch (Horizontal x Vertical)	0.0447(H) x 0.1341(V)	mm
7	Dot layout	RGB stripe	-
8	Liquid crystal mode	ECB normally black (Reflective type)	_
9	Polarizer	Hard Coat type (*Pencil Hardness : 2H)	-

Note)

(*1-1) Excluding FPC and part of protruding. See attached drawing for details.




Product Number:	LPM009M360A	Revision Number: 02	Page: 2/38

1.2 BLOCK DIAGRAM

The block diagram of a panel is shown below.


1.2.1 Pin layout and Internal circuit





Product Number: LPM009M360A Revision Number: 02 Page: 3/38

1.3 DISPLAY ADDRESS MAP AND PIXEL LAYOUT



Pixels indicated "RGB" are displayed

Number of active pixels: 72 x RGB x 144 dot

(Viewing in front of a LCD panel) H1...72 X RGB: Horizontal line

V1...144: Vertical line



1.4 I/O PINS

Product Number:	LPM009M360A	Revision Number: 02	Page: 4/38

Product Number:	LPM009M360A	Revision Number: 02	Page: 4/38

PIN	SYMBOL	TYPE	DESCRIPTION	REMARK
1	SCLK	I	Serial Clock Signal	
2	SI	I	Serial Input Signal	
3	SCS	I	Chip Select Signal	
4	EXTCOMIN	I	COM Inversion Polarity Input	
5	DISP	I	Display ON/OFF Switching signal	(*1-2)
6	VDD	Р	Power Supply	
7	NC	NC	Not connected to the LCD	
8	VSS	I	Ground	

P: Power supply NC: Not connected I: Input

Note)

(*1-2) ON/OFF switching is only for display. Data memory is kept at the time of ON/OFF.

"H": Data memory is displayed.

"L": Black color is displayed with data memory kept.

External circuit example

	symbol
1	SCLK
2	SI
3	scs
4	EXTCOMIN
5	DISP
6	VDD
7	NC
8	VSS
	3 4 5

C1: 0.1uF/B/10V C2: 1.0uF/B/10V Global LCD Panel Exchange Center

Product Number:	LPM009M360A	Revision Number: 02	Page: 5/38

2. ABSOLUTE MAXIMUM RATINGS

(VSS=0V)

PARAMETER	RATINGS	UNIT	REMARKS
Power supply voltage	3.6	V	
Input control signal voltage	0 to 3.6	V	(*2-1)
Operating temperature range (LCD panel surface)	-20 to +70	°C	(*2-2)
Storage temperature range	-30 to +80	°C	(*2-2)

Note)

(*2-1) SCLK, SI, SCS, EXTCOMIN, DISP

(*2-1): Maximum humidity is defined as follows:

Ta≦40°C: 85%RH Max.

Ta> 40°C: Absolute humidity needs to be equal or less than the numeric value at the condition of Ta=40°C, 85%RH.

Don't condense dew.



Product Number: LPM009M360A	Revision Number: 02	Page: 6/38
-----------------------------	---------------------	------------

3. OPERATING CONDITIONS

3.1 POWER SUPPLY VOLTAGE AND INPUT SIGNALS

PARAMETER	SYMBOL	Min.	Тур.	Max.	UNIT	REMARK
	VDD	2.7	3.0	3.3	V	
Power supply voltage	VSS	-	0	-	V	
Input signal voltage High	VIH	VDD-0.1	3.0	VDD	V	
Input signal voltage Low	VIL	VSS	VSS	VSS+0.1	V	(*3-1)

Note)

(*3-1) SCLK, SI, SCS, EXTCOMIN, DISP

4. ELECTRICAL CHARACTERISTICS

4.1 POWER CONSUMPTION

* Ta=25°C, Driving Condition: VDD=3.0V, VIH=3.0V, VIL=0V, Data update frequency=1Hz, COM frequency=0.5Hz

Mode	Display	Min.	Тур.	Max.	UNIT	Remark
No-update mode	White raster	-	2	60	uW	
Data-update mode	White raster	-	7	67	uW	3bit all lines data



Product Number:	LPM009M360A	Revision Number: 02	Page: 7/38


4.2 INPUT SIGNAL CHRACTERISTICS

* Ta=25°C, Driving Condition: VDD=3.0V, VIH=3.0V, VIL=0V

PARAMETER	SYMBOL	Min.	Тур.	Max.	UNIT	REMARK
Clock frequency	fSCLK	-	1.00	2.00	MHz	(*4-1)
COM frequency	fCOM	0.50	-	70.00	Hz	(*4-2)
SCS rising time	trSCS	-	-	50	nsec	
SCS falling time	tfSCS	-	-	50	nsec	
SCS Low width	twSCSL	6.0	-	-	usec	
SCS settling time	tsSCS	6.0	-	-	usec	
SCS holding time	thSCS	2.0	-	-	usec	(*4-3)
SI rising time	trSI	-	-	50	nsec	
SI falling time	tfSI	-	-	50	nsec	
SI settling time	tsSI	200	450	-	nsec	
SI holding time	thSI	250	500	-	nsec	
SCLK rising time	trSCLK	-	-	50	nsec	
SCLK falling time	tfSCLK	-	-	50	nsec	
SCLK High width	twSCLKH	250	500	-	nsec	(*4-4)
SCLK Low width	twSCLKL	250	500	- 1	nsec	(*4-4)
EXTCOMIN frequency	fEXTCOMIN	1.00	-	140.00	Hz	(*4-2)
EXTCOMIN rising time	trEXTCOMIN	-	-	50	nsec	
EXTCOMIN falling time	tfEXTCOMIN	-	-	50	nsec	
EXTCOMIN High width	twEXTCOMIN	2.0	-	-	usec	
DISP rising time	trDISP	-	-	50	nsec	
DISP falling time	tfDISP	-	-)	50	nsec	

Note)


- (*4-1) Please note that Max. fSCLK may be lowered when VDD fall than 3.0V at a low temperature.
- (*4-2) COM frequency should be around 60 Hz (EXTCOMIN frequency: around 120Hz) for transmissive mode.
- (*4-3) In case of data update mode in transmissive mode, thSCS should be 50us or less.
- (*4-4) twSCLKH and twSCLKL should be approximately the same length, if possible





Product Number:	LPM009M360A	Revision Number: 02	Page: 8/38
i ioduct indilibei.	LI MOOSIMSOOA	INCVISION NUMBER OF	1 age. 0/30

4.3 POWER ON/OFF SEQUENCE



[On sequence]

T1: Power supply rising time. (Depends on external power supply)

T2: Pixel memory initialization. 1ms or more initialize with M2 (all clear flag).

T3: Release time for internal latch circuits. 30us or more

T4: COM polarity initialization time. 30us or more

[Normal operation]

Duration of normal operation

[Off sequence]

T5: Pixel memory initialization. Same as T2.

T6: COM and latch circuits initialization. 30us or more

T7: Power supply falling time. (Depends on external power supply)

Note)

Refer to the timing chart and electrical characteristics for details.

(*4-5) It is allowed to replace T3 and T4 mutually.

In case of starting EXTCOMIN before rising DISP, EXTCOMIN is ignored during DISP="L".

Also, it is allowed to start simultaneously DISP and EXTCOMIN.

In that case, need 100us or more (200us or less) before normal operation.

(*4-6) Pixel memory initialization.

Use M2 (all clear flag: refer to 6.8),



5. MODE

5.1 MODE TABLE

Unassigned bit and AG9-8: No care, it can be H or L (L is Recommended) Mode select M2 M3 M4 M5 AG9 AG8 AG7 AG6 AG5 AG4 AG3 AG2 AG1 AG0 M0 M1 Mode

\mathbf{L}	-	\mathbf{L}	\mathbf{L}	-	-	-	-	-	-	-	-	-	-	-	-	No-Update
\mathbf{L}	-	L	Н	L/H	L/H	-	-	-	-	-	-	-	-	-	-	Blinking
L	-	Н	L/H	L/H	L/H	-	-	-	-	-	-	-	-	-	-	All Clear
Н	_	L	L/H	L/H	_	AG9	AG8	AG7	AG6	AG5	AG4	AG3	AG2	AG1	AG0	Data-Update
Н	-	Н	L/H	L/H	L/H	-	-	-	-	-	-	-	-	-	-	No-Update
						$\overline{}$										

Mode (6bit)

Gate Address (10bit)

Function table

M0=L or M0=H/M2=H


Mode	M3	M4	M5
Blinking OFF	L	-	-
Blink Black	Н	L	\mathbf{L}
Blink White	Н	Н	\mathbf{L}
Blink Inversion	Н	-	Н
		l	! !-

M0=H/M2=L

Mode	M3	M4	M5
3 bit data input	\mathbf{L}	\mathbf{L}	-
1bit data input	\mathbf{L}	Н	-
4bit data input	Н	-	-

Unassigned bit: No care, it can be H or L (L is Recommended)

5.2 MODE CHART



(*) Pixel memories are maintained

Japan Display Inc.



Product Number: LPM009M360A	Revision Number: 02	Page: 10/38
-----------------------------	---------------------	-------------


6. TIMING CHART AND DETAILS OF MODE

6.1 SINGLE LINE UPDATE MODE (3BIT-DATA MODE)

Updates data of only one specified line.

Mode table

MO	M1	M2	M3	M4	M5
H	-	L	L	L	-



M0: Mode flag. Set "H", data update mode.

M1: Invalid data, it can be "H" or "L".

M2: All clear flag. Set "L", data update mode.

M3-M4: Data-bit control flag. In case of M3="L" and M4="L", 3bit-data mode.

M5: Invalid data, it can be "H" or "L".

AG9-AG0: Gate line address (10bit), refer to the Gate line address table.

Data: Pixel memory data. In case of "L", pixel is black.

In case of 3bit-data mode,

input serially the pixel data in the order of Red-Green-Blue (3bit).


n: Number of horizontal line, refer to the Display address map and Pixel layout.

Dummy data: It can be "H" or "L".

Need transfer period which is 16 clocks after the last data.



6.2 MULTIPLE LINES UPDATE MODE (3BIT-DATA MODE)



M0: Mode flag. Set "H", data update mode.

M1: Invalid data, it can be "H" or "L".

M2: All clear flag. Set "L", data update mode.

M3-M4: Data-bit control flag. In case of M3="L" and M4="L", 3bit-data mode.

M5: Invalid data, it can be "H" or "L".

AG9-AG0: Gate line address (10bit), refer to the Gate line address table.

Data: Pixel memory data. In case of "L", pixel is black.

In case of 3bit-data mode,

input serially the pixel data in the order of Red-Green-Blue (3bit).

n: Number of horizontal line, refer to the Display address map and Pixel layout.

Dummy data: It can be "H" or "L".

Input data continuously.

m: Number of vertical line, refer to the Display address map and Pixel layout.


Need transfer period which is 6 clocks between the gate line and the next gate line.

Need transfer period which is 16 clocks after the last data.





6.3 SINGLE LINE UPDATE MODE (1BIT-DATA MODE)



M0: Mode flag. Set "H", data update mode.

M1: Invalid data, it can be "H" or "L".

M2: All clear flag. Set "L", data update mode.

M3-M4: Data-bit control flag. In case of M3="L" and M4="H", 1bit-data mode.

M5: Invalid data, it can be "H" or "L".

AG9-AG0: Gate line address (10bit), refer to the Gate line address table.

Data: Pixel memory data. In case of "L", pixel is black.

In case of 1bit-data mode, input the pixel data "H" or "L" (1bit).

Pixel memories of red, green and blue are written the same data.

n: Number of horizontal line, refer to the Display address map and Pixel layout.


Dummy data: It can be "H" or "L".

Need transfer period which is 16 clocks after the last data.



LPM009M360A Revision Number: 02 13/38 **Product Number:** Page:

6.4 MULTIPLE LINES UPDATE MODE (1BIT-DATA MODE)



M0: Mode flag. Set "H", data update mode.

M1: Invalid data, it can be "H" or "L".

M2: All clear flag. Set "L", data update mode.

M3-M4: Data-bit control flag. In case of M3="L" and M4="H", 1bit-data mode.

M5: Invalid data, it can be "H" or "L".

AG9-AG0: Gate line address (10bit), refer to the Gate line address table.

Data: Pixel memory data. In case of "L", pixel is black.

In case of 1bit-data mode, input the pixel data "H" or "L" (1bit).

Pixel memories of red, green and blue are written the same data.

n: Number of horizontal line, refer to the Display address map and Pixel layout.

Dummy data: It can be "H" or "L".

Input data continuously.

m: Number of vertical line, refer to the Display address map and Pixel layout.


Need transfer period which is 6 clocks between the gate line and the next gate line.

Need transfer period which is 16 clocks after the last data.



Product Number: LPM009M360A Revision Number: 02 Page: 14/38

6.5 SINGLE LINE UPDATE MODE (4BIT-DATA MODE)



M0: Mode flag. Set "H", data update mode.

M1: Invalid data, it can be "H" or "L".

M2: All clear flag. Set "L", data update mode.

M3: Data-bit control flag. In case of M3="H", 4bit-data mode.

M4-M5: Invalid data, it can be "H" or "L".

AG9-AG0: Gate line address (10bit), refer to the Gate line address table.

Data: Pixel memory data. In case of "L", pixel is black.

In case of 4bit-data mode,

input serially the pixel data in the order of Red-Green-Blue-Dummy (4bit).

Dummy data (DUM) can be "H" or "L".

n: Number of horizontal line, refer to the Display address map and Pixel layout.


Dummy data: It can be "H" or "L".

Need transfer period which is 16 clocks after the last data.



Product Number: LPM009M360A Revision Number: 02 Page: 15/38

6.6 MULTIPLE LINES UPDATE MODE (4BIT-DATA MODE)



M0: Mode flag. Set "H", data update mode.

M1: Invalid data, it can be "H" or "L".

M2: All clear flag. Set "L", data update mode.

M3: Data-bit control flag. In case of M3="H", 4bit-data mode.

M4-M5: Invalid data, it can be "H" or "L".

AG9-AG0: Gate line address (10bit), refer to the Gate line address table.

Data: Pixel memory data. In case of "L", pixel is black.

In case of 4bit-data mode,

input serially the pixel data in the order of Red-Green-Blue-Dummy (4bit).

Dummy data (DUM) can be "H" or "L".

n: Number of horizontal line, refer to the Display address map and Pixel layout.

Dummy data: It can be "H" or "L".

Input data continuously.

m: Number of horizontal line, refer to the Display address map and Pixel layout.

Need transfer period which is 6 clocks between the gate line and the next gate line.

Need transfer period which is 16 clocks after the last data.




Product Number: LPM009M360A Revision Number: 02 Page: 16/38

6.7 NO-UPDATE MODE

Maintains memory internal data (current display).

Mode table

M0	M1	M2	М3	M4	M5
L	-	L	L	-	-
MO	M1	M2	M3	M4	M5
H	-	H	L	-	-



M0: Mode flag.

M1: Invalid data, it can be "H" or "L".

M2: All clear flag.

Set "L" or "H" to both M0 and M2, no-update mode.

M3: Blinking flag. In case of "L", no-update mode and display blinking mode is terminated. In case of "H", display blinking mode. Refer to 6.9 for details.


M4-M5: Invalid data, it can be "H" or "L".

Dummy data: It can be "H" or "L".



Product Number: LPM009M360A Revision Number: 02 Page: 17/38

6.8 ALL CLEAR MODE



M0: Mode flag. Set "L", no-update mode.

M1: Invalid data, it can be "H" or "L".

M2: All clear flag. Set "H", all clear mode.

M3: Blinking flag. In case of "L", display blinking mode is terminated.

In case of "H", display blinking mode. Refer to 6.9 for details.

M4-M5: Blinking mode flag. In case of M3="H", validate.

In case of M3="L", invalidate, it can be "H" or "L".

Dummy data: It can be "H" or "L".


M0, M2 flags are cleared by SCS="L", and M3-M4 flags are cleared by DISP="L".

Display gives priority to blinking flag (M3).



Product Number: LPM009M360A Revision Number: 02 Page: 18/38

6.9 DISPLAY BLINKING COLOR MODE



M0: Mode flag. Set "L", no-update mode.

M1: Invalid data, it can be "H" or "L".

M2: All clear flag. Set "L", no-update mode.

In case of "H", all clear mode. Refer to 6.8 for details.

M3: Blinking flag. In case of "H", display blinking mode and forcibly display blinking color.

In case of "L", no-update mode and display blinking mode is terminated.


M4: Blinking color flag. Apply to display blinking color.

In case of "H", display blinking color is white.

In case of "L", display blinking color is black.

M5: Blinking inversion flag. Set "L", blinking color mode.

Dummy data: It can be "H" or "L".




Blink display to alternate between normal display and display blinking mode.



Product Number: LPM009M360A Revision Number: 02 Page: 19/38

6.10 DISPLAY COLOR INVERSION MODE



M0: Mode flag. Set "L", no-update mode.

M1: Invalid data, it can be "H" or "L".

M2: All clear flag. Set "L", no-update mode.

In case of "H", all clear mode. Refer to the 6.8 for details.

M3: Blinking flag. In case of "H", display blinking mode and forcibly display color inversion.

In case of "L", no-update mode and display blinking mode is terminated.

M4: Blinking color flag. In case of M5="H", invalidate, it can be "H" or "L".

In case of M5="L", refer to 6.9 for details.


M5: Color inversion flag. Set "H", display color is inverted.

For example, "Red" is changed to "Cyan".

"Cyan" is complementally color of "Red".

Dummy data: It can be "H" or "L".

M0, M2 flags are cleared by SCS="L", and M3,M5 flags are cleared by DISP="L".




Blink display to alternate between normal display and display blinking mode.





7. COM INVERSION

7.1 EXTCOMIN SIGNAL



COM polarity inversion has been changed by the rising timing of EXTCOMIN.

COM polarity (positive or negative) is controlled by internal circuit.

(*7-1) The periods of positive and negative polarity should be same length as much as possible.

Product Number: LPM009M360A Revision Number: 02 Page: 21/38

8. GATE ADDRESS TABLE

LPM009M360A : Up to V144			
V AG	V 9 8 7 6 5 4 3 2 1 0	V 9 8 7 6 5 4 3 2 1 0	V AG
0 0 0 0 0 0 0 0 0 0 0		28 0 0 1 0 0 0 0 0 0 0 0	192 0 0 1 1 0 0 0 0 0
1 0 0 0 0 0 0 0 0 0 1		129 0 0 1 0 0 0 0 0 0 1	193 0 0 1 1 0 0 0 0 0 1
2 0 0 0 0 0 0 0 0 1 0	66 0 0 0 1 0 0 0 0 1 0 1	30 0 0 1 0 0 0 0 0 1 0	194 0 0 1 1 0 0 0 0 1 0
3 0 0 0 0 0 0 0 1 1		31 0 0 1 0 0 0 0 1 1	195 0 0 1 1 0 0 0 0 1 1
4 0 0 0 0 0 0 1 0 0 5 0 0 0 0 0 0 1 0 1		32 0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	197 0 0 1 1 0 0 0 1 0 0
6 0 0 0 0 0 0 0 1 1 0		34 0 0 1 0 0 0 0 1 1 0	198 0 0 1 1 0 0 0 1 0 1
7 0 0 0 0 0 0 0 1 1 1			199 0 0 1 1 0 0 0 1 1 1
8 0 0 0 0 0 0 1 0 0 0	72 0 0 0 1 0 0 1 0 0 1 0 0 1	36 0 0 1 0 0 0 0 1 0 0 0	200 0 0 1 1 0 0 0 1 0 0
9 0 0 0 0 0 0 1 0 0 1			201 0 0 1 1 0 0 1 0 0 1
10 0 0 0 0 0 1 0 1 0 11 0 0 0 0 0 1 0 1 1 1		38 0 0 1 0 0 0 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1	203 0 0 1 1 0 0 1 0 1 0
12 0 0 0 0 0 0 1 1 0 0		40 0 0 1 0 0 0 1 1 0 0	204 0 0 1 1 0 0 1 1 0 0
13 0 0 0 0 0 0 1 1 0 1			205 0 0 1 1 0 0 1 1 0 1
14 0 0 0 0 0 0 1 1 1 0		42 0 0 1 0 0 0 1 1 1 0	206 0 0 1 1 0 0 1 1 1 0 0
15 0 0 0 0 0 0 1 1 1 1			207 0 0 1 1 0 0 1 1 1 1
16 0 0 0 0 1 0 0 0 17 0 0 0 0 1 0 0 0 1		44 0 0 1 0 0 1 0	209 0 0 1 1 0 1 0 0 0 1
18 0 0 0 0 0 1 0 0 1	82 0 0 0 1 0 1 0 0 1 0 1		210 0 0 1 1 0 1 0 0 1 0
19 0 0 0 0 0 1 0 0 1 1			211 0 0 1 1 0 1 0 0 1 1
20 0 0 0 0 0 0 1 0 1 0 0	84 0 0 0 1 0 1 0 1 0 0 1	48 0 0 1 0 0 1 0 1 0 1 0 1	212 0 0 1 1 0 1 0 1 0 0
21 0 0 0 0 0 1 0 1 0 1			213 0 0 1 1 0 1 0 1 0 1
22 0 0 0 0 0 1 0 1 1 0 23 0 0 0 0 0 1 0 1 1 1	86 0 0 0 1 0 1 0 1 1 0 1 87 0 0 0 1 0 1 0 1 1 1 1 1		214 0 0 1 1 0 1 0 1 1 0 215 0 0 1 1 0 1 0 1 1 1
24 0 0 0 0 0 1 1 0 0	88 0 0 0 1 0 1 1 0 0 0		216 0 0 1 1 0 1 1 0 0
25 0 0 0 0 0 1 1 0 0 1	89 0 0 0 1 0 1 1 0 0 1	.53 0 0 1 0 0 1 1 0 0 1 2	217 0 0 1 1 0 1 1 0 0 1
26 0 0 0 0 0 1 1 0 1 0	90 0 0 0 1 0 1 1 0 1 0 1	54 0 0 1 0 0 1 1 0 1 0 1	218 0 0 1 1 0 1 0 1 0 1 0
27 0 0 0 0 0 1 1 0 1 1	91 0 0 0 1 0 1 1 0 1 1		219 0 0 1 1 0 1 1 0 1 1
28 0 0 0 0 0 1 1 1 0 0 29 0 0 0 0 1 1 1 1 0 1	92 0 0 0 1 0 1 1 1 0 0 1 93 0 0 0 1 0 1 1 1 0 1		220 0 0 1 1 0 1 1 0 0 221 0 0 1 1 0 1 1 1 0 1
30 0 0 0 0 0 1 1 1 1 0	94 0 0 0 1 0 1 1 1 0 1		222 0 0 1 1 0 1 1 1 1 0
31 0 0 0 0 0 1 1 1 1 1		59 0 0 1 0 0 1 1 1 1 1 2	223 0 0 1 1 0 1 1 1 1 1
32 0 0 0 0 1 0 0 0 0 0	96 0 0 0 1 1 0 0 0 0 0	60 0 0 1 0 1 0 1 0 0 0 0 0	224 0 0 1 1 1 0 0 0 0 0
33 0 0 0 0 1 0 0 0 1			225 0 0 1 1 1 0 0 0 0 1
34 0 0 0 0 1 0 0 0 1 0 35 0 0 0 0 1 0 0 0 1 1	98 0 0 0 1 1 0 0 0 1 0 99 0 0 0 1 1 0 0 0 1 1		226 0 0 1 1 1 0 0 0 1 0 227 0 0 1 1 1 0 0 0 1 1
36 0 0 0 0 1 0 0 1 0 0	100 0 0 0 1 1 0 0 1 0 0	64 0 0 1 0 1 0 0 1 0 0 3	228 0 0 1 1 1 0 0 1 0 0
37 0 0 0 0 1 0 0 1 0 1	101 0 0 0 1 1 0 0 1 1	65 0 0 1 0 1 0 0 1 0 1 2	229 0 0 1 1 1 0 0 1 0 1
38 0 0 0 0 1 0 0 1 1 0	102 0 0 0 1 1 0 0 1 1 0		230 0 0 1 1 1 0 0 1 1 0
39 0 0 0 0 0 1 0 0 1 1 1 40 0 0 0 0 1 0 1 0 1 0 0	103 0 0 0 1 1 0 0 1 1 1 104 0 0 0 1 1 0 1 0 0 0 1	67 0 0 1 0 1 0 0 1 1 1 1	231 0 0 1 1 1 0 0 1 1 1
40 0 0 0 1 0 1 0 0 0 41 0 0 0 0 1 0 1 0 0 1		69 0 0 1 0 1 0 1 0 0 1 2	233 0 0 1 1 1 0 1 0 0 1
42 0 0 0 0 1 0 1 0 1 0	106 0 0 0 1 1 0 1 0 1 0 1		234 0 0 1 1 1 0 1 0 1 0
43 0 0 0 0 1 0 1 0 1 1	107 0 0 0 1 1 0 1 0 1 1	.71 0 0 1 0 1 0 1 0 1 0 1 2	235 0 0 1 1 1 0 1 0 1 1
44 0 0 0 0 1 0 1 1 0 0	108 0 0 0 1 1 0 1 1 0 0		236 0 0 1 1 1 0 1 1 0 0
45 0 0 0 0 1 0 1 0 1 46 0 0 0 0 1 0 1 1 1 0	109 0 0 0 1 1 0 1 1 0 1		237 0 0 1 1 1 0 1 1 0 1 238 0 0 1 1 1 0 1 1 0
47 0 0 0 0 1 0 1 1 1 1			239 0 0 1 1 1 0 1 1 1 1
48 0 0 0 0 1 1 0 0 0 0	112 0 0 0 1 1 1 0 0 0 0		240 0 0 1 1 1 1 0 0 0 0
49 0 0 0 0 1 1 0 0 0 1	113 0 0 0 1 1 1 0 0 1 1		241 0 0 1 1 1 1 0 0 1 1
50 0 0 0 0 1 1 0 0 1 0	114 0 0 0 1 1 1 0 0 1 0 1		242 0 0 1 1 1 1 0 0 1 0
51 0 0 0 0 1 1 0 0 1 1 52 0 0 0 0 1 1 0 0 0	115 0 0 0 1 1 1 0 0 1 1 116 0 0 0 1 1 1 0 1 0 0 1		243 0 0 1 1 1 1 0 0 1 1 244 0 0 1 1 1 1 0 0 0 0
53 0 0 0 0 1 1 0 1 0 1			245 0 0 1 1 1 1 0 1 0 1
54 0 0 0 0 1 1 0 1 0	118 0 0 0 1 1 1 0 1 1 0 1		246 0 0 1 1 1 1 0 1 1 0
55 0 0 0 0 1 1 1 1 1			247 0 0 1 1 1 1 0 1 1 1
56 0 0 0 0 1 1 1 0 0 0	120 0 0 0 1 1 1 1 0 0 0 1		248 0 0 1 1 1 1 1 0 0 0
57 0 0 0 0 1 1 1 0 0 1 58 0 0 0 0 1 1 1 0 1 0			249 0 0 1 1 1 1 1 0 0 1 250 0 0 1 1 1 1 1 0 0 1
59 0 0 0 0 1 1 1 0 1 0			251 0 0 1 1 1 1 1 0 1 0
60 0 0 0 0 1 1 1 1 0 0	124 0 0 0 1 1 1 1 1 0 0		252 0 0 1 1 1 1 1 1 0 0
61 0 0 0 0 1 1 1 1 0 1	125 0 0 0 1 1 1 1 1 0 1		253 0 0 1 1 1 1 1 1 0 1
62 0 0 0 0 1 1 1 1 0	126 0 0 0 1 1 1 1 1 1 0		254 0 0 1 1 1 1 1 1 0
63 0 0 0 0 1 1 1 1 1 1	127 0 0 0 1 1 1 1 1 1 1 1	91 0 0 1 0 1 1 1 1 1	255 0 0 1 1 1 1 1 1 1 1



Page: 22/38 Product Number: LPM009M360A Revision Number: 02

9. OPTICAL SPECIFICATION

9.1 OPTICAL CHARACTERISTICS

9.1.1 Reflective mode

* Ta=25°C VDD=3.0V, VIH=3.0V, VIL=0V

Item	Symbol	Temp.		Rating		Unit	definition	Remark
item	Symbol	(°C)	Min.	Тур.	Max.	Offic	(Measurement setup)	Remark
Contrast	CR	25	10	20	-	-	1	
Response	Tr	25	-	4	8	mo	2	Black → White
Response	Td	25	-	6	10	ms	2	White → Black
	Rx		-	0.516	-			
	Ry		-	0.319	-			
	Gx	25	-	0.310	-			
Color	Gy		-	0.452	-		3	
coordinates	Вх		-	0.165	-	_	3)
	Ву		-	0.175	-			
	Wx		-	0.325	-			
	Wy		-	0.344	-			
NTSC ratio	-	25	16	23	-	%	4	
Reflectance	-	25	17	25	-	%	-	
	θL		45	60	-			l la via a veta l
Viewing Angle	θR	0.5	50	65			_	Horizontal
(CR>2)	θТ	25	50	65	-	deg.	5	Vertical
	θВ		45	60	-			v e i licai

9.1.2 TRANSMISSIVE MODE

* Ta=25°C VDD=3.0V, VIH=3.0V, VIL=0V

Item	Svmbol	Temp.		Rating		Unit	definition	Remark
пеш	Syllibol	(°C)	Min.	Тур.	Max.	Offic	(Measurement setup)	Remark
Transmittance	T	25	-	0.3	-	%	6	

^{*} COM frequency should be around 60 Hz for transmissive mode.



Product Number: LPM009M360A	Revision Number: 02	Page: 23/38
-----------------------------	---------------------	-------------

Product Number:	LPM009M360A	Revision Number: 02	Page: 23/38

9.2 DEFINITION AND CONDITION OF OPTICAL CHARACTERISTICS


Definition 1

This is a ratio between the screen surface reflectance of the white raster and the black raster

Definition 2

The response time is defined as the following figure and shall be measured by matching the input signal for "Black" and "White".

Normally Black mode



- tr: Response time from Black to White
- tf: Response time from White to Black

Definition 3


This is the x-y coordinate of Red, Green, Blue and White colors specified on the CIE1931 chromaticity diagram. (* It is not a guaranteed value)


Definition 4

This is an area of a triangle shaped by R, G and B coordinates on the CIE1931 chromaticity diagram.

Definition 5

This is a maximum angle θ from the normal direction that keeps having the contrast more than 2.







	Product Number:	LPM009M360A	Revision Number: 02	Page: 24/38
--	-----------------	-------------	---------------------	-------------

Definition 6

Transmittance is defined by the result of measuring backlight provided by Japan Display Inc.

- Measurement method of optical characteristics -
- < Basic measurement conditions >
- a) Driving voltage

VDD = 3.0V

b) Measurement temperature

25°C unless otherwise specified

c) Measurement point

Center of the Active area (one point) unless otherwise specified


d) Measurement equipment

LCD5200 or equivalent

f) Light source

Parallel light source


- D65 / 2 degree viewing angle
- Light source input direction: from TOP side (30°)
- Light source receive direction: at LCD center (0°)
- < Measurement system>





Product Number:	LPM009M360A	Revision Number: 02	Page: 25/38

< Measurement system for transmissive mode >



Global LCD Panel Exchange Center



Product Number: LPM009M360A	Revision Number: 02	Page: 26/38
-----------------------------	---------------------	-------------

10. INSPECTION

10.1 QUALITY STANDARD

10.1.1 Lot

Lot means the unit includes all products delivered to your company at one time.

10.1.2 INSPECTION CONDITION

(1) Ambient Conditions

Temperature : 25°C (±5°C) Humidity : 60% (±20%) **Ambient Luminance** : 1000 – 2000 lux


Supply Voltage : VDD=3.0(V), VIH=3.0V, VIL=0V

(2) Viewing Distance

The distance between the LCD and the inspector's eyes should be $30 \text{cm} \ (\pm 10 \text{cm})$.


(3) Viewing Angle

Viewing angle shall be ±45 degrees from the vertical direction as shown below.



10.1.3 ZONE DEFINITION

A zone : Active area B zone : except A zone



*For detail dimensions refer to outline drawing.



Product Number: LPM009M360A Revision Number: 02 Page: 27/38	Product Number:	LPM009M360A	Revision Number: 02	Page: 27/38
---	-----------------	-------------	---------------------	-------------

Product Number:	LPM009M360A	Revision Number: 02	Page:	27/38

10.1.4 TREATMENT OF OTHER PROBLEMS

If any troubles should occur concerns our products that have been assembled at your company's manufacturing processes, both companies shall jointly investigate and resolve the causes.







Product Number:	LPM009M360A	Revision Number: 02	Page: 28/38

10.2. DISPLAY APPEARANCE STANDARDS

	Item	7	Criteria		Davasala
Name	Cause	Zone	Size(mm)	N.	Remark
	B/W spot		D≦0.15	Ignore	
D	(Dent in glass or	Α	0.15 <d≦0.25< td=""><td>2</td><td>Keep two defect distance more than 5mm</td></d≦0.25<>	2	Keep two defect distance more than 5mm
Dot type defect	Upper polarizer, Particle, Swell)		0.25 <d< td=""><td>0</td><td>more than onlin</td></d<>	0	more than onlin
	Bright/Dark dot defect	В	Ignore		
	Scratch on polarizer		W≦0.03	Ignore	16 ()
Line type defect	or Foreign material between	Α	0.03 <w≦0.08, l≦2<="" td=""><td>2</td><td>Keep two defect distance</td></w≦0.08,>	2	Keep two defect distance
			0.08 <d 2<l<="" or="" td=""><td>0</td><td>more than 5mm</td></d>	0	more than 5mm
	Upper polarizer and glass	В	Ignore		
			D2≦0.25	2	
Air bubble	Air bubble	А	D1≦0.20	2	
			0.5 <d1+d2< td=""><td>0</td><td></td></d1+d2<>	0	
		В	Ignore		





Line type defect

^{*}B zone defects other than the above are ignored when function / display is not affected

^{*}When there is an agreement limit samples, Item is judged according to limit sample.

^{*}Total defect quantity: A zone (N \leq 3) *each inspection (lighting / appearance) , B zone (N \leq 5)

^{*}Other items are to be decided by agreement between both parties.


^{*}Cosmetic imperfection will be allowed outside the A.A. (Active Area).



|--|

10.3. EXTERNAL APPEARANCE STANDARDS

lkomo	Criteria		Damada	
Item	Size(mm)	Number	Remarks	
	(A) W≦3 , L≦0.2 , T=1/2t	Ignore	Fig 1	
Chipping	(B) W≦3 , L≦0.6 , T<1/2t	Ignore	Fig 2	
	Except (A)	0		
	W≦3.0 , L≦0.5	Ignore	V ahanad ahinning ingludad Fig2	
Crack	3.0 <w 0.5<l<="" or="" td=""><td>0</td><td>V-shaped chipping included Fig3</td></w>	0	V-shaped chipping included Fig3	
Chipping on the corner	Showing on below figure			
Drojection	W≦0.3 , L≦5.0	Ignore		
Projection	0.3 <w 5.0<l<="" or="" td=""><td>0</td><td></td></w>	0		





Product Number:	LPM009M360A	Revision Number: 02	Page: 30/38
i ioduct ivalliber.	LI WOOSWISOOA	INCVISION NUMBER OF	1 age. 30/30

Product Number:	LPM009M360A	Revision Number: 02	Page: 30/38

11. RELIABILITY TEST

11.1 CONDITIONS OF RELIABILITY AND MECHANICAL TEST

No.	TEST ITEM	CONDITION	REMARK	
1	High Temperature Storage	Ta=80°C	240h	
2	Low Temperature Storage	Ta=-30°C	240h	
3	High Temperature & High Humidity Storage	Ta=60°C ∕ 90%RH (No condensation)	240h	
4	High Temperature & High Humidity Operation	Ta=40°C ∕ 90%RH (No condensation)	240h	
5	High Temperature Operation	Ta=70°C	240h	
6	Low Temperature Operation	Ta=-20°C	240h	
7	Thermal shock (non-operating)	Ta=-20°C to 70°C (30min each)	50cycles	
8	ESD	HBM IEC 61340-3-1, ESD STM5.1 V = 1.0kV (Contact) R = 1.5kΩ, C = 100pF	1 time each terminal	
9	Packing Vibration	Random Vibration 5~500Hz	101min Direction Z	(*11-1)
10	Packing Drop	Height 60cm,1 corner 3 edges,6 surfaces	1 time Each direction	(*11-1)

Note)

(*11-1) Tests are done using conducted package.

Above test evaluate for development. It is not guaranteed value for lot acceptance.

If a nonconformance is found, both parties will have a discussion to solve it.

11.2 CRITERIA FOR JUDGEMENT

After the above tests, return samples to the normal temperature and moisture environment in the thermostat chamber room over 30 minutes not to condense. Inspect samples kept for more than 1 hour after pulling them out of the thermostat chamber room.

- (1) There shall be no abnormality in the functions (Ex. No display, abnormal display, line defects).
- (2) There shall be no serious degradation. (Ex. Brightness uniformity, reversible changes, optical changes due to back light or polarizer are ignored.)

Japan	Disbig	ıy ınc.




Product Number: LPM009M360A	Revision Number: 02	Page: 31/38
-----------------------------	---------------------	-------------

12. DESIGNATION OF LOT MARK

12.1 LOT MARK

Lot mark is printed on the FPC of the LCD module.



Year	Figure in lot mark
2016	6
2017	7
2018	8
2019	9
2020	0

Month	Figure in let mort	Month	Figure in let mark
Month	Figure in lot mark	Month	Figure in lot mark
Jan.	А	July	G
Feb.	В	Aug.	Н
Mar.	С	Sep.	I
Apr.	D	Oct.	J
May	E	Nov.	K
June	F	Dec.	L

Japan Display Inc.




Product Number:	LPM009M360A	Revision Number: 02	Page: 32/38
i iodact indilibei.	LI WOOSWISOOA	I (CVISIOII I VUITIDGI. UZ	1 age. 52/50


13. PACKING SPECIFICATIONS

13.1 INNER CARTON


30pcs LCD modules per tray 10 trays with products + empty tray as cover = 11 trays




Product Number: LPM009M360A Revision Number: 02 Page: 33/38



Indication onto [A] [B] [C] [D] on master carton is shown as below



Outer label



Japan Display Inc.



Product Number: LPM009M360A	Revision Number: 02	Page: 34/38
-----------------------------	---------------------	-------------

14. LCD MODULE USAGE AND PRECAUTIONS

14.1 HANDLING

- (1) The display panel is made of glass. Do not subject it to mechanical shock such as dropping it from a high position,
- (2) If the display panel is damaged and internal liquid crystal substance leaks out, be sure not to inhale or consume it. If the internal liquid crystal substance comes into contact with skin or clothing, promptly wash it off using soap and running water.
- (3) Do not apply excessive force on the surface, perimeter or adjoining areas of LCD module since this may cause display panel color tone to vary.
- (4) The polarizer covering the display panel surface of the LCD module is soft and can be easily scratched or dented. Handle this polarizer carefully.
- (5) If the surface polarizer becomes contaminated, use the following recommended or equivalent adhesive tape for contaminants removal.
- Scotch-brand mending tape (No. 810)
- (6) Do not breathe on the display surface or use Ethyl Alcohol solvent for contaminant removal as polarizer discoloration may occur. Furthermore, solvent other than mentioned above may also damage the polarizer. Especially, do not use the followings.
- Water
- Ketones
- Aromatic solvents
- (7) When mounting the LCD Module, be sure that it is free from twisting, warping, or distortion. Any stress can have great influence to the display quality. Also, in cases where outer case or frame is included, be sure to secure sufficient stiffness on the outer case or frame for a robust design.
- (8) Do not apply pressure at or around the FPC bonding area and the surrounding area.
- (9) Do not attempt to disassemble or rework the LCD module.
- (10) To prevent destruction of the elements by static electricity, be careful to maintain an optimum working environment.
- Be sure to ground your body before handling the LCD module.
- Make sure that solder guns and all other tools required for assembly have been grounded.
- To reduce occurrence of static electricity, avoid using this product in dry environments.
- · A protective film has been attached to the surface of the LCD panel. When peeling off the protective film, be careful to prevent electrostatic discharges.
- (11) To minimize performance degradation of the LCD module caused by destructive forces such as static electricity, etc., avoid direct contact to the following sections when handling the LCD module.
- · terminal electrodes of connector
- · wiring pattern on FPC
- (12) LCD Panel surface is protected by a protective film layer. This protective film must be removed before final product installation. After removal of protective film layer, some adhesive residues maybe left on the LCD panel, especially after long storage period, please refer to section 5) listed above for proper contaminant removal procedure.
- (13) Take precaution to minimize corrosion of electrodes. Corrosion of electrodes is accelerated by moisture, condensation or a current flow in a high-humidity environment.
- (14) Do not apply excessive pressure to the FPC part. Force type such as twist, warp, etc., may damage FCP patterning traces.
- (15) Do not use sharp, pointy or rigid tools when handing LCD panels. These objects can scratch or nick the glass panel which can cause it to crack.

Global LCD Panel Exchange Center



LPM009M360A 35/38

Product Number: Revision Number: 02

- (16) Do not touch or handle the LCD module directly with bare hands. Residue of dirt, oil or water may have the possibility to cause corrosion. Be sure to wear finger sacks or gloves when handling LCD modules. When holding an LCD panel module, carefully hold the panel by the edges of the glass plate.
- (17) Avoid using LCD module under condensation or high humidity environment because polarizer etc. maybe damaged in these conditions.
- (18) Trays are used to package LCD modules for shipment. If LCD modules scratch the tray during shipment, material of the scratched tray may be left on LCD modules. In such case, clean up LCD modules after removal from trays.
- (19) When installing LCD module, don't apply excess stress of bending or stretching to the input cable
- (20) Keep NC terminal open electrically.
- (21) After storage under high humidity or condensation environment, keep LCD module under room temperature more than 30 minutes before operation.
- (22) Take precautions to handling LCD module because the glass plate has very keen edges.

14.2 DESIGN OF APPLICATION

- (1) The absolute maximum ratings represent the rated values which LCD module cannot exceed. When LCD modules are used beyond this rated value, the operating characteristics may be adversely affected.
- (2) To prevent the occurrence of erroneous operation caused by noise, special attention on satisfying VIL, VIH specified values is required. This includes taking the precautionary measures of using short cables for signal transferring.
- (3) An inherent characteristic of liquid crystal display is its temperature dependency. Be sure to use the LCD modules within the specified operating temperature range, as recognition of the display becomes difficult when the LCD module is used outside its range. Also, keep in mind that the voltage levels necessary for clear display images will vary according to temperature.
- (4) It is recommended that power supply lines (VDD) to include current surge protection. (Fuse etc. recommend value: 0.5A)
- (5) Note the peripheral devices can cause mutual noise interference with LCD modules. Especially, input devices such as Touch Panel, etc., may output operational level by radiation noise even when these devices are not in operation. Actual performance confirmation and verification under actual usage environment by actual final product is highly recommended.
- (6) To avoid EMI, preventive measures should be implemented in the final product.
- (7) Display abnormality may occur with sudden removal of power supply such as device battery. Sudden removal of power supply shall be avoided at all time. LCD module quality cannot be guaranteed under such condition.
- (8) Ensure sufficient light shading measures during design phase and when assemble the LCD module.
- (9) Ensure sufficient light shading measures in the inspection process.
- (10) Similar to general electronic components, ESD may cause LCD IC to malfunction. ESD preventive measures should be considered around the LCD module.
- (11) While display data may be kept, data can be easily changed by external noise. Noise shall be minimized at device or system level.
- (12) As unexpected noise may occur, periodic refresh operation such as resend the command and display data is highly recommended as part of the software routine.
- (13) When logic circuit power is off, do not apply any signals to the input terminals.
- (14) Do not use other components such as FPC or other features to fix the LCD module position, as pressure/tension may produce undesired result such as FPC trace crack.

14.3 DISPLAY CHARACTERISTICS

- (1) Because the optimum LCD driving voltage depends on the ambient temperature, display may slightly flicker at the environment of high temperature.
- (2) One of the special characteristics of liquid crystal is that it freezes when stored at the temperature below the storage temperature range. Such freezing may cause orientation defects or bubbles (black or white) to appear in the LCD panel. Bubbles may also occur if the panel receives an impact in a low-temperature environment.
- (3) If the LCD module is left operating for a long time with the same display showing, the displayed pattern may leave traces on the screen or the contrast may become inconsistent.



|--|

14.4 KEEPING THE PRODUCTS

- $(1) \ When \ keeping \ LCD \ modules, avoid \ the \ following \ condition \ or \ environment.$
- Exposure to direct sunlight or fluorescent lamps lightings.
- $\bullet \ \ \text{High-temperature/high-humidity or very low-temperature (below 0 ^{\circ}\text{C}) environments}.$
- Exposure to water droplets, condensation, etc.

Furthermore, keep LCD modules in anti-static bags to prevent static electricity charge ups. Whenever possible, LCD modules should be stored in the same conditions in which they were shipped from Japan Display Inc.

- (2) Take precaution to minimize corrosion of electrodes. Corrosion of electrodes is accelerated by moisture, condensation or a current flow in a high-humidity environment.
- (3) Recommended keeping conditions.
- Keeping environment: +15°C to 35°C, less than 65%RH
- Duration: up to 2 months after shipping date
- (4) The shipping carton must not be stacked up over 1.5m in height.

14.5 DISPOSAL

(1) When disposing LCD modules, consult company specialized in industrial waste treatment which is permitted by the government or local authority. When incineration is the method of LCD module disposal, law of environmental hygienic must be obeyed.


14.6 OTHERS


- (1) This product is designed to be used in ordinary electronic devices. Do not use this product in other applications, especially in devices that may cause direct bodily damage to end users (such as aerospace equipment, traffic control equipment, medical equipment, life-support system equipment, or safety equipment).
- (2) Japan Display Inc. shall not be responsible for defects that occur in this product or in equipment connected to this product if the product is used in an environment that exceeds the ranges specified in this document, or in an environment not described in this document.




Product Number: LPM009M360A Revision Number: 02 Page: 37/38

15. OUTLINE DRAWING









Japan Display Inc.



Product Number: LPM009M360A Revision Number: 02 Page: 38/38





Note 1) Unit: mm

2) General tolerance: +/-0.2

3) Scale: NTS

4) Unless otherwise specified, radius shall be R0.5.

5) Example of suitable FPC connector: 10062827-0810EDLF (8pin / FCI)

Japan Display Inc.