

RF Exposure

Applicant : Makerfabs
Address : 6th North, Bldg A, ShangHe NanChang Industry Zone, SanWei Community, HangCheng St, Bao'an, ShenZhen, GuangDong, China
Product Name : UWB Radio Frequency Module
Brand Mark : 
Model : MaUWB-DW3000 CE
Series model : N/A
Report Number : BLA-EMC-202607-A39-02
Date of Receipt : Jul. 20, 2026
Date of Test : Jul. 20, 2026 to Sep. 07, 2026
Test Standard : EN 62479:2010
Test Result : Pass

Compiled by: Mark Chen

Review by: Xavier

Approved by:

Issued Date: Sep. 08, 2026

BlueAsia Technical Services (Shenzhen) Co., Ltd

Address: No.41, South of Beihuan Road, Shangwu Community, Shiyan Subdistrict, Bao'an District, Shenzhen, Guangdong, China



The test report is effective only with both signature and specialized stamp and The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full. The results described in this report do not represent the quality or characteristics of the sampled batch, nor do they represent any similar or identical products that are not explicitly stated.

Table of Contents

1 General information	4
1.1 General information	4
1.2 General description of EUT	4
2 Test summary	5
3 Laboratory information	5
3.1 Laboratory and accreditations	5
4 RF exposure	6
4.1 Limit	6
4.2 Procedure	6
4.3 Evaluation results	6

Revise Record

Version No.	Date	Description
01	Sep. 08, 2026	Original

1 General information

1.1 General information

Applicant	Makerfabs
Address	6th North, Bldg A, ShangHe NanChang Industry Zone, SanWei Community, HangCheng St, Bao'an, ShenZhen, GuangDong, China
Manufacturer	Makerfabs
Address	6th North, Bldg A, ShangHe NanChang Industry Zone, SanWei Community, HangCheng St, Bao'an, ShenZhen, GuangDong, China
Factory	Makerfabs
Address	6th North, Bldg A, ShangHe NanChang Industry Zone, SanWei Community, HangCheng St, Bao'an, ShenZhen, GuangDong, China

1.2 General description of EUT

Product Name	UWB Radio Frequency Module
Model No.	MaUWB-DW3000 CE
Operation Frequency	6.0GHz to 8.5GHz
Test Frequency	6500MHz
Modulation Type	BPM-BPSK
Type of equipment	Type 1
EUT category	1B
Signal characteristic	CASE 4
Number of Channels	1
Antenna Type	Chip antenna
Antenna Gain	5.3dBi(Provided by customer)
Power supply	DC 3.3V
Hardware Version	N/A
Software Version	N/A

Note: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2 Test summary

Test item	Test Requirement	Test Method	Class/Severity	Result
RF Exposure	EN 62479:2010	EN 62479:2010	EN 62479:2010	PASS

3 Laboratory information

3.1 Laboratory and accreditations

The test facility is recognized, certified, or accredited by the following organizations:

Company name:	BlueAsia Technical Services (Shenzhen) Co.,Ltd.
Address:	No.41, South of Beihuan Road, Shangwu Community, Shiyan Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Registration No.:	L9788
Telephone:	+86-755-28682673
FAX:	+86-755-28682673

4 RF exposure

4.1 Limit

According to EN 62479 clause 4.2 Low-power electronic and electrical equipment is deemed to comply with the provisions of this standard if it can be demonstrated using routes B, C or D that the available antenna power and/or the average total radiated power is less than or equal to the applicable low-power exclusion level $P_{\max}$.

$P_{\max} = 20\text{mW}$ (13dBm) according to ICNIRP guidelines, since the EUT is General public used.

Remark:

- B. The input power level to electrical or electronic components that are capable of radiating electromagnetic energy in the relevant frequency range is so low that the available antenna power and/or the average total radiated power cannot exceed the low-power exclusion level defined in EN 62479 clause 4.2
- C. The available antenna power and/or the average total radiated power are limited by product standards for transmitters to levels below the low-power exclusion level defined in EN 62479 clause 4.2
- D. Measurements or calculations show that the available antenna power and/or the average total radiated power are below the low-power exclusion level defined in EN 62479 clauses 4.2.

4.2 Procedure

The maximum EIRP of the EUT is 0.007mW, which is less than or equal to the applicable low-power exclusion level $P_{\max}$ (20mW), so the EUT is deemed to comply with the provisions of this standard.

4.3 Evaluation results

Maximum Emissions Level of UWB (Worst case)			
Test Frequency (MHz)	EIRP Level(mW)	Limit (mW)	Result
6500	0.007	20	Pass

Remark:

$\text{EIRP} = \text{Mean e.i.r.p.spectral density (dBm/MHz)} + 10 \cdot \log(-10\text{dB Bandwidth})$

$= -48.155 + 10 \cdot \log(458) = -21.55\text{dBm} = 0.007\text{mW}$, refer to project No. BLA-EMC-202607-A39-01.

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, the result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.