SahodSuri: System Cheat Sheet

Understand Your Pay. Know Your Rights. | React + Vite / Express / Supabase / Lumen OCR + Chat | JavaScript only, npm workspaces

COMMANDS (repo root)

`npm install`	Install all workspaces (root only)
`npm run dev:backend`	API on http://localhost:5000
`npm run dev:frontend`	App on http://localhost:5173
`npm run build`	Production build of frontend
`GET /api/health`	Backend health check

TESTS

`backend/`	node --test src/modules/dashboard/__tests__/dashboard.test.js
`frontend/`	node --test "src/**/*.test.js"
`note`	Pass a file/glob, not a folder. npm test/lint scripts not defined yet.

BACKEND backend/src/

`app.js`	CORS, JSON parsing, route mounting, error handlers
`config/env.js`	All settings, read once from root .env
`config/supabase.js`	Lazy service-role client (bypasses RLS)
`middleware/`	apiResponse, errorHandler, validateRequest, userContext
`modules/<name>/`	routes > controller > service > repository + validators
`documents/`	Uploads, ocrService.js (Lumen OCR), corrections
`ai-assistant/`	routes.js chat; knowledge/ = FAQ, refs, prompts
`payroll/`	calculator.js = deterministic pay math; records
`dashboard/`	Summary, trends, analytics, reports; __tests__/

FRONTEND frontend/src/

`App.jsx`	Shell + page switching (AppLayout)
`components/`	Shared layout, dialogs; ui/ = shadcn primitives
`services/apiClient.js`	ONLY way to call the API (api.get/post/...)
`config/`	env.js, supabase.js (public keys only)
`modules/<name>/`	Page.jsx, components/, services/, lib/, hooks/
`@/...`	Import alias for src/ (vite + jsconfig)

API ROUTES

`/api/documents`	GET /, POST /upload-url, GET|PATCH|DELETE /:id, POST /:id/extract
`/api/ai-assistant`	POST /chat
`/api/payroll`	POST /preview (no user), GET|POST /records, GET|DELETE /records/:id
`/api/dashboard`	GET /summary /history /salary-trends /analytics /reports/payroll

RESPONSE FORMAT

`ok`	{ success: true, message, data }
`error`	{ success: false, message, error: { code, details } }
`backend`	sendSuccess(res, data, msg) / throw new AppError(msg, status, code)

WHO OWNS THE DATA (userContext.js)

- Signed in: req.user.id.
- Production, no user: 401 UNAUTHENTICATED.
- Dev: DEV_USER_ID. Documents/Payroll return 503 if unset; Dashboard shows all rows.
- Never read a user id from body or query.

ENVIRONMENT (single root .env)

`VITE_*`	PUBLIC: bundled into the browser. No secrets.
`VITE_API_BASE_URL`	Browser API base (or /api via Vite proxy)
`SUPABASE_URL / _ANON_KEY`	Backend Supabase project + anon key
`SUPABASE_SERVICE_ROLE_KEY`	SECRET, backend only
`LUMEN_API_KEY / _SECRET`	SECRET, sent as lumen-api-key/-secret headers
`LUMEN_OCR_ENDPOINT`	OCR gateway
`LUMEN_CHAT_ORIGIN`	Chat gateway origin (+ LUMEN_INSTANCE_ID)
`DEV_USER_ID`	Dev-only Supabase auth user id
`FRONTEND_URL / PORT`	CORS allow-list / API port (5000)

SUPABASE SETUP

- Copy URL + anon key into SUPABASE_* and VITE_SUPABASE_*.
- Put the service role key in SUPABASE_SERVICE_ROLE_KEY only.
- Run database/schema.sql (tables + RLS).
- The backend creates the private "documents" bucket on first upload.
- Create a test user and copy its id into DEV_USER_ID.

TEAM + GIT

`Lead`	Shared code, deps, schema, env, CI, routes
`M1 / M2`	Documents / AI Assistant
`M3 / M4`	Payroll / Dashboard

- Work only in your modules/<feature>/ folders.
- Use branch feature/<feature> and open PRs to main. Only the lead merges.
- CI (install, lint, test, build) runs on PRs and pushes to main.

PRIVACY RULES

- Use only synthetic documents. Never commit .env or real data.
- Use private buckets with RLS. Never expose permanent URLs.
- Never log extracted text, salaries, or personal ids.
- Label every value as extracted, calculated, or AI-generated.
- Never declare that an employer broke the law.