

OpenCTI

Deploy OpenCTI on Ubuntu-Wazu-Server (Recommended)

This is the best option same VM as Wazuh, both tools talk to each other directly.

Step 1 — Check Ubuntu-Wazu-Server disk space first

bash

```
df -h  
free -h
```

If it has 20+ GB free, deploy there. If not, you need to expand the VM disk first.

Step 2 — Install Docker on Ubuntu-Wazu-Server (if not already)

bash

```
sudo apt update  
sudo apt install docker.io docker-compose -y  
sudo systemctl enable docker  
sudo usermod -aG docker $USER
```

Step 3 — Create OpenCTI folder

bash

```
mkdir ~/opencti && cd ~/opencti
```

Step 4 — Create docker-compose.yml

bash

```
nano docker-compose.yml
```

Paste this minimal config:

yml

```
version: '3'
services:
  redis:
    image: redis:7.2.4
    restart: always
    volumes:
      - redisdata:/data

  elasticsearch:
    image: docker.elastic.co/elasticsearch/elasticsearch:8.12.2
    volumes:
      - esdata:/usr/share/elasticsearch/data
    environment:
      - discovery.type=single-node
      - xpack.security.enabled=false
      - "ES_JAVA_OPTS=-Xms1G -Xmx1G"
    restart: always
    ulimits:
      memlock:
        soft: -1
        hard: -1

  minio:
    image: minio/minio:latest
    volumes:
      - s3data:/data
    environment:
      MINIO_ROOT_USER: opencti
      MINIO_ROOT_PASSWORD: changeme123
    command: server /data
    restart: always

  rabbitmq:
    image: rabbitmq:3.12-management
    environment:
      - RABBITMQ_DEFAULT_USER=opencti
      - RABBITMQ_DEFAULT_PASS=changeme123
    volumes:
      - amqpdata:/var/lib/rabbitmq
    restart: always
```

```

opencti:
  image: opencti/platform:6.3.0
  environment:
    - NODE_OPTIONS=--max-old-space-size=8096
    - APP__PORT=8080
    - APP__BASE_URL=http://localhost:8080
    - APP__ADMIN__EMAIL=admin@opencti.io
    - APP__ADMIN__PASSWORD=changeme123
    - APP__ADMIN__TOKEN=changeme-token-replace-this
    - REDIS__HOSTNAME=redis
    - ELASTICSEARCH__URL=http://elasticsearch:9200
    - MINIO__ENDPOINT=minio
    - MINIO__PORT=9000
    - MINIO__USE_SSL=false
    - MINIO__ACCESS_KEY=opencti
    - MINIO__SECRET_KEY=changeme123
    - RABBITMQ__HOSTNAME=rabbitmq
    - RABBITMQ__USERNAME=opencti
    - RABBITMQ__PASSWORD=changeme123
    - SMTP__HOSTNAME=localhost
    - PROVIDERS__LOCAL__STRATEGY=LocalStrategy
  ports:
    - "8080:8080"
  depends_on:
    - redis
    - elasticsearch
    - minio
    - rabbitmq
  restart: always

worker:
  image: opencti/worker:6.3.0
  environment:
    - OPENCTI_URL=http://opencti:8080
    - OPENCTI_TOKEN=changeme-token-replace-this
    - WORKER_LOG_LEVEL=info
  depends_on:
    - opencti
  restart: always

volumes:
  esdata:
  s3data:
  redisdata:
  amqpdata:

```

Step 5 — Start OpenCTI

bash

```
docker compose up -d
```

First run downloads ~5 GB of images.

Step 6 — Verify it's running

bash

```
docker compose ps
docker logs opencti_opencti_1 --follow
```

Step 7 — Access OpenCTI

```
http://UBUNTU-VM-IP:8080
```

```
Login: admin@opencti.io / changeme123
```