

Assignment 3

Questions from A to G and the bonus:

Assignment 3:

A. Select * from FLIGHT order by Airline;

B. Select Fare_code, Restrictions, (Amount * 1.15) as Amt.-after-tax
From FARE where Amount > 50;

C. Delete from SEAT-RESERVATION
Where rowid in (select rowid from SEAT-RESERVATION
limit (select cast (count(*) * 0.05 as integer) from SEAT-
RESERVATION
));

D. Select Airplane-type-name, Max-seats from AIRPLANE-TYPE;

E. Select Airplane-type-name from AIRPLANE-TYPE where
Airplane-type-name like 'E.T.';

F. Select F.Flight-number, A1.Name as Departure-airport, A2.Name
as Arrival-airport,

FL.Scheduled-departure-time, FL.Scheduled-arrival-time, AT.Airplane-
type-name
From FLIGHT F

join FLIGHT-LEG FL on F.Flight-number = FL.Flight-number

join AIRPORT A1 on FL.Departure-airport-code = A1.Airport-
code

join AIRPORT A2 on FL.Arrival-airport-code = A2.Airport-code

join LEG_INSTANCE LI on FL.Flight-number = LI.Flight-number
and FL.Leg-numbers = LI.Leg-numbers.

join AIRPLANE AP on LI.Airplane-id = AP.Airplane-id

join AIRPLANE-TYPE AT on AP.Airplane-type = AT.Airplane-type-name
Where F.Weekdays = 'Monday';

G. Select F.Flight-number, F.Airline, A1.name as Departure-airport, A2.name
as Arrival-airport,

FL.Scheduled-departure-time, FL.Scheduled-arrival-time

From FLIGHT F

join AIRPORT A1 on FL.Departure-airport-code = A1.Airport-Code

join AIRPORT A2 on FL.Arrival-airport-code = A2.Airport-Code

Where F.Airline Like '%Air';

Bonus.

Insert into FLIGHT values ('AA101', 'American Air', 'Sunday');

Insert into FLIGHT values ('EA102', 'Egypt Air', 'Monday');

Insert into FARE values ('AA101', 'F1', 120, 'Refundable');

Insert into FARE values ('EA102', 'F2', 75, 'Non-Refundable');

Bonus:

- drop table Customers;
- drop table Orders;
- drop table Shippings;
- create table AIRPORT(
 - Airport_code varchar(10) primary key,
 - Name varchar(100),
 - City varchar(100),
 - State varchar(100)
-);
-
- create table FLIGHT(
 - Flight_number varchar(10) primary key,
 - Airline varchar(100),
 - Weekdays varchar(50)
-);
-
- create table FLIGHT_LEG(
 - Flight_number varchar(10),
 - Leg_number int,
 - Departure_airport_code varchar(10),
 - Scheduled_departure_time time,
 - Arrival_airport_code varchar(10),
 - Scheduled_arrival_time time,
 - primary key (Flight_number, Leg_number),
 - foreign key (Flight_number) references FLIGHT(Flight_number) on delete cascade,
 - foreign key (Departure_airport_code) references AIRPORT(Airport_code),
 - foreign key (Arrival_airport_code) references AIRPORT(Airport_code)
-);
-
- create table AIRPLANE_TYPE(
 - Airplane_type_name varchar(50) primary key,
 - Max_seats int,
 - Company varchar(100)
-);

-
- create table CAN_LAND(
 - Airplane_type_name varchar(50),
 - Airport_code varchar(10),
 - primary key (Airplane_type_name, Airport_code),
 - foreign key (Airplane_type_name) references AIRPLANE_TYPE(Airplane_type_name),
 - foreign key (Airport_code) references AIRPORT(Airport_code)
-);
-
- create table AIRPLANE(
 - Airplane_id varchar(20) primary key,
 - Total_number_of_seats int,
 - Airplane_type varchar(50),
 - foreign key (Airplane_type) references AIRPLANE_TYPE(Airplane_type_name)
-);
-
- create table LEG_INSTANCE(
 - Flight_number varchar(10),
 - Leg_number int,
 - Date date,
 - Number_of_available_seats int,
 - Airplane_id varchar(20),
 - Departure_airport_code varchar(10),
 - Departure_time time,
 - Arrival_airport_code varchar(10),
 - Arrival_time time,
 - primary key (Flight_number, Leg_number, Date),
 - foreign key (Flight_number, Leg_number) references FLIGHT_LEG(Flight_number, Leg_number),
 - foreign key (Airplane_id) references AIRPLANE(Airplane_id)
-);
-
- create table FARE(
 - Flight_number varchar(10),
 - Fare_code varchar(10),

- Amount decimal(10,2),
- Restrictions varchar(255),
- primary key (Flight_number, Fare_code),
- foreign key (Flight_number) references FLIGHT(Flight_number) on delete cascade
-);
-
- create table SEAT_RESERVATION(
- Flight_number varchar(10),
- Leg_number int,
- Date date,
- Seat_number varchar(5),
- Customer_name varchar(100),
- Customer_phone varchar(20),
- primary key (Flight_number, Leg_number, Date, Seat_number),
- foreign key (Flight_number, Leg_number, Date) references
LEG_INSTANCE(Flight_number,Leg_number,Date)
-);
-
-
- --bonus
- insert into FLIGHT values ('AA101','American Air','Sunday');
- insert into FLIGHT values ('EA220','Egypt Air','Monday');
-
- insert into FARE values ('AA101','F1',120,'Refundable');
- insert into FARE values ('EA220','F2',75,'Non-refundable');
-
- select * from FARE;

AIRPLANE

Airplane_id	Total_number_of_seats	Airplane
empty		



AIRPLANE_TYPE

Airplane_type_name	Max_seats	Company
empty		



AIRPORT

Airport_code	Name	City	State
empty			

•

FLIGHT_LEG

Flight_number	Leg_number	Departure_airpo
empty		



LEG_INSTANCE

Flight_number	Leg_number	Date	Numb
empty			



SEAT_RESERVATION

Flight_number	Leg_number	Date	Seat_r
empty			

•

CAN_LAND

Airplane_type_name	Airport_code
empty	

FARE

Flight_number	Fare_code	Amount	Restr
AA101	F1	120	Refur
EA220	F2	75	Non-refun



FLIGHT

Flight_number	Airline	Weekdays
AA101	American Air	Sunday
EA220	Egypt Air	Monday

Output

Flight_number	Fare_code	Amount	Restrictions
AA101	F1	120	Refundable
EA220	F2	75	Non-refundable

•