

Appendix C –Torque Specifications

Table C-1 lists torque values for the fasteners used in the FastBack® Model 90E.

Location	Description	Quantity	Torque Value (Imp)	Torque Value (N-m)
Enclosure	Pan attachment disk – 1/4-20x3/4"	8	110 in-lbs	12.4
	Pan attachment disk – 6mm (Some 50E models only)	8	90 in-lbs	10.2
Drive assembly	Torsion bushing bolt – 1/2-13x8"	3	42 ft-lbs	57
	Pan attachment arm bolt – 1/2-13x8"	2	42 ft-lbs	57
	Top brace nylock nuts – 1/2-13 (90E only)	4	42 ft-lbs	57
	Drive arm clevis – 1/2-13x4-1/2"	1	42 ft-lbs	57
Eccentric sprocket system	Tensioner pivot bolt – 1/2-13x1-1/4"	1	42 ft-lbs	57
	Cam adjustment pivot bolt – 1/2-13x1-1/4"	1	42 ft-lbs	57
	Flange bearing bolts – 3/8-16x1-1/2"	16	20 ft-lbs	27
	Tensioner sprocket stud – 5/8-18	1	75 ft-lbs	102
	Idler sprocket stud – 5/8-18	1	75 ft-lbs	102
	JA QD bushing screws – 10-24x1"	6	54 in-lbs	6.1
Motor plate	Motor plate bolts – 3/8-16x1"	3	20 ft-lbs	27
	Motor mounting bolts – 1/4-20x3/4"	4	80 in-lbs	9.0
Counterweight	Counterweight studs – 1/2-13	4	42 ft-lbs	57
	Two-piece collar screws – 1/4-28x11/16"	4	110 in-lbs	12.4
Articulating foot (Model-90E only)	Vertical adjustment jam nut – 3/4-10	4/(3)	100 ft-lbs	136
	Mounting bolts – 3/8 hardware	8/(6)	20 ft-lbs	27
Power module	Cover screws – #10-32	6	15 in-lbs	1.7
	Ground screw – #6-32	1	15 in-lbs	1.7
	Power mod./Shell bracket – 1/4-20 studs	1	110 in-lbs	12.4
Inverter – Yaskawa, Model V7 & V1000	Power terminals L1, L2, L3, T1, T2, T3 (200V-class)	6	7.1-8.9 in-lbs	0.8-1.0
	Power terminals L1, L2, L3, T1, T2, T3 (400 V-class)	6	10.7 -13.3 in-lbs	1.2-1.5
	Output terminals MA, MB, MC	As required	4.4-5.3 in- lbs	0.5-0.6
	Input terminals SC, S1, S3, S5, S6, FC, FR	As required	1.9-2.2 in- lbs	0.22-0.25
Photoeye & Proximity Sensor	Photoeye bracket – 1/4-28x11/16"	1	110 in-lbs	12.4
	Photoeye bracket – 3/8-16" bolt	1	20 ft-lbs	27
	Two-piece collar screws – 1/4-28x11/16"	4	110 in-lbs	12.4
Torsion bushing collar clamps	One-piece collar screws – 1/4-28x3/4"	10	110 in-lbs	12.4
Crank assembly	Flange bearing set screws – 1/4-28x1/4 "	8	75 in-lbs	8.5

Table C-1 – FastBack® Models 50E/90E Torque Specifications

APPENDIX C –TORQUE SPECIFICATIONS

FastBack® Model 90E Technical Manual
