

APPENDIX C –TORQUE SPECIFICATIONS

FastBack® Model 260E-G2 Technical Manual

Appendix C Torque Specifications

Location	Description	Quantity	Torque Value (Standard)	Torque Value (Metric)
Transmission Assembly	Crankshaft Bearing Retainer Screws - 1/4-20	6	110 in-lbs	12.4 N-m
	Taper Lock Set Screws - 1/4-20 (#1108)	4	55 in-lbs	6.2 N-m
	Taper Lock Set Screws - 3/8-16 (#1310)	4	144 in-lbs	16 N-m
	Transmission Top Brace Screws - 5/16-18	8	11 ft-lbs	15 N-m
	Flange BRG. Collar Set Screws - 5/16-24	8	13 ft-lbs	17.6 N-m
	Flange Bearing Mounting Bolts - 3/8-16	16	20 ft-lbs	27 N-m
	Cam Pivot Nut - 1/2-13	1	42 ft-lbs	57 N-m
	Tensioner Pivot Nut - 1/2-13	1	42 ft-lbs	57 N-m
	Idler & Tensioner Sprocket Nuts - 3/4-10	2	100 ft-lbs	136 N-m
Motor Assembly	Motor Plate Nuts - 3/8-16	4	20 ft-lbs	27 N-m
	Motor Mounting Bolts – 12 mm	4	42 ft-lbs	27 N-m
	Taper Lock Set Screws - 1/4-20 (#1008)	2	55 in-lbs	6.2 N-m
Base CW Assembly	Counterweight Connecting Rod Bushing Clamp Screws - 3/8-16	4	20 ft-lbs	27 N-m
	Bushing Bolts - 1/2-13	8	42 ft-lbs	57 N-m
Drive Assembly	Drive Sprocket Bushing Bolts - 5/16-18	3	15 ft-lbs	20 N-m
	Motor Plate, Utility Panel Mtg. - 3/8-16	6	20 ft-lbs	27 N-m
	C'W Drive Arm Stop Bolts & Pivots - 1/2-13	8	42 ft-lbs	57 N-m
	Transmission Mtg. & C'Rod Bolts - 1/2-13	8	42 ft-lbs	68 N-m
Pan Assembly	Pan Attachment Bolts - 1/2-13	4	42 ft-lbs	57 N-m
	Doubler Plate Bolts - 3/8-16	8	20 ft-lbs	27 N-m
	Pan Connecting Rod Bushing Clamp Screws - 3/8-16	4	20 ft-lbs	27 N-m

Table C-1 – FastBack® Model 260E-G2 Torque Specifications