

11 APPENDIX

11.1 Model Specifications

Specifications by model are shown in the "Table 11-1 ", "Table 11-2 "

Table 11-1

Item		Specifications			
Model		DACS-GN-S015-**-**-I-S		DACS-GN-S060-**-**-I-S	
Capacity		1500 g (600<=>1500 multirange convert) Span adjustment weight: 1 kg		6000 g (3000<=>6000 multirange convert) Span adjustment weight: 5 kg	
Weighing range		6 to 600 g	15 to 1500 g	30 to 3000 g	60 to 6000 g
Minimum graduation		0.05 g	0.1 g	0.2 g	0.5 g
Speed *1		Max. 440 times/min.			Max. 240 times/min.
Accuracy (3σ) *2		± 0.1 g or more	± 0.2 g or more	± 0.4 g or more	± 1 g or more
Product condition	length	46 to 400 mm		58 to 500 mm	
	Width	20 to 320 mm		20 to 400 mm	
	Height	10 to 180 mm (10 to 150 mm with windshield cover equipped) *3			
Weighing conveyor		W: 100 mm × L: 150 mm (SS only) (W: 670 mm × L: 605 mm) W: 160 mm × L: 250 mm (*6) (W: 670 mm × L: 605 mm) (*6) W: 160 mm × L: 350 mm (*6) (W: 670 mm × L: 705 mm) (*6) W: 160 mm × L: 450 mm (*6) (W: 670 mm × L: 805 mm) (*6) W: 240 mm × L: 250 mm (*6) (W: 670 mm × L: 605 mm) (*6) W: 240 mm × L: 350 mm (*6) (W: 670 mm × L: 705 mm) (*6) W: 240 mm × L: 450 mm (*6) (W: 670 mm × L: 805 mm) (*6) W: 320 mm × L: 350 mm (*6) (W: 800 mm × L: 705 mm) (*6) W: 320 mm × L: 450 mm (*6) (W: 800 mm × L: 805 mm) (*6)		W: 240 mm × L: 250 mm (*6) (W: 670 mm × L: 605 mm) (*6) W: 240 mm × L: 350 mm (*6) (W: 670 mm × L: 705 mm) (*6) W: 240 mm × L: 450 mm (*6) (W: 670 mm × L: 805 mm) (*6) W: 320 mm × L: 350 mm (*6) (W: 800 mm × L: 705 mm) (*6) W: 320 mm × L: 450 mm (*6) (W: 800 mm × L: 905 mm) (*6) W: 320 mm × L: 550 mm (*6) (W: 800 mm × L:1005 mm) (*6) W: 320 mm × L: 650 mm (*6) (W: 800 mm × L:1205 mm) (*6) W: 400 mm × L:445 mm (W: 800 mm × L:900 mm) W: 400 mm × L:545 mm (W: 800 mm × L:1000 mm) W: 400 mm × L:645 mm (W: 800 mm × L:1200 mm)	
Material of conveyor belt		Plain belt (urethane)			
Weighing sensor		Strain gage type load cell (high output type)			
Display and interface		Standard type RCU: 7-inch color LCD Tact key switch, command dial			

Table 11-1

Item	Specifications	
Model	DACS-GN-S015-**-**-I-S	DACS-GN-S060-**-**-I-S
Language	Japanese • English	
Preset setting	Up to 300 items can be registered.	
Protection grade	SS (Non-waterproof): IP30 (International standard) CR (Waterproof): IP69K (International standard)	
Belt speed	SS (Non-waterproof): Max.120m/min. CR (Waterproof • Corrosion resistance): Max.95m/min.	SS (Non-waterproof): Max.120m/min. CR (Waterproof • Corrosion resistance): Max.95m/min. Over 3000g, Max.60m/min. for SS and CR.
Use environment *4	Temperature: 0 to 40°C Humidity: 30 to 85% (no condensation)	
Power	Single-phase 100 to 120 VAC (standard) Single-phase 200 to 240 VAC (standard) Single-phase 120 to 240 VAC (UL)	
Power consumption	155 W	255 W
Main body weight	Approx. 80 kg	Approx. 90 kg
Height of belt surface (Jack adjustment)	750 to 900 mm (Adjustment width ± 50)	
Main body material and surface processing	Power source and main body Weigher Conveyor frame Legs	Stainless (SUS304) Stainless (SUS304) SS (non-waterproof): aluminum (alumite) CR (waterproof): Stainless (SUS304) Stainless (SUS304)
Standard equipment	USB slot (for data output) *5	

*1 Capacity varies depending on the conveyor size, shape and condition of the product, as well as the supplied status.

- When zero adjustment is necessary for each weighing, the speed is the half of the described.

*2 Depends on the shape and condition of the product, and environment condition such as vibration of the floor.

*3 Windshield cover is an option.

*4 To keep the weighing accuracy, use the device within the temperature range of $\pm 5^{\circ}\text{C/h}$.

*5 Only the device specified by Ishida can be connected to the USB connector. As USB memory is not attached, purchase an USB memory specified by Ishida.

- Data output is available with the optional printer as well.

*6 CR is 5 mm shorter than the listed dimensions.

Table 11-2

Item		Specifications	
Model		DACS-GN-F006-*/SS-I-S	DACS-GN-F030-*/SS-I-S
Capacity		600 g Span adjustment weight: 600 g	3000 g Span adjustment weight: 3 kg
Weighing range		1.5 to 600 g	3 to 500 g 7.5 to 3000 g
Minimum graduation		0.01 g	0.02 g 0.05 g
Speed *1		Max. 600 times/min.	Max. 440 times/min.
Accuracy (3 σ)*2		± 0.02 g or more	± 0.1 g or more
Product condition	length	46 to 320 mm	58 to 500 mm
	Width	20 to 160 mm	20 to 320 mm
	Height	10 to 180 mm (10 to 150 mm with wind cover equipped) *3	
Weighing conveyor		L: 100 mm $\times$ W: 150 mm L: 160 mm $\times$ W: 250 mm L: 160 mm $\times$ W: 350 mm	L: 240 mm $\times$ W: 250 mm L: 240 mm $\times$ W: 350 mm L: 240 mm $\times$ W: 450 mm L: 320 mm $\times$ W: 350 mm L: 320 mm $\times$ W: 450 mm L: 320 mm $\times$ W: 550 mm
Material of conveyor belt		Plain belt (urethane)	
Weighing sensor		Electromagnetic sensor load cell	
Display and interface		Standard type RCU: 7-inch color LCD Tact key switch, command dial	
Language		Japanese • English	
Preset setting		Up to 300 items can be registered.	
Protection grade		IP30 (International standard)	
Belt speed		Max. 120 m/min.	
Use environment *4		Temperature: 0°C to 40°C Humidity: 30 to 85% (no condensation)	
Power		Single-phase 100 to 120 VAC (standard) Single-phase 200 to 240 VAC (standard) Single-phase 120 to 240 VAC (UL)	
Power consumption		155 W	255 W
Main body weight		Approx. 80 kg	
Height of belt surface (Jack adjustment)		750 to 900 mm (Adjustment width ± 50)	

Table 11-2

Item	Specifications	
Model	DACS-GN-F006-*/SS-I-S	DACS-GN-F030-*/SS-I-S
Main body material and surface processing	Power source and main body Weigher Conveyor frame Legs	Stainless (SUS304) Stainless (SUS304) Aluminum(alumite) Stainless (SUS304)
Standard equipment	USB slot (for data output) *5	

*1 Capacity varies depending on the conveyor size, shape and condition of the product, as well as the supplied status.

- When zero adjustment is necessary for each weighing, the speed is the half of the described.

*2 Depends on the shape and condition of the product, and environment condition such as vibration of the floor.

*3 Wind cover is an option.

*4 To keep the weighing accuracy, use the device within the temperature range of $\pm 5^{\circ}\text{C/h}$.

*5 Only the device specified by Ishida can be connected to the USB connector. As USB memory is not attached, purchase an USB memory specified by Ishida.

- Data output is available with the optional printer as well.