

1 – SUMMARY

The CD30 with software version “L” or higher is compatible with both Wright LT conveyors and PPM VF & Magnatron conveyors. The main changes from the DMT include:

- The CD30/35 runs about half as quiet (10dbA less) as the DMT
- All settings are made by using the touch-panel and display (similar to a VFD touch-panel) that is incorporated into the front panel of the CD30
- The CD30/35 does not come standard with a door potentiometer
- The CD30/35 does come with a local disconnect switch mounted onto the door
- The CD30/35 works as a replacement for both the DMT & MagII controllers, and will be phased in PPM's new standard controller for all applications for the above legacy controllers.

1.1 – CONTROLLER SPECIFICATIONS

- Supply voltage: 115/230 v, +/-15%, 50/60 Hz
- Supply Power Draw: 3 to 4A
- Set Point: display, potentiometer 10kOhm, 0-10vdc, 0(4)-20mA
- Enable Input: contact, 24vdc
- Enable 2nd Setpoint: contact, 24vdc
- Status relay: change over contacts (max 250v, 2A)
- Fuse: 10A, Type B
- Operating Temperature: 0°C to 45°C

1.2 – APPLICATIONS

The CD30/35 has been tested & validated to work on the following equipment:

- VF Advance & Mini at 1200cpm (20hz) to 1450cpm (24.2hz)
- VF Premier & VFX at 750cpm (12.5hz) to 1200cpm (20hz)
- Magnatron at 1500cpm (25hz) to 2100cpm (35hz)

NOTE: CD30/35 will virtually work at any speed from 5hz to 60hz on all equipment, with or without a feedback sensor. The above equipment speed ranges are just guidelines for our typical equipment.

There are two sizes of CD30/35 Controller, a 10A & a 15A controller. The controller required is base on the rules below regarding the application & product density:

- Use the CD30 (10A controller) if:
 - Product density is 20lb/ft³ or less
- Use the CD35 (15A controller) if:
 - Product density is greater than 20lb/ft³, or
 - The conveyor is being fed by a hopper

1.3 – SAFETY CONSIDERATIONS

Safety instructions

This description contains the necessary information for the correct application of the product described below. It is intended for use by technically qualified personnel. Qualified personnel are persons who, because of their training, experience and position, as well as their knowledge of appropriate standards, regulations, health and safety requirements and working conditions, are authorised to be responsible for the safety of the equipment, at all times, whilst carrying out their normal duties and are therefore aware of, and can report possible hazards (definition of qualified employees according to IEC 364).



WARNING!

Hazardous voltage!

Failure to observe can kill, cause serious injury or damage.
Isolate from mains before installation or dismantling work, as well as for fuse changes or post installation modifications.
Observe the prescribed accident prevention and safety rules for the specific application.
Before putting into operation, check if the rated voltage for the unit conforms with the local supply voltage.
Emergency stop devices must be provided for all applications. Operation of the emergency stop must inhibit any further uncontrolled operation.
Electrical connections must be covered.
Earth connections must be checked for correct function, after installation.



Installation

	Check ! Do supply voltage, operating voltage of the conveyor and controller input voltage match ? Is the controller adequately rated for the rated power of the feeder ? What is the vibrating frequency of the feeder ?
	Connect the unit in accordance with the wiring instructions and ensure that earthing is correct !
	Caution ! Incorrect setting of the vibrating frequency can lead to damage of the connected magnets! Carefully check that the correct vibrating frequency has been selected for the magnets used.

Specified use

The units described herein are electrical controllers for installation in industrial plants. They are designed for power adjustment on vibratory feed equipment.

Declaration of Conformity

We confirm that these products conform with the following standards and regulations:
EN 61000-6-2 and EN 61000-6-4 in accordance with Directive 89/336/EEWG

Subject to technical modifications without prior notice.

