



III. Main Specification

Model Items	Horizontal mode	Vertical mode
Voltage	AC 110V/60	
Power	50W	
Sealing Power	300×2 (W)	
Printing power	40×2 (W)	
Sealing speed	0~16 (m/min)	
Sealing width	8 、 10 (mm)	
Temperature controller	0~300 (°C) (Stepless adjustable)	
Height from sealing center to conveyor	10~40 (mm)	200~320 (mm)
Film thickness (monolayer)	≤0.08 mm	
Max. single conveyor loading	≤1 Kg	
Max. overall conveyor loading	≤3 Kg	
Dimension (LXWXH)	950×400×430 (mm)	950×400×640 (mm)
Net Weight	45 Kg	50 Kg



IV. Performance Features

This sealer uses an electronic thermostat control unit and stepless speed-adjusting transmission mechanism. It can seal various plastic film bags in different materials and can also be used with varied packaging production lines. The machine has no limitations on sealing length with high efficiency continuous sealing, reliable sealing quality, and convenient operation.



V. Structure & Working Principle

This machine is made up of the machine frame, speed regulator, sealing temperature control system, transmission and conveyor system, and printing device (see Diagram).

The sealing and printing transmission are driven by one motor, which drives the sealing belts, guiding belts and conveyor belt to work synchronously, as well as make printing mechanism working intermittently.

- 5.1 Once the power is turned ON, the electrothermal elements start to produce heat, which leads to a rapid temperature rise of both upper and lower heating blocks.
- 5.2 Adjust the temperature control and speed control to the required temperature and speed for your application.
- 5.3 The plastic packing bag is transferred by the conveying belt, and its sealing part will be guided into the clearance between two sealing belts,
- 5.4 The bag is clamped by two sealing belts and conveyed into the heating area.
- 5.5 Sealing belts are pressed by two heating blocks and impressing wheels which fuse the plastic film together.
- 5.6 The sealed bag is conveyed into the cooling area for cooling.
- 5.7 The sealed bag is pressed by embossing wheel to make stripe or netted pattern.