

MANUAL & TRAINING GUIDE

A17028 GV38-40

Genesis Servo 2, 3 & 4 Row

Flour Tortilla

Counter Stacker

with Vibration

built for:

Ante Sano LLC



Introduction.....	5	Maintenance and Troubleshooting Guide.....	33
Safety and Handling Guide.....	9	Installation.....	35
Safety	11	Location	35
Warning Labels	12	Infeed Conveyor	35
Machine Handling.....	14	Leveling.....	35
Food Handling	15	Offload Table	35
Additional Safety Considerations	18	Before Initial Use	36
Operator's Guide	19	Electrical.....	37
Machine Description.....	21	Electrical Hookup.....	37
Operation Procedures.....	22	Supply Air.....	37
Pre-Operation.....	22	Air Pressure	37
Start-up	22	Air Hookup.....	37
Normal Shutdown.....	22	Remote Access Connection	38
Emergency Shutdown.....	23	Electrical Panels.....	39
Change-over.....	23	Programming the Variable Speed Drive.....	41
Single Lane Clear Out	23	Air Preparation Unit.....	43
Clearing Jams	23	Main Air Prep Unit	43
Controls.....	24	Air Pressure Regulator / Filter.....	43
Main Disconnect.....	24	Solenoid Valves.....	44
Emergency Stop.....	24	PLC: Direct Logic DL-06	45
Safety Reset	24	PLC: Inputs and Outputs.....	46
Cycle Start	24	Guard Interlocks.....	49
Cycle Stop.....	24	Timers and Count Functions	50
User Interface.....	25	Cleaning	53
Adjustments	30	Maintenance.....	55
Insert Cup Tray	30	Spare Parts Kit	59
Pre-Alignment Guides	30	Troubleshooting	60
Stacking Platform Adjustment.....	31	Appendix A - Training	73
Belt Tension	31	Operator Training.....	75
Photoeyes.....	32	Operator Performance Assessment	77
		Maintenance Training	81
		Maintenance Performance Assessment.....	83
		Appendix B - Drawings and Diagrams	87



Intended Use for A17028 GV38-40:

The Arr-Tech Genesis, Model GV38-40 Counter Stacker can receive flour tortillas arranged in 2, 3 or 4 rows at up to 180 per lane per minute. This unit will receive, count, stack and release package counts ranging from 6 to 36 per stack, depending on product thickness. Each stack can be up to 5” tall. This unit is designed to handle product from **5” to 12” in size**.

Documents included in this manual:

Dimensional Drawing - LFA89A27-119

Electrical Schematic #A17028

Other Arr-Tech Documents included with this manual (see included Service CD):

A17028.pdf

AIR ASSIST-A17028.pdf

AIRCHUTE-G38-9.pdf

INFEED-GV38-1.pdf

INFEEDSTABILIZER-GV38-1.pdf

INSERTTRAYGUARD-G38-9.pdf

INTERUPTFORK-GV38-DF.pdf

LEGS-G38-4.pdf

MAINFRAME-GV38-DF.pdf

OFFLOADTABLE-G38-1.pdf

PHOTOEYE-G38-7.pdf

STACKINGPLATFORM GV38-2.pdf

VIBRATION-GV38-DF.pdf

COG A17028.pdf

MASS PROPERTIES A17028.pdf

COMPLETE BOM.pdf

PLEASE READ YOUR MANUAL BEFORE OPERATING YOUR ARR-TECH EQUIPMENT

Introduction

Company

Arr-Tech Manufacturing, Inc. has been manufacturing counter stackers for the tortilla industry for over 30 years.

Arr-Tech uses high quality components that are built to last. They are supported by a strong stainless steel framework; and protected by exterior side construction. All food contact surfaces are made of food grade plastics and stainless steel materials. This increases longevity and clean up ease. The Counter Stacker is made for heavy and continuous use.

Manual Overview

This manual contains information needed to operate, maintain, and troubleshoot your machine. The following page describes the general safety precautions you should take when you operate the Genesis Flour Counter Stacker.

The main body of the manual contains information on the machine and its operation. The various controls are described. Operating Procedures are shown in step by step detail. Toward the end of the manual you will find maintenance and troubleshooting information.

The Appendixes contain a detailed description of the timers, and a suggested spare parts list.

Throughout this manual:

- The names of all **BUTTONS**, **KEYS** and **SWITCHES** will appear in **BOLD CAPITAL LETTERS**.
- Controls and variable names associated with the User interface appear in ***bold, italic*** type.

Satisfactory operation of any Arr-Tech Counter Stacker depends on proper application, correct installation, and proper maintenance. In addition, modifications to the equipment may result in less than satisfactory performance. The quality of the product being stacked, as well as the presentation and delivery also affect the performance of the Arr-Tech Counter Stacker.

Contact Information:

Arr-Tech Manufacturing Incorporated
3801 W. Washington Ave
Yakima, WA 98903
Internet: www.arr-tech.com

<u>Contact Name</u> <u>E-Mail Address</u>	<u>Cell #</u> <u>Direct Phone</u>	<u>Toll Free</u>	<u>Department</u>
Kevin Pearson kpearson@arr-tech.com	509-728-3136 509-654-7607	800-998-4301 ext. 208	Sales / VP
Matt Marquis mattm@arr-tech.com	509-728-1129 509-853-2170	800-998-4301 ext. 118	Sales
Trevor Dohrman tdohrman@marq.net	509-728-2974 509-654-7609	800-998-4301 ext. 215	Service Manager
Gene Barton gbarton@marq.net	509-728-3148 509-654-7610	800-998-4301 ext. 102	Tech Support / Parts
24 hr Service	509-728-3238	800-998-4301 ext. 399	Service

PLEASE READ YOUR MANUAL BEFORE OPERATING YOUR ARR-TECH EQUIPMENT

Customer to provide:

Required Surge Protection

Voltage: 230V +/- 10%, 3 Phase, 60Hz +/- 0.2 Hz

Fusing: 20Amp

Allowable Voltage Drop: 22VAC (Minimum Voltage 208VAC)

Machine Amps: 14.42 Amps

Minimum Supply Size: 12Awg or 3.31mm²

Peak Starting Current: 35 Amps

Approximate Running Current: 8 Amps

Air Required: 5 CFM @ minimum 80 psi (5.6 Bar), Clean Dry Air

Maximum Pressure 100 psi (6.9 Bar), Clean Dry Air

Minimum Pressure 65 psi (4.5 Bar), Clean Dry Air

IP Rating 52

Operating Noise Level: 85dB @ 3ft (1M)

Peak Noise Level: 102dB @ 3Ft (1M)

Controller/Display:

Controller: Direct Logic DL-06 PLC

Display: 6" C-More Color Touch Screen

Production:

Production Rate: 3600 Dozen/Hr

Stack Count: Depends on Thickness

Maximum Stack Height: 5 Inches

Environmental Conditions:

Transport Conditions

-13°F to 131°F (-25°C to 55°C)

80% RH W 131°F (55°C)

6562Ft (2000M) Altitude)

Storage Conditions

-13°F to 131°F (-25°C to 55°C)

80% RH W 131°F (55°C)

3280Ft (1000M) Altitude)

Operating Conditions

Clean and Dry Environment required for safety and optimal performance.

41°F to 85°F (-5°C to 30°C)

50% RH W 104°F (40°C)

3280 Ft (1000M) Altitude)

