

Implementing an HTML5 mobile simulation utilizing web workers

Submitted on 27/11/2020

authored by

Lari Alakukku (528362), Miika Rouvinen (356770), Ilkka Malassu (430463)

Index Terms—HTML5, web, workers

Abstract—HTML5 introduced web workers as a way to utilize concurrent computation in the domain of web-based JavaScript applications. This paper follows the implementation of a computer physics simulation and compares the architectural decisions that can be applied to it. Different architectures with and without web workers are analysed and compared in terms of their performance metrics such as FPS, memory usage and message transfer time.

I. INTRODUCTION

The internet has progressed from a distributed document sharing system to a platform that can host computationally demanding applications. This evolution makes performance a crucial web-client requirement. The modern browser provides a possibility to develop intricate web applications utilizing only HTML, CSS and JavaScript. The developers of a web-based game, for example, need to optimize their code taking the processing capability of different browsers into account. Current hardware mostly focuses on concurrent execution while many web applications still only use the main browser thread. HTML5 introduced web workers as a first step towards concurrent execution in web applications. [1]

Web workers offload processing tasks from the main browser thread to background worker threads, requiring the platform to have basic support for concurrency. The communication between the threads is facilitated with message sending. Web workers can not use DOM operations or access window objects and parent objects. Also, direct data sharing between the main thread and the worker threads is not possible. The process of main thread web worker communication is illustrated in Figure 1. [1], [2]

This paper follows and compares the architecturally different implementations of a computer physics simulation. These architectures apply different ways to implement a web-based application with and without

web workers. The comparison is done with respect to performance metrics such as FPS, memory usage and message transfer time. After this introduction, section II of this paper covers the literature and studies related to web workers. Section III describes all the physics simulation implementations made for the purposes of this research paper. Section IV evaluates and compares the performance of these implementations and Section V concludes this paper.




Fig. 1. Communication between the main thread and worker threads [2].

II. RELATED WORK

For web-based games, Erbad et al. [1] propose a concurrent processing solution called DOHA, which consists of game event-loops running in worker threads and MultiProc, which is the module for scheduling, state management and other concurrent execution related tasks. Their game implementation had three main components: simulation, graphics rendering and AI. The main thread handles rendering and offloads game event processing to web workers. This communication also requires the sending of state information. In general, DOHA offered better scalability and responsiveness across different platforms. However, thread communication required replicating state across workers, which increased jitter.

Zhang et al. [3] introduce WWOFF, which is a framework for seamlessly offloading web workers to the cloud. On average, the framework achieved energy savings of 85% on devices such as mobile phones, desktop computers and pads. The performance of the devices improved by a factor of 2-4.

Verdú et al. [4] examine how utilizing web workers scales the performance of a JavaScript application. They found that the optimal number of workers depends on various factors such as the CPU architecture and the browser. Using a large number of web workers did not prove to be beneficial compared to using only a few.

III. IMPLEMENTATION

Here we present our implementation.

A. Context

Maybe a subsection if needed.

IV. EVALUATION

Here we present our evaluation of the implementation.

V. CONCLUSIONS

We conclude our research paper here.

REFERENCES

- [1] A. Erbad, N. Hutchinson, and C. Krasic, "Doha: Scalable real-time web applications through adaptive concurrent execution," Apr. 2012. DOI: 10.1145/2187836.2187859.
- [2] Y. Watanabe, S. Okamoto, M. Kohana, M. Kamada, and T. Yonekura, "A parallelization of interactive animation software with web workers," in *2013 16th International Conference on Network-Based Information Systems*, 2013, pp. 448–452. DOI: 10.1109/NBiS.2013.74.
- [3] J. Zhang, W. Liu, W. Zhao, X. Ma, H. Xu, X. Gong, C. Liu, and H. Yu, "A webpage offloading framework for smart devices," *Mobile Networks and Applications*, vol. 23, Jan. 2018. DOI: 10.1007/s11036-018-1009-z.
- [4] J. Verdú and A. Pajuelo, "Performance scalability analysis of javascript applications with web workers," *IEEE Computer Architecture Letters*, vol. 15, no. 2, pp. 105–108, 2016. DOI: 10.1109/LCA.2015.2494585.