



EXERCISES — Fact Iter

version #cb69afd89690e908c9ef3ff2545b93df54f86b1f



Copyright

This document is for internal use at EPITA ([website](#)) only.

Copyright © 2023-2024 Assistants <assistants@tickets.assistants.epita.fr>

The use of this document must abide by the following rules:

- ▷ You downloaded it from the assistants' intranet.*
- ▷ This document is strictly personal and must **not** be passed onto someone else.
- ▷ Non-compliance with these rules can lead to severe sanctions.

Contents

| | | |
|---|---------|---|
| 1 | Goal | 3 |
| 2 | Example | 3 |

*<https://intra.forge.epita.fr>

File Tree

```
fact_iter/  
└─ fact_iter.sh  (to submit)
```

Authorized commands : You are only allowed to use the following commands

- builtins

Reminder : Grant execution permission to your scripts before pushing them

1 Goal

You have to write a script taking only one number as argument and printing the factorial of this number on the standard output followed by a line break.

If you do not have exactly one argument, you have to exit 1. Otherwise, you will exit 0.

You do not have to handle the negative numbers.

2 Example

```
42sh$ ./fact_iter.sh  
42sh$ echo "$?"  
1  
42sh$ ./fact_iter.sh 1  
1  
42sh$ echo "$?"  
0  
42sh$ for i in $(seq 1 5); do ./fact_iter.sh "$i"; done  
1  
2  
6  
24  
120  
42sh$ echo "$?"  
0
```

I must not fear. Fear is the mind-killer.