

The schematic diagram illustrates the TRF372017IRGZR circuit, which is a 2.4 GHz RF front-end and baseband processor. The circuit is divided into three main sections:

- Loop Filter:** This section is highlighted with a blue border. It includes a feedback loop with capacitors CLF1 (270pF), CLF2 (4.7nF), and CLF3 (4.7nF). A resistor RLF1 (1.5k) is connected in parallel with CLF2, and RLF2 (1.5k) is connected in series with CLF3. The output is CP_OUT, and the input is VTUNE.
- RF Front-End:** This section includes the RF input (RFIN) and the RF output (RFOUT). It features a matching network with capacitors CCQ1 (100nF) and CCQ2 (100nF), and a resistor RDIFF2 (100R). The RF output is connected to the RF input of the baseband processor.
- Baseband Processor:** This section includes the baseband processor (U2, TRF372017IRGZR) and the baseband output (BBIN and BBIP). It features a matching network with capacitors CD15 (100pF), CD14 (100pF), CD12 (4.7pF), and CD13 (4.7pF). The baseband output is connected to the baseband input of the baseband processor.

The circuit is powered by a +5V supply and a +3.3V supply. The +5V supply is connected to the VCC_DIG and VCC_LO1 pins. The +3.3V supply is connected to the VCC_PLL and VCC_OUT pins. The circuit also includes several other components, such as resistors RDBK, RDBK, and RDBK, and capacitors CBULK5, CBULK6, CBULK7, and CBULK8.

[illegible]