

Production Cutover — Information Request

Everything the MyInstantAI technical team needs to provide so the marketplace can boot on hardened production (P0-5). The application is **built and verified**; this is a configuration handoff — each item maps to an environment variable the code reads.

- Fill-in & return
- Grounded in code
- Blocker P0-5

00 Purpose & how to respond

The app **fails closed at boot** if production config is incomplete — so every row below is a specific value or confirmation we need from your side (Azure, identity, billing, model, Key Vault, DNS). Fill the **“Your response”** column or mark  **pending** /  **ready**.

 **Do not paste live secrets into this document.** Load secret values (client secrets, API keys, connection strings) **directly into the deployment’s Azure Key Vault** and mark the row **loaded** → **<name>**, or share via a secure channel. Non-secret values (URLs, issuer, deployment names, regions) can be filled in here directly.

01 Ownership at a glance — from MIGRATION_RUNBOOK.md / B2B_ONBOARDING.md

MYINSTANTAI OWNS

Azure subscription/RG, DNS/Front Door, OIDC identity + workspace minting, the wallet/billing gateway, model keys, Key Vault, and the native app release.

MOVE DIGITAL OWNS

The marketplace app, onboarding UX, catalogue, and verification —  **complete**.

02 Decisions to confirm first — these cascade into several rows below

#	DECISION	OPTIONS	YOUR CHOICE
D1	Model path	Azure OpenAI direct (azure) · or your model gateway (gateway)	
D2	Consumer identity	Your OIDC issuer · or Google as the IdP	
D3	Azure subscription + tenant→partner mapping	Which subscription hosts it; how tenants map to partners	
D4	Region / data residency	Per market — Postgres + model co-located	

03 Identity / OIDC

You own identity + workspace minting → `MIAI_AUTH_MODE=oidc`

ITEM & ENV VAR	WHAT WE NEED	YOUR RESPONSE
Issuer <code>MIAI_OIDC_ISSUER</code>	OIDC issuer URL	
Client <code>MIAI_OIDC_CLIENT_ID</code> / <code>_SECRET</code>	App registration (secret → Key Vault)	
Token validation <code>MIAI_OIDC_AUDIENCE</code> / <code>_JWKS_URL</code>	Audience + JWKS URL	
Sample token	A sample JWT containing <code>workspace_id</code> so we can verify the token → tenant mapping against staging	
Redirect URIs	Confirm you'll register our prod callback URL(s) — we supply the exact URLs once the FQDN is set (\$06)	

04 Wallet / billing gateway — ⚠ critical path (P0-4)

Real billing runs through your gateway, not Paystack → `MIAI_WALLET_MODE=http`

ITEM & ENV VAR	WHAT WE NEED	YOUR RESPONSE
Gateway URL <code>MIAI_WALLET_API_URL</code>	Base URL	
Auth <code>MIAI_WALLET_API_KEY</code>	API key (→ Key Vault)	
API contract	Debit + credit + balance/ledger-read endpoints, with request/response shapes	
Idempotency	How idempotency keys are honoured (we send one per turn)	
Liveness	✅ confirm the gateway is live, durable, and idempotent in production	

The single hardest dependency. Everything else is a value we wire in; this one is a build-status confirmation on your side. The cutover checklist treats “gateway not yet durable” as an **immediate NO-GO**.

05 Model access — per Decision D1

If Azure OpenAI → `MIAI_MODEL_MODE=azure`

ITEM & ENV VAR	WHAT WE NEED	YOUR RESPONSE
Endpoint <code>AZURE_OPENAI_ENDPOINT</code>	Endpoint URL	
Key <code>AZURE_OPENAI_API_KEY</code>	Key (→ Key Vault)	
Deployments	Two deployment names: a large (gpt-4o-class) + a small/cheap one — we map model tiers to them	
Region	Azure region (per D4)	

Or, if your model gateway → `MIAI_MODEL_MODE=gateway`

ITEM & ENV VAR	WHAT WE NEED	YOUR RESPONSE
Gateway <code>MIAI_MODEL_GATEWAY_URL</code> / <code>_KEY</code>	URL + key (→ Key Vault)	

06 Infrastructure — your Azure subscription

ITEM & ENV VAR	WHAT WE NEED	YOUR RESPONSE
Database <code>DATABASE_URL</code>	Azure Postgres connection string, SSL required (→ Key Vault)	
Redis <code>UPSTASH_REDIS_REST_URL</code> / <code>_TOKEN</code>	Redis URL + token (or Azure Cache) — required once >1 replica for shared rate-limits	
FQDN / domain <code>APP_URL</code>	Production hostname + TLS (DNS/Front Door) — also needed for OIDC + connector redirect URIs	
Key Vault	Confirm the Vault exists and the Container App can reference secrets from it	

07 Connectors — optional per end-customer, needed for any live at launch

ITEM	WHAT WE NEED	YOUR RESPONSE
In-scope list	Which connectors go live at launch (Slack, Google Calendar/Gmail, HubSpot, M365, Shopify, ...)	
OAuth apps + branding	Whose OAuth apps back them (consent-screen branding). If yours → client ID/secret per connector (→ Key Vault)	
Redirect URIs	We provide the exact callback URLs to register once the FQDN (§06) is set	
Staging test creds	So your team can exercise the live connector path on staging before cutover	

Note: `GOOGLE_OAUTH_CLIENT_ID` / `_SECRET` is **dual-use** — it powers both Google sign-in and the Google Calendar/Gmail connectors.

08 Release & ops

ITEM	WHAT WE NEED	YOUR RESPONSE
Azure / pipeline access	Who runs <code>az deployment</code> / holds the reviewer role on the release	
Native app	WebView / deep-link (or native chat client) release plan + timing	

ACCEPTANCE — “GREEN” LOOKS LIKE

Wired correctly, `GET /api/health` returns:

```
{ status:"ok", hardening:"ok",
  mockRailsAllowed:false, sandboxMode:false,
  authMode:"oidc", walletMode:"http",
  modelMode:"azure", storeBackend:"postgres" }
```

Then one real OIDC login + one real wallet debit prove reachability. Full go/no-go: `CUTOVER_CHECKLIST.md`.

WHAT MOVE DIGITAL PROVIDES IN RETURN

- ☐ The container image (pinned SHA) + full env map (`AZURE_DEPLOYMENT.md`).
- ☐ Strong random values for the app-level secrets (`OAUTH_TOKEN_SECRET`, `MAIA_SESSION_SECRET`, ...) for you to load into Key Vault.
- ☐ The exact prod redirect URIs (OIDC + connectors) once the FQDN is set.
- ☐ Boot-hardening preflight + cutover smoke verification on the day.