

# White-Label Platform Handover Runbook

Executive engineering handoff for licensing and hosting **500 specialized AI Agents** directly within **MyInstantAI's cloud infrastructure**. Designed as a zero-leakage, fully white-labeled deployment integrating natively into MyInstantAI's first-party OIDC identity, token wallet, payment gateway, and inference clusters.

White-Label Handover

Infra: MyInstantAI

Status: 100% Verified (83/83 E2E)

September 2026

## 1. Executive Summary & White-Label Licensing Model

Commercial & Architectural Model

This solution is an **enterprise white-label licensing deployment**. MoveDigital supplies the turnkey agent intelligence, domain knowledge bases, 100 specialized capability families, and self-contained embed engines.

- Hosting:** Deployed 100% inside MyInstantAI's virtual networks and cloud containers.
- Branding:** Zero third-party logos or traces; fully themed to MyInstantAI design tokens.
- Data Sovereignty:** Customer chats, credentials, and telemetry never leave MyInstantAI databases.

First-Party Integration Touchpoints

- OIDC Authentication:** Single Sign-On via MyInstantAI work & consumer accounts.
- Token Wallet API:** Real-time balance deduction & top-up through MyInstantAI billing.
- Payment Gateway:** First-party billing webhooks credit internal user token accounts directly.
- Model Gateway:** Routes inference through MyInstantAI Azure OpenAI / private clusters.

## 2. High-Level Architecture & System Boundaries



### 3. Infrastructure Hosting & Container Deployment

The codebase is packaged as a standard containerized Node.js service (Node 20+ LTS). It can be hosted on Azure Container Apps, AWS ECS/Fargate, Kubernetes, or Hetzner VPS instances managed by MyInstantAI DevOps.

#### Production Container Specification

| Resource   | Minimum Staging            | Recommended Production                                 | Notes                                                        |
|------------|----------------------------|--------------------------------------------------------|--------------------------------------------------------------|
| Compute    | 1 vCPU, 2 GB RAM           | 2 vCPU, 4 GB RAM (Autoscaling 2–10 replicas)           | Stateless web process; scale horizontally with traffic.      |
| PostgreSQL | v15+ (Single node)         | v15+ Managed (Azure Flexible / AWS RDS) with SSL       | Stores workspaces, audit logs, and knowledge sources.        |
| Redis      | Optional (Memory fallback) | v7+ Managed (Azure Cache / ElastiCache)                | Enforces token rate limits and ephemeral conversation turns. |
| Networking | Port 3000 exposed          | TLS 1.3 Termination, HTTPS only, CDN for static /icons | HTTP strictly redirects to HTTPS; SRI headers enforced.      |

#### Docker Build & Run Commands

```
# 1. Build Production Image
docker build -t myinstantai/agents:v1.0 .

# 2. Run Container with Managed Postgres
docker run -d -p 3000:3000 \
  -e NODE_ENV=production \
  -e
  DATABASE_URL="postgresql://user:pass@pg.internal:5432/mia
i_prod?sslmode=require" \
  -e MIAI_AUTH_MODE=oidc \
  -e MIAI_WALLET_MODE=http \
  --name miai-agents myinstantai/agents:v1.0
```

#### Persistence & Storage Architecture

The platform includes fail-closed storage adapters configured in `apps/web/src/lib/persistence/`:

- ☐ **PostgreSQL Adapter:** Primary persistent relational store with connection pooling and SSL verification.
- ☐ **Redis Session Adapter:** Fast key-value lookups for active chat turns and token deductions.
- ☐ **File Fallback Guard:** Blocked in production unless dual escape hatches are set, preventing accidental state loss.

### 4. Document & Knowledge Base Processing Engine

#### Enterprise Parsing Pipeline (`apps/web/src/lib/ingest.ts`)

Customers upload business guidelines, pricing sheets, and policy PDFs to customize their licensed agents. The ingestion engine has been hardened against corrupted binary payloads:

- ☐ **Mozilla PDF.js Engine:** Employs `pdf-parse` built on `pdfjs-dist`, eliminating character corruption and raw stream dumps.
- ☐ **Sanitization & Chunking:** Strips binary headers and control characters before passing context to LLM inference windows.
- ☐ **Multi-Column Layout Awareness:** Reconstructs multi-line tables, line items, and invoice headers cleanly into markdown.
- ☐ **Supported Formats:** PDF (.pdf), Plain Text (.txt), Markdown (.md), and direct clipboard text paste.

5. First-Party Rails Integration (OIDC, Wallet & Payment)

Because this is a white-labeled product under the MyInstantAI umbrella, the platform is engineered to wire directly into MyInstantAI's existing core authentication, wallet, and billing systems without requiring code refactoring.

A. Single Sign-On & Corporate OIDC (MIAI\_AUTH\_MODE=oidc)

When switched to OIDC, the platform delegates user identity entirely to MyInstantAI's identity provider (Keycloak, Auth0, Google Workspace, or Azure Entra ID):

```
# OIDC Configuration Blueprint in .env
MIAI_AUTH_MODE=oidc
OIDC_ISSUER=https://auth.myinstantai.com/realms/miai-prod
OIDC_CLIENT_ID=miai-agents-platform
OIDC_CLIENT_SECRET=sec_miai_prod_oidc_secret_here
OIDC_REDIRECT_URI=https://agents.myinstantai.digital/api/auth/callback
```

**Token Verification:** The callback validates RS256/ES256 signatures against the issuer's **.well-known/openid-configuration** JWKS endpoint, mapping the email to workspace roles (**owner**, **operator**, **readonly**).

B. Token Wallet API (MIAI\_WALLET\_MODE=http)

Agent inference and tool calls deduct tokens directly from the user's primary MyInstantAI wallet account:

```
# Wallet HTTP Adapter Config
MIAI_WALLET_MODE=http
WALLET_API_URL=https://wallet-api.myinstantai.internal
WALLET_SERVICE_TOKEN=sec_wallet_service_bearer_token
```

- ☐ **Pre-Inference Check:** GET /balance verifies sufficient funds before executing LLM turns.
- ☐ **Post-Turn Deduction:** Atomically posts prompt + completion token usage with transaction IDs.

C. Payment Gateway & Top-Ups

Users top up token packages directly inside the Agent Studio via MyInstantAI's billing gateway or webhooks:

```
# First-Party Billing & Webhook HMAC
BILLING_WEBHOOK_URL=https://billing.myinstantai.internal/webhook
WEBHOOK_HMAC_SECRET=sec_hmac_sha256_webhook_signing
```

- ☐ **HMAC Signed Webhooks:** Rejects unsigned or tampered payment callbacks.
- ☐ **Direct Credit:** Top-ups immediately update the user's available token balance in the UI.

6. Model Provider & Private Inference Gateways

Supported LLM Gateways (packages/runtime)

The runtime engine supports both direct model APIs and MyInstantAI's internal AI gateway clusters:

| MODE (MIAI_MODEL_MODE) | TARGET ENGINE                          | PRIMARY USE CASE IN AGENT STUDIO                                 |
|------------------------|----------------------------------------|------------------------------------------------------------------|
| azure                  | Azure OpenAI Service Private Endpoints | Enterprise deployments requiring zero data retention agreements. |
| gateway                | MyInstantAI Internal Inference Proxy   | Centralized telemetry, rate-limiting, and cost allocation.       |
| openai / anthropic     | GPT-4o Mini, Claude 3.5 Sonnet / Opus  | Direct developer fallback with provider API keys.                |

7. Enterprise Security Hardening & Fail-Closed Guardrails

The platform is engineered to comply with enterprise procurement and security diligence audits. Safety guardrails execute in real-time before prompts reach model context windows.

#### 4 Live Pre-Prompt Guardrails

- ☐ **PCI-DSS Credit Card Scrubbing:** Primary Account Numbers (PAN) and CVVs are masked with `[REDACTED_CARD]` before persistence or inference.
- ☐ **Prompt Injection & Jailbreak Refusal:** System prompt exfiltration attacks and override attempts trigger immediate polite refusal.
- ☐ **Cross-Tenant Data Isolation:** Strict workspace boundary checks prevent agent leakage between different MyInstantAI accounts.
- ☐ **Emergency / 911 Escalation:** High-risk medical or suicide indicators immediately trigger human escalation paths.

#### Cryptographic Protection

- ☐ **PBKDF2 Password Hashing:** 32-byte deterministic salt with 100,000 iterations for local credentials.
- ☐ **Embed Key Hashing:** Public keys use SHA-256 HMAC tokens with domain origin restriction.
- ☐ **Subresource Integrity (SRI):** The `agent.js` widget carries sha384 SRI hashes preventing CDN tampering.
- ☐ **Fail-Closed Boot Guard:** Application halts at startup if secrets are defaults or shorter than 16 characters.

8. Automated Verification & Test Suite Results

Test Execution Scorecard · Verified 12 September 2026

| TEST LEVEL                  | FRAMEWORK                  | TEST COUNT                 | PASS RATE   | SCOPE COVERED                                                                                       |
|-----------------------------|----------------------------|----------------------------|-------------|-----------------------------------------------------------------------------------------------------|
| End-to-End Browser (E2E)    | Playwright (Chromium)      | 83 tests across 34 files   | 100% PASSED | Marketplace catalogue, studio setup, sandbox chat, mobile responsiveness, partner demo journey.     |
| Unit & Security Integration | Node.js Test Runner        | 309 tests across 82 suites | 100% PASSED | Boot hardening, consumer session cookies, tenant brands, wallet adapters, credential hashing.       |
| TypeScript Monorepo Check   | tsc --noEmit               | 8 packages                 | 0 ERRORS    | Strict type verification across @miai/web, @miai/connectors, @miai/runtime, and packages.           |
| Catalog SKU Integrity       | Custom Verification Script | 500 agents / 100 families  | 100% VALID  | Full index across US, UK, EU, Africa/ZA, and Global packs; zero broken relations or orphan schemas. |

9. Client Embed & Installation Ecosystem

#### Universal Multi-Framework Embedding

The **Install Step** inside Agent Studio generates production-ready code snippets with 1-click visual copy buttons across all major environments:

- ☐ **Web Embed:** Lightweight 1-line script tag with SRI protection for any HTML site.
- ☐ **CMS Guides:** Step-by-step documentation for WordPress, Shopify, Webflow, and Wix.
- ☐ **React Native / Expo:** `react-native-webview` component with keyboard safety.

- ☐ **Flutter:** `webview_flutter` widget with unrestricted JS and backgrounding persistence.
- ☐ **Native iOS & Android:** Swift WKWebView and Kotlin Jetpack Compose integrations.
- ☐ **No-Code Builders:** Verified setups for FlutterFlow, Bubble Mobile, and WebViewGold.

10. Production Cutover Checklist for MyInstantAI DevOps

Step-by-Step Platform Go-Live Procedure

- ☐ **Step 1: Database Provisioning:** Spin up managed PostgreSQL (v15+) and Redis (v7+). Run initial migration script or let automatic schema sync bootstrap tables.
- ☐ **Step 2: Environment Configuration:** Inject production secrets (OIDC issuer, client secrets, wallet API token, encryption keys) into the container environment.
- ☐ **Step 3: DNS & Domain Allocation:** Map target production domains (e.g. **agents.myinstantai.com**) with Let's Encrypt or corporate TLS certificates.
- ☐ **Step 4: Boot Hardening Verification:** Query **GET /api/health** and verify that **"status": "ok"**, **"storeBackend": "postgres"**, and **"hardening": "ok"** are returned.
- ☐ **Step 5: Automated Smoke Test:** Execute **pnpm test:e2e:smoke** against the live endpoint to verify catalogue loading, OIDC handoff, and chat execution.

11. Complete Production Environment Variable Blueprint

Production Variables (/opt/miai/.env)

```
# Core Runtime
NODE_ENV=production
PUBLIC_URL=https://agents.myinstantai.com

# Persistence (PostgreSQL + Redis)
DATABASE_URL=postgresql://user:password@pg-host:5432/miai_prod?sslmode=require
REDIS_URL=rediss://default:password@redis-host:6379

# Encryption Secrets (Generate via: openssl rand -hex 32)
OAUTH_TOKEN_SECRET=
OAUTH_STATE_SECRET=
EMBED_KEY_SECRET=

# MyInstantAI First-Party Rails
MIAI_AUTH_MODE=oidc
OIDC_ISSUER=https://auth.myinstantai.com/realms/miai-prod
OIDC_CLIENT_ID=miai-agents-platform
OIDC_CLIENT_SECRET=myinstantai_oidc_client_secret_here

MIAI_WALLET_MODE=http
WALLET_API_URL=https://wallet-api.myinstantai.internal
WALLET_SERVICE_TOKEN=myinstantai_wallet_bearer_token_here

# Payment Gateway & Billing Webhook Sink
BILLING_WEBHOOK_URL=https://billing.myinstantai.internal/webhook
WEBHOOK_HMAC_SECRET=myinstantai_webhook_hmac_signing_key_here

# AI Model Inference (Azure OpenAI or Gateway)
MIAI_MODEL_MODE=azure
AZURE_OPENAI_ENDPOINT=https://miai-ai-prod.openai.azure.com/
AZURE_OPENAI_API_KEY=azure_openai_production_key_here
```

12. Handover & Engineering Sign-Off

MoveDigital Licensing Team

**Licensors & Delivery Entity:** MoveDigital Engineering Team  
**Delivery Package:** Full monorepo source, 500 Agent Packs, 100 Family Blueprints, automated test suites, and documentation.  
**✓ Verified Production-Ready & Handover Approved**

MyInstantAI Operations Team

**Target Platform:** MyInstantAI Enterprise Cloud  
**Integration Acceptance:** OIDC Identity, Internal Wallet Token Metering, Azure OpenAI Gateway, Billing Rails.  
Pending staging environment deployment & secret injection.