

Tel: 015 293 1459 Fax:015 293 0368

> P.O. Box 465 Ladanna, 0704

43 Staal Street Ladanna Polokwane 0704

# Multi Pre-Packed Under water Gunnite

Natural aggregate, High Strength, Non Shrink, water proof Gunnitable mortar. Packed in 25kg bags.

#### Description

Multi Pre-Packed Gunnite is a Pre-mixed ready to use Gunnitable water proof mortar blend. The product consists of a graded silicious sand blended with Portland cement (52.5), proprietary chemicals, fibres, waterproofing additives and set controlling materials to achieve controlled setting and workability characteristics with no shrinkage.

#### **Typical Applications**

- \* Repairs to heavy wear areas such as water canals.
- \* Repairs to areas that are water logged
- \* Repairs to areas that has running water
- \* Repairs to concrete surfaces
- \* Material must be applied as a low slump mortar mix.

#### **Advantages**

- \* Economical
- \* Can be applied in wet areas
- \* Easy to use and apply
- \* Concrete appearance
- \* High final strengths
- \* Bonds well to existing concrete surface

## **Typical Properties**

- \* Non Shrink
- \* Operating temperatures 10°C 40°C
- \* Cement water ratio constant at the recommended water content

Water demand: 5.5 - 6.0L / 25kg bag

Storage Life: Up to 1 year when stored under cover

and in dry condition

# Mixing Instructions Preparation

- \* All equipment must be free of grease, oil and dirt
- \* The area to be repaired must be cleaned of all dust, sand and grime.
- \* The wet areas need to be properly washed with water to expose the area to which the water proof Gunnite must be applied.

#### **Gunnite Application**

- \* Pour approximately three quarters of the required water into the mixer
- \* Slowly start the mixer and gradually add the powdered product
- \* As the paste stiffens add the balance of the required water to form a slurry that will be pumped onto the water/damped surface
- \* The mixed product must then be transfered into a suitable Gunnite application machine, equipped with the correct pressure to ensure that the product paste is transferred to the wet surface area

- \* Using a straight edge, strike off the excess Gunnite and level the wet surface using a standard steel trowal.
- \* let the Gunnite material harden on its won even if it is confined under water.
- \* No curing compound will be required since the damp conditions will act as a curing membrane.
- \* The strength development of Multi 1038 under water Gunnite is dependent on the water demand of the product (.L/25Kp) wet conditions into which the product has been sprayed, temperature of the environment and the duration of the product insitu.
- \* The 28 day strengths will range between Mpa at a water demand of \_\_\_\_L / 25 kilogram bag.

#### **Watch Points**

- \* Site tests should be determined on the desired placing consistency.
- \* Excess water demand will render the repellency againts water and affect the final strengths of the finished Gunnited product in place
- \* Continuous Gunniting of the product is strongly recommended in order tyo prevent the inclusion of water in the Gunnited product.
- \* Do not use contaminated water or water in an amount not specified.

#### **Cleaning Instructions**

\* Clean all mixing and application equipment with water immediately after use, to prevent material front setting in the equipment

## **Packaging**

Multi Pre-Packed 1038 under water Gunnite is supplied in 25 kilogram water resistant Polypropylene bags

## Guarantee

REG No: 2003/054665/23

The product is guaranteed when use in accordance with correct product application and instruction procedures. For further technical information, please contact MCC LIMPOPO

#### **Quality Assurance**

Multi Pre-Packed 1038 underwater Gunnite is manufactured under strict quality control procedures and tested in accordance with proven quality testing procedures and standards.

## **Environmental and Safety Precautions**

Multi Pre-packed 1038 under water Gunnite contains Portland cement and is alkaline on contact with water.

VAT No: 4470209109



Tel: 015 293 1459 Fax:015 293 0368

> P.O. Box 465 Ladanna, 0704

43 Staal Street Ladanna Polokwane 0704

# Multi Pre-Packed Under water Gunnite

REG No: 2003/054665/23

VAT No: 4470209109

- \* Avoid splashing into eyes or contact with skin.
- \* Use the required protective clothing, gloves and goggles.
- \* In case of eye contact, flood eyes repeatedly with water.
- \* Wash hands thoroughly after handling.