

## MULTI FEATHEREDGE 1050

### Permanent Thin Concrete Repairs

#### Description

MULTI FEATHEREDGE 1050 is a two-component polymer / cement system for permanent thin concrete repairs and being similar in appearance to that of plain concrete.

#### Typical Applications

- \* Leveling and smoothing rough or worn concrete
- \* Patching in thin concrete repairs from 6mm down to featheredge
- \* Rubbing concrete
- \* Joint filler for concrete floors
- \* Floor under lays
- \* Skim coat applications
- \* Leveling floors to receive carpets and vinyl tiles
- \*

#### Advantages

- \* Self-bonding
- \* No priming necessary
- \* Used on concrete, wood, steel and masonry
- \* Can be applied to surfaces previously painted with water based acrylics
- \* Interior or exterior use
- \* Can be used above and below grade
- \* Similar in appearance to concrete

#### Directions for Use

MULTI FEATHEREDGE 1050 has been formulated to allow a thin, hard cementitious coating over concrete, masonry, wood and steel. A sound base is essential for good repairs. Remove all oils, grease, and dirt, disintegrated or unsound concrete from the areas to be repaired. When covering wood, clean the surface and seal with undiluted MULTI BOND SBR 1070 using a brush or roller. Allow the surface to become tacky before applying MULTI FEATHEREDGE 1050.

- \* Roughen surfaces to receive MULTI FEATHEREDGE 1050
- \* Pre-saturate area to be repaired
- \* Place the MULTI FEATHEREDGE 1050 in a clean container
- \* Add the MULTIBOND SBR 1070 and hand mix to a workable consistency
- \* Mix only the quantity that can be placed in 20 minutes
- \* To eliminate air pockets and provide a good bond, work the product firmly into the prepared surface
- \* Delay trowelling until surface has begun to harden
- \* Cure repairs with potable water

**Note:** Mix MULTI FEATHEREDGE 1050 with 5 litres MULTIBOND SBR 1070 and 1 litre water.

#### Yield

25kg of MULTI FEATHEREDGE 1050 mixed with 5 litres of MULTIBOND SBR 1070 will yield 12 litres. The contents cover 3m<sup>2</sup> at 4mm depth.

#### Packaging

Supplied in 25 litre buckets containing 25kg MULTI FEATHEREDGE 1050 and 5 litres of MULTI BOND SBR 1070.

#### Quality Assurance

MCC LIMPOPO production and testing programmes comply with local and international

#### Updates

This data sheet supersedes all previous issues prior to this date: 31/05/97.