

MULTI TILE BOND 555

Adhesive and Grout Additive

Description

MULTI TILE BOND 555 is a milky white liquid, produced from styrene and butadiene by high-pressured emulsion polymerisation. The latex contains microscopic particles of synthetic rubber, dispersed in an aqueous solution.

Typical Applications

MULTI TILE BOND 555 replaces the mixing water when using cement based MULTI TILE ADHESIVES and MULTI TILE GROUTS in the following facilities:

- * Abattoirs, breweries and food processing areas
- * Swimming pools and continuously wet areas
- * Tiling onto smooth trowelled floors and walls
- * In areas where regular temperature changes occur

It is also added to the mixing water at a ratio of 1 :1 when encountering difficult applications:

- * In difficult and complicated conditions
- * In permanently wet conditions
- * To increase water resistance
- * To increase bond and flexural strength

Directions for Use

Surface Preparation

Follow preparation instructions pertaining to the adhesive or grout being used.

Dosage Rate

Use as directed for the specific adhesive and grout products

Watchpoints

- * Cement based products will dry a shade darker and setting times will be extended \pm 12 hours with the addition of MULTI TILE BOND 555.
- * Clean face of tiles before adhesive/ grout hardens
- * Do not ingest and keep away from children and pets.
- * Do not empty into drains

Packaging

Supplied in 1 litre and 5 litre bottles and in 25 litre drums

Quality Assurance

MCC LIMPOPO's production and testing programmes comply with all local and international testing standards.