

Tel: 015 293 1459 Fax:015 293 0368

> P.O. Box 465 Ladanna. 0704

43 Staal Street Ladanna Polokwane 0704

# **MULTIFLUID 960**

# **Mining Product for Ore Lubrication**

### Description

MULTIFLUID 960 a non-toxic synthetic water-soluble additive which contains EP, lubricity and active agents for use in the mining industry. Test work has proved that the product does not affect metallurgical processes.

# **Typical Applications**

- \* Many mines are dogged by the build-up of clays, shales and other minerals on conveyor belts, box holes, chutes and ore passes. Besides significantly reducing total throughput, these build-ups can often lead to complete blockages, resulting in a significant safety hazard, major operational delays I problems and costly cleaning procedures.
- \* MULTIFLUID 960 acts as a lubricant to ensure the clean flow of the ore by the encapsulation of the clay thereby preventing the mineral fines from building-up on working surfaces.
- \* Unlike the use of detergent, or oil-based additives, MULTIFLUID 960 does not cause foaming and does not affect flotation, collection, suppression or the absorption of gold by activated carbon in CIP or OIL processes.

### Advantages

- \* Non-flammable
- \* Non-toxic
- \* Environmentally compatible
- \* Non-foaming
- \* Cost effective

## **Directions for Use**

Use recommended dispensing procedures and equipment Dilution: Mix up to 4 parts water to one part MULTIFLUID 960 (dependent upon ore characteristics and application).

Dosage: As per recommendation and field test work

## **Typical Properties**

Skin irritation:

Eye irritation:

Composition: Patented synthetic water

soluble additive

Fluorescent yellow Colour:

Specific Gravity: 1.04 Typical viscosity at40° C: 32 Typical viscosity at 95° C: 10 Viscosity Index: 240

Toxicity- Ld50: Approximately 1 0m2/kg (based

on ingredient information) Non-irritating (based on

ingredient information)

Non-irritating (based on ingredient information)

Available on request Packaging

**Material Safety Data** 

Supplied in 200 litre drums

#### **Quality Assurance**

MCC LIMPOPO's production and testing programmes comply to local and international testing standards. These stringent testing programmes also comply with mining requirements.

REG No: 2003/054665/23

This data sheet supersedes all previous issues prior to this date: 31/05/97

Counterpoint Trading 512 CC

VAT No: 4470209109