

MULTIBIT 1702

Bitumen Aluminium UV Resistant Coating

Description

MULTIBIT 1702 a thixotropic bitumen aluminium emulsion which dries to provide a tough, seamless, smooth and UV resistant coating.

Typical Application

- * To provide an economical topcoat for sealing and preserving MULTIBIT 1702 rubberized bitumen waterproofing system.
- * It also assists the reflectance of sun rays.

Advantages

Water based, economical, good adhesion to concrete, brick, damp surfaces, waterproof coatings and substrates.

Composition

A thixotropic cold bitumen emulsion with added plasticizers and aluminium paste

Direction for Use

- * Apply by brush, roller or spray to clean surfaces.
- * Surfaces may be damp but there should be no surface water.

Typical Properties

Specific Gravity:	0.98
Spreading Rate:	5m ² / litre depending on surface and application
Application Temp:	5°C to 35°C
Thinners:	Water
Shelf Life:	>1 year

Watchpoints

- * Wash equipment immediately after use with water or once dried, use MULTITHINNERS 1604.

Packaging

Supplied in 5 and 25 litre tins

Quality Assurance

MCC LIMPOPO's production and testing programmes comply with local and international testing standards.

Updates

This data sheet supersedes all previous issues prior to this date: 31/05/97.