

Tel: 015 293 1459 Fax:015 293 0368

> P.O. Box 465 Ladanna, 0704

43 Staal Street Ladanna Polokwane 0704

Multi Pre-Packed Plaster A Cementitious and Sand Blend

Description

Multi Pre-Packed Plaster, a cementitious sand blend product specially formulated for the application by normal steel trowelling onto masonry / concrete surfaces to seal pores, voids and as new rendering to old and new masonry surfaces.

Typical Applications

- * Multi Pre-Packed Plaster decorates masonry and concrete surfaces
- * Can be applied onto interior and exterior surfaces above or belows grade
- * Multi Pre-Packed Plaster can be applied to concrete mortar, block, brick, stone, pre-cast elements, cement plaster and other properly prepared structurally sound wall surfaces.

Composition

Multi Pre-Packed Plaster consists of a blend of special cements, sand fillers and any activating chemicals

Mixing Instructions

- * Pour approximately three quarters of the required water into an empty clean container and begin slow mixing while adding the powdered product.
- * Gradually add the balance of the water to bring the slurry to a consistency of a heavy pancake batter
- * Stop mixing and allow the material to "fatten" for 5 minutes
- * Remix after above period. It may be necessary to add more water to bring to the correct consistency

Directions for Use

- * All surfaces to be structurally sound and clean
- * Saturate the mortar / concrete surface and ensure it remains damp throughout the plaster application
- * Using a standard steel trowel, apply the plaster onto the damp surface at the required thickness
- * Using a straight edge, strike off the excess plaster and level the wet plaster surface
- * Smooth trowel the surface and leave to harden
- * Let the surface cure for 24 hours before any decoratile material is applied.

Coverage

The coverage rate is dependent upon the applied thickness of the plaster mix. Surface texture and porosity determines the total amount of product required:

- One 25kg bag will yield ±12 Litres
- One 40kg bag will yield ± 19 Litres

Cleaning Instructions

* Clean all mixing and application equipment with water immediately after use

* Clean any spatters or spills with water before material sets

Packaging

Supplied in both 25kg and 40kg Polypropylene bags

Environmental and Safety Precautions

- * Multi Pre-Packed Plaster contains Portland cement and is alkaline on contact with water.
- * Avoid splashing into eyes or contact with skin
- * Use the required protective clothing, gloves and goggles
- * In case of eye contact, floor eyes repeatedly with water
- * Wash hands thoroughly after handling

Quality Assurance

REG No: 2003/054665/23

Multi Pre-Packed Plaster products are manufactured under strict quality control procedures and tested in accordance with proven quality testing procedures and standards

VAT No: 4470209109