

## MULTIPRIME 1101 Epoxy Primer

### Description

MULTIPRIME 1101 a clear high solid epoxy primer / sealer for application to porous and friable surfaces

### Primary Uses

To seal porous surfaces, preventing dusting, ingress of dirt and moisture. to bind friable areas and to prepare surfaces for subsequent application of pigmented coatings, flooring systems and sealants.

### Advantages

- \* Long pot life
- \* Easy application
- \* Good penetration

### Composition

Twin pack epoxy system

### Typical Properties

Specify Gravity:	0.97
Flashpoint:	8°C
Pot Life:	1 Hour
Spreading Rate:	4-6m <sup>2</sup> / litre
Solvent:	MULTI THINNERS 1601
Storage Life:	1 Year
Mixing Ratio:	As supplied
Thin film cure:	6 Hours

### Directions for Use

Mix thoroughly and brush apply to clean, dry surfaces.

### Watchpoints

- \* Flammable - use only in well ventilated areas
- \* Wear protective clothing and gloves
- \* In case of eye contact wash well with clean water and obtain medical assistance
- \* Clean all equipment immediately after use

### Packaging

Supplied in 2 litre-kits

### Quality Assurance

MCC LIMPOPO's production and testing programmes comply with all local and international testing standards.

### Updates

This data sheet supersedes all previous issues prior to this date: 31/05/97