Slack MCP: CODE workspace

Connect Claude Code to the CODE University Slack (codeuniversity.slack.com) as malek.hassan@code.berlin. Use this guide for the first setup and whenever the tokens expire.

What you get

A Claude Code MCP server named **slack-code** that can read channels, threads and DMs, search messages, list unreads, look up people, and **post messages** (enabled). It runs as your own Slack login, with no Slack app or admin approval needed.

When to redo this

The tokens are tied to your browser session. Redo steps 1–3 if you sign out of Slack in Chrome, if Slack signs you out, or if Claude reports *invalid_auth* / *not_authed*.

Step 1: Get the xoxc token (Chrome console)

1. Open Chrome and go to **https://app.slack.com**, then sign in to the CODE workspace. If it offers to open the desktop app, choose *use Slack in your browser*.
2. Open DevTools: **Cmd + Option + J** (lands on the **Console** tab).
3. Paste the line below and press **Enter**:

```
Object.values(JSON.parse(localStorage.localConfig_v2).teams)
  .map(t => `${t.name} (${t.domain}): ${t.token}`).join('\n')
```

4. Copy the token on the line that starts with **CODE (codeuniversity):**, beginning at `xoxc-`. Ignore the other workspaces.

Only if Chrome shows a yellow warning that pasting is blocked: type `allow pasting`, press Enter, then paste the line again. Typing it when there is no warning gives a harmless *SyntaxError … pasting*. Just ignore it.

Step 2: Get the d cookie (xoxd token)

1. In the same DevTools window, click the **Application** tab (it may be behind the **»** arrow).
2. Left sidebar: **Storage** → **Cookies** → **https://app.slack.com**.
3. Click the row whose Name is just **d**.
4. Copy the full **Value** from the bottom panel. It starts with `xoxd-`. Keep the %2F / %3D characters exactly as they are.

This cookie is HttpOnly, so console scripts and browser automation can't read it. It has to be copied by hand.

Step 3: Register it with Claude Code

In Claude Code, type this into the prompt (the leading **!** runs it as a shell command), or run it without the **!** in Terminal:

```
! ~/Desktop/Projects/slack-mcp-code/setup-code-slack.sh
```

Paste the xoxc token, then the d cookie, when asked. Input is hidden, so nothing appears as you paste. The script checks both with Slack first, then registers **slack-code** in `~/.claude.json` (user

scope, so every project has it) with posting enabled.

Step 4: Load it

Restart Claude Code, or run `/mcp`. Check from Terminal with:

```
claude mcp get slack-code        # should say: Status: ✔ Connected
```

Troubleshooting

Symptom	Fix
SyntaxError … pasting	You typed *allow pasting* with no warning showing. Ignore it and paste the command.
Cannot read properties of undefined	Not on app.slack.com or not signed in. Open the workspace in the browser first.
Script: *Slack rejected these tokens*	Tokens are stale or mis-copied. Reload Slack and redo steps 1–2.
Status: Failed to connect / timed out	The first run caches ~2,200 users and ~930 channels (~40 s). Run `/mcp` to reconnect after a minute.
Want posting off again	Edit the script: delete the `SLACK_MCP_ADD_MESSAGE_TOOL=true` line, then re-run it.

Files & security

• Project folder: `~/Desktop/Projects/slack-mcp-code/`: this guide, the setup script, README, and `upstream-repo/` (github.com/c3-oss/slack-mcp-server, reference only; the server runs via npx).

• Caches: `~/.cache/slack-mcp-code/`. Tokens live in plain text in `~/.claude.json`.

• The tokens are your full Slack login. Never share them. To revoke them, sign out of Slack in Chrome, then redo this guide.

• Posting is on, so Claude can send messages as you. It should always ask you before sending.