

```

#include <iostream>

using namespace std;

class NoteFrais{

    int idNote;
    string salarie;
    float *depenses;
    int nbDep;
    static int compteur;

public:
    NoteFrais(string salarie, int nbDep){

        idNote = ++compteur;
        this->salarie = salarie;
        this->nbDep= nbDep;

        depenses = new float[nbDep];

        for(int i = 0; i<nbDep; i++){
            depenses[i]=0;
        }
    }

    ~NoteFrais(){

        cout<<"Notes supprim e"<<endl;
        delete []depenses;
    }

    NoteFrais(NoteFrais &nf){

        idNote = ++compteur;
        salarie = nf.salarie;
        nbDep= nf.nbDep;

        depenses = new float[nbDep];

        for(int i = 0; i<nbDep; i++){
            depenses[i]=nf.depenses[i];
        }
    }
}

```

```

    void Saisir(){

        for(int i=0; i<nbDep; i++){
            cout<<"Entrez le cout ["<<i<<" : ";

            cin>>depenses[i];
        }

        friend void totalR(const NoteFrais &N);
};

int NoteFrais::compteur=0;

void totalR(const NoteFrais &N){

    int som=0;
    cout<<"ID : "<<N.idNote<<endl;
    cout<<"Salarie : "<<N.salarie<<endl;

    for(int i = 0; i<N.nbDep; i++){

        som+=N.depenses[i];
    }
    cout<<"La somme vaut : "<<som;
}

int main()
{
    NoteFrais N1("Dupont",3);
    N1.Saisir();
    totalR(N1);

    NoteFrais N2(N1);
    totalR(N2);
    return 0;
}

```