

Capture reelle du module Auth

Extraits du code source: routes de connexion, service de session et signature JWT.

Capture composee a partir des fichiers reels du depot GesPharmacie.

src/modules/auth/auth.routes.ts | lignes 9-16

```
9 | export const buildAuthRouter = (controller: AuthController) => {
10 |   const router = Router();
11 |   const validator = new AuthValidator();
12 |
13 |   router.post("/login", validate(validator.getCreateSchema()), asyncHandler(controller.login));
14 |   router.get("/me", authMiddleware, asyncHandler(controller.me));
15 |
16 |   return router;
```

src/modules/auth/auth.service.ts | lignes 8-13

```
8 | export class AuthService implements IAuthService {
9 |   constructor(private readonly authRepository: IAuthRepository = new AuthRepository()) {}
10 |
11 |   async login(payload: LoginDTO): Promise<AuthResponseDTO> {
12 |     return this.authRepository.createLoginSession(payload.email, UserRole.ADMIN);
13 |   }
```

src/modules/auth/auth.repository.ts | lignes 8-22

```
8 | export class AuthRepository implements IAuthRepository {
9 |   async createLoginSession(email: string, role: UserRole): Promise<AuthResponseDTO> {
10 |     const token = jwt.sign({ role }, env.JWT_SECRET, {
11 |       subject: email,
12 |       expiresIn: "1d",
13 |     });
14 |
15 |     return {
16 |       token,
17 |       user: {
18 |         email,
19 |         role,
20 |       },
21 |     };
22 |   }
```