

PLAYWRIGHT MCP + GOOGLE ANTIGRAVITY

Complete Global Setup & Verification Guide

Windows • Global MCP • Browser testing • Troubleshooting

THE OUTCOME

Configure Microsoft's official Playwright MCP server globally in Google Antigravity so it can be used across existing and new projects.

UPDATED • SEPTEMBER 3, 2026

What You're Installing

Playwright MCP connects an AI agent to browser automation through the Model Context Protocol. The official package is `@playwright/mcp`. Antigravity supports custom MCP servers through its MCP configuration.

GLOBAL VS PROJECT

Global: `~/.gemini/config/mcp_config.json` — all Antigravity workspaces.

Workspace: `.agents/mcp_config.json` — only that workspace.

Prerequisites

You need Google Antigravity, Node.js/npm, and internet access. Playwright MCP is launched with **npx**; Playwright does not need to be installed globally.

```
node --version  
npm --version
```

WARNING

If Node/npm commands are not recognized, install Node.js first and reopen Antigravity.

Open the Global MCP Configuration

In Antigravity: Agent side panel → ... → MCP Servers → Manage MCP Servers → View raw config.

```
C:\Users\<YOUR_USERNAME>\.gemini\config\mcp_config.json
```

Add the Official Playwright MCP Server

Do not delete existing MCP servers such as Context7. Add Playwright inside the existing **mcpServers** object.

```
"playwright": {
  "command": "npx",
  "args": [
    "@playwright/mcp@latest"
  ]
}
```

IMPORTANT

Keep your real Context7 configuration and credentials unchanged. Only add the Playwright entry.

COMBINED STRUCTURE

Both servers must be entries under **mcpServers**.

```
{
  "mcpServers": {
    "context7": {
      "...": "existing Context7 configuration"
    },
    "playwright": {
      "command": "npx",
      "args": ["@playwright/mcp@latest"]
    }
  }
}
```

JSON Rules That Prevent Errors

CHECK BEFORE SAVING

- Playwright must be inside **mcpServers**.
- Add a comma after the previous server entry.
- No comma after the final Playwright entry.
- Never expose API keys in screenshots.

Save & Reload

Save **mcp_config.json**. Return to Antigravity's MCP manager and Refresh/Reload if available. If it remains disconnected, completely close and reopen Antigravity.

Verify the Server

Open the MCP server manager and confirm Playwright is listed and connected/available. CLI users can also use **/mcp** to inspect live status/logs.

First Functional Test

Use a harmless public demo before testing a real project.

```
Use Playwright MCP.  
Navigate to:  
https://demo.playwright.dev/todomvc  
Verify that Playwright MCP can control the browser.  
Add a todo called "Test Playwright MCP".  
Mark it completed and take a screenshot.  
Do not modify any files in my project.
```

Test an Existing Local Project

Start your project's development server:

```
npm run dev
```

TEST PROMPT

Open **http://localhost:3000**. Do not modify files. Check page loading, console errors, failed network requests, broken images, navigation, buttons, and responsive behavior. Report issues and take screenshots of important failures.

Test Responsive UI

Test at: **1440×900, 1920×1080, 1024×768, 768×1024, 390×844, 375×812**. Check overflow, clipping, navigation, buttons, images, spacing, typography, and mobile layout. Do not modify code.

Test a Scroll-Driven / Scrollytelling Hero

Open **http://localhost:3000** and slowly scroll through the entire hero. Verify animation progression, image-frame loading, broken URLs, console errors, and desktop/mobile behavior. Capture important states. Do not modify code.

What Playwright MCP Can Do

Depending on enabled tools/configuration: navigation, clicking, form entry, page inspection, screenshots, console/network-oriented debugging, and browser/session workflows. The key benefit is testing the rendered application rather than only reading source code.

Browser Choice — Optional

Start with the default configuration. If you need a specific browser, Playwright MCP supports browser options.

```
"playwright": {
  "command": "npx",
  "args": [
    "@playwright/mcp@latest",
    "--browser=chrome"
  ]
}
```

RECOMMENDATION

Do not add options until the basic setup is working.

Global vs Project Installation

Configuration	Scope
Global: ~/.gemini/config/mcp_config.json	All Antigravity workspaces
Workspace: ./agents/mcp_config.json	Only that workspace

Existing & New Projects

A global configuration means you do not reinstall the MCP for every project. Projects only need to be runnable and reachable by the browser.

```
Project A → npm run dev → http://localhost:3000
Project B → npm run dev → http://localhost:5173
Project C → deployed URL
```

Security & Permissions

MCP gives an agent access to external tools. Only connect servers you trust. Review requested actions. Never put secrets in prompts or screenshots. Antigravity supports MCP permissions/access controls and server enable/disable management.

Troubleshooting

PLAYWRIGHT DOES NOT APPEAR

Confirm it is in the global file and inside **mcpServers**; refresh/restart Antigravity.

JSON ERROR

Check commas, quotes, and braces. Do not paste the entire example over your existing configuration.

NPX / PACKAGE PROBLEM

Run **node --version** and **npm --version**. Reopen Antigravity after installing/updating Node.js.

BROWSER DOES NOT START

Let MCP initialize once; npx may need to obtain package/browser components. Check MCP logs.

LOCALHOST CANNOT BE REACHED

Start the dev server and verify the URL manually in a normal browser first.

Recommended Development Workflow

1. Build/modify → 2. Use Context7 when current docs are needed → 3. Run locally → 4. Test with Playwright MCP → 5. Capture failures → 6. Fix → 7. Re-test → 8. Build/test before deployment.

Final Checklist

READY

- Node.js/npm works
- Global mcp_config.json opened
- Existing MCP entries preserved
- Playwright added under mcpServers
- JSON saved without syntax errors
- MCP refreshed
- Antigravity restarted
- Playwright connected/available
- TodoMVC test succeeds
- Local project test succeeds
- Responsive test succeeds

YOU'RE READY.

BUILD → RUN → TEST → FIX → REPEAT.

Playwright MCP becomes a reusable browser-testing layer across your Antigravity projects.

OFFICIAL REFERENCES

[Google Antigravity MCP documentation](#) • [Microsoft Playwright MCP documentation](#) • [Microsoft Playwright MCP repository](#)

Source content preserved from the uploaded 4-page setup guide.