

# Ensembles

# What are ensembles

# What are ensembles

- Ensembles are predictors defined as an average/vote over “base” or “weak” predictors.

# What are ensembles

- Ensembles are predictors defined as an average/vote over “base” or “weak” predictors.
- Ensembles come in two main flavors:

# What are ensembles

- Ensembles are predictors defined as an average/vote over “base” or “weak” predictors.
- Ensembles come in two main flavors:
  - Boosting based Ensembles

# What are ensembles

- Ensembles are predictors defined as an average/vote over “base” or “weak” predictors.
- Ensembles come in two main flavors:
  - Boosting based Ensembles
  - Bootstrap based Ensembles.

# What are ensembles

- Ensembles are predictors defined as an average/vote over “base” or “weak” predictors.
- Ensembles come in two main flavors:
  - Boosting based Ensembles
  - Bootstrap based Ensembles.
- Any predictor can be used as a base predictor.

# What are ensembles


- Ensembles are predictors defined as an average/vote over “base” or “weak” predictors.
- Ensembles come in two main flavors:
  - Boosting based Ensembles
  - Bootstrap based Ensembles.
- Any predictor can be used as a base predictor.
  - In this talk, and in Spark, the base predictors are decision trees.




# What are ensembles

- Ensembles are predictors defined as an average/vote over “base” or “weak” predictors.
- Ensembles come in two main flavors:
  - Boosting based Ensembles
  - Bootstrap based Ensembles.
- Any predictor can be used as a base predictor.
  - In this talk, and in Spark, the base predictors are decision trees.
  - We will restrict our attention to binary classification, but there are solutions for multi class and for regression.


# An Ensemble of trees




# An Ensemble of trees




# An Ensemble of trees




# An Ensemble of trees



# An Ensemble of trees



# An Ensemble of trees



**Bagging = bootstrap aggregation**



# Bagging = bootstrap aggregation

- Decision trees have high data variation.

# Bagging = bootstrap aggregation

- Decision trees have high data variation.
  - i.e. the generated tree is sensitive to small changes in the training set.

# Bagging = bootstrap aggregation

- Decision trees have high data variation.
  - i.e. the generated tree is sensitive to small changes in the training set.
- To reduce the variation, we take a majority vote over several runs, each using an independent random resample of the training data.

# Bagging = bootstrap aggregation

- Decision trees have high data variation.
  - i.e. the generated tree is sensitive to small changes in the training set.
- To reduce the variation, we take a majority vote over several runs, each using an independent random resample of the training data.
- Running an algorithm over random resampling is called “The Bootstrap”

# Bagging = bootstrap aggregation

- Decision trees have high data variation.
  - i.e. the generated tree is sensitive to small changes in the training set.
- To reduce the variation, we take a majority vote over several runs, each using an independent random resample of the training data.
  - Running an algorithm over random resampling is called “The Bootstrap”
- Trees can be learned in parallel and

# Bagging = bootstrap aggregation

- Decision trees have high data variation.
  - i.e. the generated tree is sensitive to small changes in the training set.
- To reduce the variation, we take a majority vote over several runs, each using an independent random resample of the training data.
  - Running an algorithm over random resampling is called “The Bootstrap”
- Trees can be learned in parallel and
- The result is a reduction in variation with no increase

# Random Forests

# Random Forests

- Based on bagging trees.



# Random Forests

- Based on bagging trees.
- Additional randomization: before choosing which leaf to split and how, choose a random subset of the features.

# Random Forests

- Based on bagging trees.
- Additional randomization: before choosing which leaf to split and how, choose a random subset of the features.
- Decreases the correlation between different trees.

# Random Forests

- Based on bagging trees.
- Additional randomization: before choosing which leaf to split and how, choose a random subset of the features.
- Decreases the correlation between different trees.
- Speeds up the learning process.

# Random Forests

- Based on bagging trees.
- Additional randomization: before choosing which leaf to split and how, choose a random subset of the features.
- Decreases the correlation between different trees.
- Speeds up the learning process.
- All trees get equal weight (1.0)

# Random Forests

- Based on bagging trees.
- Additional randomization: before choosing which leaf to split and how, choose a random subset of the features.
- Decreases the correlation between different trees.
- Speeds up the learning process.
- All trees get equal weight (1.0)
- All trees can be learned in parallel.

# Gradient Tree Boosting

# Gradient Tree Boosting

- The trees are trained sequentially, one after the other.

# Gradient Tree Boosting

- The trees are trained sequentially, one after the other.
- Each tree is trained using a **weighted** training set. The weights represent the gradient of the loss function.



# Gradient Tree Boosting

- The trees are trained sequentially, one after the other.
- Each tree is trained using a **weighted** training set. The weights represent the gradient of the loss function.
- Each tree receives a different weight (corresponding to the alpha in adaboost)

# Gradient Tree Boosting

- The trees are trained sequentially, one after the other.
- Each tree is trained using a **weighted** training set. The weights represent the gradient of the loss function.
- Each tree receives a different weight (corresponding to the alpha in adaboost)
- Stochastic gradient boosting: use random resampling of the training set a.k.a. Bagging.