

Operators Overloading



Dra. M^a Dolores Rodríguez Moreno

Objectives

Specific Objectives

- Understanding what is Operator Overloading
- Main Magic Methods for Operator Overloading

Source

- <https://docs.python.org/3/reference/>
- <https://ellibrodepython.com/>
- Python Tutorial - Tapa blanda. Guido Van Rossum (2012)

Outline

- Introduction
- Magic Methods
- Best Practices

Introduction

- Customizing how operators work with user-defined classes
- Allows objects to behave like built-in types
- Makes code more intuitive and readable
- Operator overloading allows operators to have different meanings based on their operands
- Implemented using special methods (magic methods)
- For example:
 - ``+`` for addition of numbers, concatenation of strings, or merging of lists

Outline

- Introduction
- **Magic Methods**
- Best Practices

Magic Methods

- Arithmetic Operators
 - `__add__(self, other)` for `+`
 - `__sub__(self, other)` for `-`
 - `__mul__(self, other)` for `*`
 - `__truediv__(self, other)` for `/`
- Comparison Operators
 - `__eq__(self, other)` for `==`
 - `__lt__(self, other)` for `<`
 - `__gt__(self, other)` for `>`
 - `__le__(self, other)` for `<=`

Example: Add two Vector

Example: +

```
class Vector:
    def __init__(self, x, y):

        self.x = x

        self.y = y

    def sumar(self, other):

        return Vector(self.x + other.x, self.y + other.y)

v1 = Vector(2, 3)
v2 = Vector(4, 5)
v3 = v1.sumar(v2)
```

Example: Overloading '+' Operator

Example: +

```
class Vector:

    def __init__(self, x, y):

        self.x = x

        self.y = y

    def __add__(self, other):

        return Vector(self.x + other.x, self.y + other.y)

v1 = Vector(2, 3)
v2 = Vector(4, 5)
v3 = v1.__add__(v2) #Explicit call
```


Example: Overloading '+' Operator

Example: +

```
class Vector:
```

```
    def __init__(self, x, y):
```

```
        self.x = x
```

```
        self.y = y
```

```
    def __add__(self, other):
```

```
        return Vector(self.x + other.x, self.y + other.y)
```

```
v1 = Vector(2, 3)
```

```
v2 = Vector(4, 5)
```

```
v3 = v1 + v2 # Output: <__main__.Vector object at 0x7ee28d312830>
```

Example: str

Example: str

```
class Vector:
    def __init__(self, x, y):

        self.x = x

        self.y = y

    def __add__(self, other):

        return Vector(self.x + other.x, self.y + other.y)

    def __str__(self)

        return str("{self.x}, {self.y}") # Formato deseado

        #return "(" + str(self.x) + "," + str(self.y) + ")"
```

Example: Overloading '+' Operator

Example: + & str

```
v1 = Vector(2, 3)
```

```
v2 = Vector(4, 5)
```

```
v3 = v1 + v2
```

```
print(v3) # Output: (6, 8)
```

Example: Overloading '+' Operator

Example: + with different types

```
v1 = Vector(2, 3)
```

```
v2 = Vector(4, 5)
```

#What happen if we add a number?

```
v3 = v1 + 4
```

Example: __add__ with different types

Example: add a number

```
class Vector:
    ...

    def __add__(self, other):

        if isinstance(other, Vector):

            return Vector(self.x + other.x, self.y + other.y)

        elif isinstance(other, (int, float)):

            return Vector(self.x + other, self.y + other)

        else:

            raise TypeError("Unsupported operand type")
```

Example: commutative '+' Operator

Example: + with different types

```
v1 = Vector(2, 3)
```

```
v2 = Vector(4, 5)
```

```
#What happen if we add a number?
```

```
v5 = 4 + v2 # ERROR: unsupported operand type(s) for +: 'int' and 'Vector'
```

Example: __radd__

Example: add a number in both sides of +

```
class Vector:
```

```
...
```

```
    def __radd__(self, other):
```

```
        return self.__add__(other)
```

```
v5= v2.__radd__(4)
```

Outline

- Introduction
- Magic Methods
- **Best Practices**

Best Practices

- Follow Python's operator semantics (e.g., + should add, not subtract)
- Implement related operators together (if you implement <, implement >)
- Return *NotImplemented* for unsupported operand types
- Maintain consistency with built-in types
- Document the behavior of overloaded operators
- Consider implementing reverse (conmutative) operations (radd, rsub, etc.)

Practical Exercises

1. Create a Rectangle class and overload the * operator to multiply areas