

1. Open Microsoft Word or any word processing software that supports document creation.
2. Start a new document.
3. Copy and paste the instructions for Machine Problem #2 into the document. Ensure proper formatting and readability.
4. Insert your source code into the document. You can either copy and paste it directly or take a screenshot of the code and insert the image into the document.
5. Capture screenshots of the output of your code execution. Make sure the screenshots are clear and readable.
6. Insert the screenshots into the document. You can either directly insert the images or embed them as links, depending on your preference and the document's requirements.
7. Arrange the content in a logical and organized manner. You may want to use headings, subheadings, and bullet points to make the document easy to follow.
8. Review the document for any errors or formatting issues. Make necessary adjustments to ensure clarity and correctness.
9. Save the document as a PDF file. Most word processing software offers an option to save or export documents as PDFs. Choose this option and follow the prompts to save your document in PDF format.
10. Once saved, review the PDF file to ensure that all content, including instructions, source code, and screenshots, is accurately captured and presented.
11. If everything looks good, your Word document containing instructions, source code, and screenshots, saved as a PDF file, is ready for submission or sharing.
 - Please follow the filename format (**minus 10** for the wrong filename)
 - *MP2<Lastname>.pdf*
 - **Example:** *MP2Mansueto.pdf*

Instructions:

1. Create an Android application named "CC Jitters".

Frappuccino	Price
Caffè Vanilla Frappuccino	150
Green Tea Crème Frappuccino	190
S'mores Frappuccino	199
Mocha Frappuccino	130

2. **For the compute button:**

- Sub-Total: will display the amount based on the selected Frappuccino.
- Discount - displays the amount based on the selected discount.
- Net Amount is the difference between the sub-total and the discount amount.

3. You can select one or more items (check boxes).
(See the sample output below).

4. If **"No Discount"** is selected, the app will assume a 0% discount.


5. If **"No Frappuccino"** is selected, all text views will have a value of 0.00.

6. **For the Clear All button,**

- Will deselect all checkboxes and set the radio button to **"No Discount."**
- Will clear all text view. (i.e., sub-total, discount, and net amount).

Additional Logical Problems:

- Once a specific Frappuccino is selected or clicked, make a toast message (see the image below).



- Once a specific discount is selected or clicked, make a toast message (see the image below).



SAMPLE OUTPUT:

CC Jitters		CC Jitters	
Frappuccino		Frappuccino	
☒ Caffè Vanilla Frappuccino	Discount	☒ Caffè Vanilla Frappuccino	Discount
☐ Green Tea Crème Frappuccino	☐ 5%	☐ Green Tea Crème Frappuccino	☐ 5%
☒ S'mores Frappuccino	☐ 10%	☐ S'mores Frappuccino	☒ 10%
☐ Mocha Frappuccino	☐ 15%	☐ Mocha Frappuccino	☐ 15%
	☒ No Discount		☐ No Discount
Sub-Total:	349.0	Sub-Total:	150.0
Discount:	0.0	Discount:	15.0
Net Amount:	349.0	Net Amount:	135.0
COMPUTE CLEAR ALL		COMPUTE CLEAR ALL	

Source Code:

```
package com.example.ccjitters;

import android.os.Bundle;
import android.widget.Button;
import android.widget.CheckBox;
import android.widget.RadioButton;
import android.widget.RadioGroup;
import android.widget.TextView;
import android.widget.Toast;

import java.util.Locale;

import androidx.activity.EdgeToEdge;
import androidx.appcompat.app.AppCompatActivity;
import androidx.core.graphics.Insets;
import androidx.core.view.ViewCompat;
import androidx.core.view.WindowInsetsCompat;

public class MainActivity extends AppCompatActivity {

    private static final double pricevanilla = 150.0;
    private static final double pricegreentea = 190.0;
    private static final double pricesmores = 199.0;
    private static final double pricemocha = 130.0;

    private TextView txtsubtotal, txtdiscount, txtnetamount;
    private Button btncompute, btnclearall;
    private CheckBox chkvanilla, chkgreentea, chksmores, chkmocha;
    private RadioButton rdofive, rdoten, rdofifteen, rdonodiscount;
    private RadioGroup rdodiscount;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        EdgeToEdge.enable(this);
        setContentView(R.layout.activity_main);
```

```

ViewCompat.setOnApplyWindowInsetsListener(findViewById(R.id.main), (v, insets) -> {
    Insets systemBars = insets.getInsets(WindowInsetsCompat.Type.systemBars());
    v.setPadding(systemBars.left, systemBars.top, systemBars.right,
systemBars.bottom);
    return insets;
});

views();
rdonodiscount.setChecked(true);

toastSelect();
discounttotals();
displayZeros();

btncompute.setOnClickListener(v -> computation());
btnclearall.setOnClickListener(v -> {
    chkvanilla.setChecked(false);
    chkgreentea.setChecked(false);
    chksmores.setChecked(false);
    chkmocha.setChecked(false);
    rdonodiscount.setChecked(true);
    displayZeros();
});
}

private void views(){

    chkgreentea = findViewById(R.id.chkgreentea);
    chkvanilla = findViewById(R.id.chkvanilla);
    chksmores = findViewById(R.id.chksmores);
    chkmocha = findViewById(R.id.chkmocha);

    txtdiscount = findViewById(R.id.txtdiscount);
    txtnetamount = findViewById(R.id.txtnetamount);
    txtsubtotal = findViewById(R.id.txtsubtotal);

```

```

btnclearall = findViewById(R.id.btnclearall);
btncompute = findViewById(R.id.btncompute);

rdodiscount = findViewById(R.id.rdodiscount);
rdofifteen = findViewById(R.id.rdofifteen);
rdofive = findViewById(R.id.rdofive);
rdoten = findViewById(R.id.rdoten);
rdonodiscount = findViewById(R.id.rdonodiscount);
}

private void toastSelect(){
    chkvanilla.setOnCheckedChangeListener((b, checked) -> {
        if (checked) toastItem("Caffè Vanilla Frappuccino", pricevanilla);
    });
    chkgreentea.setOnCheckedChangeListener((b, checked) -> {
        if (checked) toastItem("Green Tea Crème Frappuccino", pricegreentea);
    });
    chksmores.setOnCheckedChangeListener((b, checked) -> {
        if (checked) toastItem("S'mores Frappuccino", pricesmores);
    });
    chkmocha.setOnCheckedChangeListener((b, checked) -> {
        if (checked) toastItem("Mocha Frappuccino", pricemocha);
    });
}

private void discounttotals(){
    rdodiscount.setOnCheckedChangeListener((group, checkedId) -> {
        String msg;
        if (checkedId == R.id.rdofive) msg = "You select 5% discount";
        else if (checkedId == R.id.rdoten) msg = "You select 10% discount";
        else if (checkedId == R.id.rdofifteen) msg = "You select 15% discount";
        else msg = "You select No Discount";
        Toast.makeText(this, msg, Toast.LENGTH_SHORT).show();
    });
}

private void computation(){
    double subtotal = 0.0;

```

```

        if (chkvanilla.isChecked()) subtotal += pricevanilla;
        if (chkgreentea.isChecked()) subtotal += pricegreentea;
        if (chksmores.isChecked()) subtotal += pricesmores;
        if (chkmocha.isChecked()) subtotal += pricemocha;

        if (subtotal == 0.0) {
            displayZeros();
            return;
        }

        double rate = discountrate();
        double discount = subtotal * rate;
        double net = subtotal - discount;

        txtsubtotal.setText(formatphp(subtotal));
        txtdiscount.setText(formatphp(discount));
        txtnetamount.setText(formatphp(net));
    }

    private double discountrate(){
        int id = rdodiscount.getCheckedRadioButtonId();
        if (id == R.id.rdofive)    return 0.05;
        if (id == R.id.rdoten)    return 0.10;
        if (id == R.id.rdofifteen) return 0.15;
        return 0.0;
    }

    private void displayZeros() {
        txtsubtotal.setText(formatphp(0));
        txtdiscount.setText(formatphp(0));
        txtnetamount.setText(formatphp(0));
    }

    private void toastItem(String name, double price) {
        String msg = String.format(Locale.ENGLISH,
            "You select %s\nPhp %s",
            name, twodec(price));
    }

```

```
    Toast.makeText(this, msg, Toast.LENGTH_SHORT).show();
}

private String formatphp(double amount) {
    return "Php " + twodec(amount);
}

private String twodec(double amount) {
    return String.format(Locale.ENGLISH, "%.2f", amount);
}
}
```

OUTPUTS:

