

Start coding or [generate](#) with AI.

```
from google.colab import drive
drive.mount('/content/drive')
```

Mounted at /content/drive

```
import os # For directory and file operations
import numpy as np # For numerical operations and handling image arrays
import random # For generating random values for augmentation
from PIL import Image, ImageEnhance # For image processing and enhancement
from tensorflow.keras.preprocessing.image import load_img # For loading images
from tensorflow.keras.models import Sequential # For building the model
from tensorflow.keras.layers import Input, Flatten, Dropout, Dense # For model layers
from tensorflow.keras.optimizers import Adam # For optimizer
from tensorflow.keras.applications import VGG16 # For using VGG16 model
from sklearn.utils import shuffle # For shuffling the data
```

```
# Directories for training and testing data
train_dir = '/content/drive/MyDrive/MRI Images/Training/'
test_dir = '/content/drive/MyDrive/MRI Images/Testing/'

# Load and shuffle the train data
train_paths = []
train_labels = []
for label in os.listdir(train_dir):
    for image in os.listdir(os.path.join(train_dir, label)):
        train_paths.append(os.path.join(train_dir, label, image))
        train_labels.append(label)

train_paths, train_labels = shuffle(train_paths, train_labels)

# Load and shuffle the test data
test_paths = []
test_labels = []
for label in os.listdir(test_dir):
    for image in os.listdir(os.path.join(test_dir, label)):
        test_paths.append(os.path.join(test_dir, label, image))
        test_labels.append(label)

test_paths, test_labels = shuffle(test_paths, test_labels)
```

```
import random
import matplotlib.pyplot as plt
from PIL import Image
import os


# Select random indices for 10 images
random_indices = random.sample(range(len(train_paths)), 10)

# Create a figure to display images in 2 rows
fig, axes = plt.subplots(2, 5, figsize=(15, 8))
axes = axes.ravel()

for i, idx in enumerate(random_indices):
    # Load image
    img_path = train_paths[idx]
    img = Image.open(img_path)
    img = img.resize((224, 224)) # Resize to consistent size

    # Display image
    axes[i].imshow(img)
    axes[i].axis('off') # Hide axis
    # Display class label in the second row
    axes[i].set_title(f"Label: {train_labels[idx]}", fontsize=10)

plt.tight_layout()
plt.show()
```



```
# Image Augmentation function
def augment_image(image):
    image = Image.fromarray(np.uint8(image))
    image = ImageEnhance.Brightness(image).enhance(random.uniform(0.8, 1.2)) # Random brightness
    image = ImageEnhance.Contrast(image).enhance(random.uniform(0.8, 1.2)) # Random contrast
    image = np.array(image) / 255.0 # Normalize pixel values to [0, 1]
    return image

# Load images and apply augmentation
def open_images(paths):
    images = []
    for path in paths:
        image = load_img(path, target_size=(IMAGE_SIZE, IMAGE_SIZE))
        image = augment_image(image)
        images.append(image)
    return np.array(images)

# Encoding labels (convert label names to integers)
def encode_label(labels):
    unique_labels = os.listdir(train_dir) # Ensure unique labels are determined
    encoded = [unique_labels.index(label) for label in labels]
    return np.array(encoded)

# Data generator for batching
def datagen(paths, labels, batch_size=12, epochs=1):
    for _ in range(epochs):
        for i in range(0, len(paths), batch_size):
            batch_paths = paths[i:i + batch_size]
            batch_images = open_images(batch_paths) # Open and augment images
            batch_labels = labels[i:i + batch_size]
            batch_labels = encode_label(batch_labels) # Encode labels
            yield batch_images, batch_labels # Yield the batch
```

```
# Model architecture
IMAGE_SIZE = 128 # Image size (adjust based on your requirements)
base_model = VGG16(input_shape=(IMAGE_SIZE, IMAGE_SIZE, 3), include_top=False, weights='imagenet')

# Freeze all layers of the VGG16 base model
for layer in base_model.layers:
    layer.trainable = False

# Set the last few layers of the VGG16 base model to be trainable
base_model.layers[-2].trainable = True
base_model.layers[-3].trainable = True
base_model.layers[-4].trainable = True
```

```
# Build the final model
model = Sequential()
model.add(Input(shape=(IMAGE_SIZE, IMAGE_SIZE, 3))) # Input layer
model.add(base_model) # Add VGG16 base model
model.add(Flatten()) # Flatten the output of the base model
model.add(Dropout(0.3)) # Dropout layer for regularization
model.add(Dense(128, activation='relu')) # Dense layer with ReLU activation
model.add(Dropout(0.2)) # Dropout layer for regularization
model.add(Dense(len(os.listdir(train_dir)), activation='softmax')) # Output layer with softmax activation

# Compile the model
model.compile(optimizer=Adam(learning_rate=0.0001),
              loss='sparse_categorical_crossentropy',
              metrics=['sparse_categorical_accuracy'])

# Parameters
batch_size = 20
steps = int(len(train_paths) / batch_size) # Steps per epoch
epochs = 5

# Train the model
history = model.fit(datagen(train_paths, train_labels, batch_size=batch_size, epochs=epochs),
                    epochs=epochs, steps_per_epoch=steps)
```

Downloading data from https://storage.googleapis.com/tensorflow/keras-applications/vgg16/vgg16_weights_tf_dim_ordering_tf_kernels/58889256/58889256 0s 0us/step

Epoch 1/5
285/285 1401s 5s/step - loss: 0.6435 - sparse_categorical_accuracy: 0.7511


Epoch 2/5
285/285 37s 103ms/step - loss: 0.2426 - sparse_categorical_accuracy: 0.9046

Epoch 3/5
285/285 30s 104ms/step - loss: 0.1563 - sparse_categorical_accuracy: 0.9373

Epoch 4/5
285/285 30s 104ms/step - loss: 0.1049 - sparse_categorical_accuracy: 0.9586

Epoch 5/5
285/285 29s 103ms/step - loss: 0.0603 - sparse_categorical_accuracy: 0.9738

```
plt.figure(figsize=(8,4))
plt.grid(True)
plt.plot(history.history['sparse_categorical_accuracy'], 'g-', linewidth=2)
plt.plot(history.history['loss'], 'r-', linewidth=2)
plt.title('Model Training History')
plt.xlabel('epoch')
plt.xticks([x for x in range(epochs)])
plt.legend(['Accuracy', 'Loss'], loc='upper left', bbox_to_anchor=(1, 1))
plt.show()
```



```
import matplotlib.pyplot as plt
from sklearn.metrics import classification_report, confusion_matrix, roc_curve, auc
import seaborn as sns
from sklearn.preprocessing import label_binarize
from tensorflow.keras.models import load_model
import numpy as np

# 1. Prediction on test data
test_images = open_images(test_paths) # Load and augment test images
test_labels_encoded = encode_label(test_labels) # Encode the test labels

# Predict using the trained model
test_predictions = model.predict(test_images)
```

```
# 2. Classification Report
print("Classification Report:")
print(classification_report(test_labels_encoded, np.argmax(test_predictions, axis=1)))
```

41/41 ————— 13s 182ms/step

Classification Report:


	precision	recall	f1-score	support
0	0.99	1.00	1.00	405
1	0.95	0.99	0.97	300
2	0.88	0.92	0.90	306
3	0.96	0.87	0.91	300
accuracy			0.95	1311
macro avg	0.95	0.94	0.94	1311
weighted avg	0.95	0.95	0.95	1311

```
# 3. Confusion Matrix
conf_matrix = confusion_matrix(test_labels_encoded, np.argmax(test_predictions, axis=1))
print("Confusion Matrix:")
print(conf_matrix)

# Plot the Confusion Matrix
plt.figure(figsize=(8, 6))
sns.heatmap(conf_matrix, annot=True, fmt="d", cmap="Blues", xticklabels=os.listdir(train_dir), yticklabels=os.listdir(train_dir))
plt.title("Confusion Matrix")
plt.xlabel("Predicted Labels")
plt.ylabel("True Labels")
plt.show()
```

Confusion Matrix:

```
[[405  0  0  0]
 [ 0 298  2  0]
 [ 3 13 280 10]
 [ 0  3 36 261]]
```




```
# 4. ROC Curve and AUC
# Binarize the test labels and predictions for multi-class ROC
test_labels_bin = label_binarize(test_labels_encoded, classes=np.arange(len(os.listdir(train_dir))))
test_predictions_bin = test_predictions # The predicted probabilities for each class

# Compute ROC curve and ROC AUC for each class
fpr, tpr, roc_auc = {}, {}, {}
for i in range(len(os.listdir(train_dir))):
    fpr[i], tpr[i], _ = roc_curve(test_labels_bin[:, i], test_predictions_bin[:, i])
    roc_auc[i] = auc(fpr[i], tpr[i])

# Plot ROC curve
plt.figure(figsize=(10, 8))
for i in range(len(os.listdir(train_dir))):
    plt.plot(fpr[i], tpr[i], label=f'Class {i} (AUC = {roc_auc[i]:.2f})')
```

```
plt.plot([0, 1], [0, 1], linestyle='--', color='gray') # Diagonal line
plt.title("ROC Curve")
plt.xlabel("False Positive Rate")
plt.ylabel("True Positive Rate")
plt.legend(loc="lower right")
plt.show()
```



```
# Save the entire model
model.save('model.h5')
```

WARNING:absl:You are saving your model as an HDF5 file via `model.save()` or `keras.saving.save\_model(model)`. This file for

```
from tensorflow.keras.models import load_model
# Load the trained model
model = load_model('model.h5')
```

WARNING:absl:Compiled the loaded model, but the compiled metrics have yet to be built. `model.compile\_metrics` will be empty

```
from keras.preprocessing.image import load_img, img_to_array
import numpy as np
import matplotlib.pyplot as plt

# Class labels
class_labels = ['pituitary', 'glioma', 'notumor', 'meningioma']

def detect_and_display(img_path, model, image_size=128):
    """
    Function to detect tumor and display results.
    If no tumor is detected, it displays "No Tumor".
    Otherwise, it shows the predicted tumor class and confidence.
    """
    try:
        # Load and preprocess the image
        img = load_img(img_path, target_size=(image_size, image_size))
        img_array = img_to_array(img) / 255.0 # Normalize pixel values
        img_array = np.expand_dims(img_array, axis=0) # Add batch dimension

        # Make a prediction
        predictions = model.predict(img_array)
        predicted_class_index = np.argmax(predictions, axis=1)[0]
        confidence_score = np.max(predictions, axis=1)[0]
```

```

# Determine the class
if class_labels[predicted_class_index] == 'notumor':
    result = "No Tumor"
else:
    result = f"Tumor: {class_labels[predicted_class_index]}"

# Display the image with the prediction
plt.imshow(load_img(img_path))
plt.axis('off')
plt.title(f"{result} (Confidence: {confidence_score * 100:.2f}%)")
plt.show()

except Exception as e:
    print("Error processing the image:", str(e))

```


```

# Example usage
image_path = '/content/drive/MyDrive/MRI Images/Testing/meningioma/Te-meTr_0001.jpg' # Provide the path to your new image
detect_and_display(image_path, model)

```

1/1 ————— 2s 2s/step

No Tumor (Confidence: 93.49%)



```

# Example usage
image_path = '/content/drive/MyDrive/MRI Images/Testing/notumor/Te-noTr_0004.jpg' # Provide the path to your new image
detect_and_display(image_path, model)

```

1/1 ————— 0s 35ms/step

Tumor: pituitary (Confidence: 99.99%)




```

# Example usage
image_path = '/content/drive/MyDrive/MRI Images/Testing/pituitary/Te-piTr_0003.jpg' # Provide the path to your new image
detect_and_display(image_path, model)

```

1/1 — 0s 34ms/step

Tumor: glioma (Confidence: 100.00%)




Example usage

```
image_path = '/content/drive/MyDrive/MRI Images/Testing/glioma/Te-gl_0015.jpg' # Provide the path to your new image
detect_and_display(image_path, model)
```

1/1 — 0s 35ms/step

Tumor: meningioma (Confidence: 99.98%)



```
from tensorflow.keras.models import load_model

model = load_model('/content/drive/MyDrive/model.h5')
print("✅ Model loaded successfully from Drive")
```

WARNING:absl:Compiled the loaded model, but the compiled metrics have yet to be built. `model.compile\_metrics` will be empty
 ✅ Model loaded successfully from Drive

```
from google.colab import files
uploaded = files.upload()
```

Choose Files No file chosen
 this cell to enable.
 Saving 1 img to 1 (1) img

Upload widget is only available when the cell has been executed in the current browser session. Please rerun

```
import numpy as np
import matplotlib.pyplot as plt
from tensorflow.keras.preprocessing import image

img_name = list(uploaded.keys())[0]

IMG_SIZE = 128 # 🔥 MUST match training size

img = image.load_img(img_name, target_size=(IMG_SIZE, IMG_SIZE))
img_array = image.img_to_array(img) / 255.0
img_array = np.expand_dims(img_array, axis=0)
```

```
plt.imshow(img)
plt.axis("off")

prediction = model.predict(img_array)[0][0]

if prediction > 0.5:
    print(f"🚫 Brain Tumor Detected ({prediction*100:.2f}% confidence)")
else:
    print(f"✅ No Tumor Detected ({(1-prediction)*100:.2f}% confidence)")
```

1/1 ————— 3s 3s/step
✅ No Tumor Detected (99.99% confidence)

