



Scuola Superiore
Sant'Anna

Master of Science in Bionics Engineering

Academic Year 2025-2026

Pontedera, March 12, 2026

Bioinspired and Soft Robotics


Soft Robotics Technologies

Bioinspiration and Biomimetics

Matteo Cianchetti - matteo.cianchetti@santannapisa.it



How to leave the cage?



Abilities not yet reached by robots



Lessons from Nature: bioinspiration and biomimetics



Definition

The field of bioinspiration and biomimetics is based on the idea that natural biological systems can provide inspiration for the development of new technologies.

By studying biological systems and understanding their underlying principles, researchers can create innovative designs that mimic or improve upon the functions of these systems.



Biomimetics pioneers

Dr. Schmitt and his wife completed an incredible dual career studying **natural biological processes** and **inventing methods and machines that duplicated those actions**. This new science became known as "**Biomimetics**" or "**The Mimicry of Nature**".

His doctoral research was an attempt to produce a physical device that explicitly mimicked **the electrical action of a nerve**.



Otto H. Schmitt and his wife Viola


The word **biomimetics** was used for the first time by Schmitt on **1957**. Later, Schmitt used the word biomimetics in the title of a paper (Schmitt, O. **1969** Some interesting and useful biomimetic transforms. In Third Int. Biophysics Congress, p. 297)



Leonardo's biomimetics

Leonardo was dissatisfied with the description of the human anatomy reported by his contemporaries and their predecessors.

Muscles of the human arm



Initially, Leonardo approaches to the study of the muscular system in a superficial manner, that underlines that the aim of this study is more related to his artistic activities. With the passage of time, he developed a **passion for the muscular physiology and mechanics**. In his treatise, to better explain the movement, he proposes to replace the muscles and tendons with ropes and wires.

WINDSOR ROYAL LIBRARY




Leonardo's biomimetics

Study of bones and joints

Leonardo was determined to **understand the full skeleton and each individual bone**, as he believed that they were the bearing elements of the “**human machine**”.

Leonardo accurately depicts the curvature of the spine and includes the correct number of vertebrae.

Its clear detailing of spinal curvatures reflects Leonardo's appreciation of its important role in bodily mechanics and often used exploded views of anatomical parts to **show every single detail**.



WINDSOR ROYAL LIBRARY




Early studies on flight


Milan, 1480 - 1490

Early studies are not bioinspired. Leonardo is more focused on the study of **human capabilities to match its motor abilities with the requirements for the flight**.

Convergence between **ANATOMY** (human body and proportions) and **MECHANICS** (kinematics and dynamics of the motion)



Flapping wing




Ornithopter




Early studies on flight




Milan, 1480 - 1490



Flying machine



Mechanical wings




Codex on the flight of birds

Florence, 1500 - 1505

Leonardo resumes his investigation on flight, but with fundamental **studies on bird's flight**.

Zoology becomes a key aspect.


The project of the flying machine becomes a **radical attempt of Nature mimicry**.



Bioinspiration and Biomimetics

Codex on the flight of birds


- Flapping flight or active flight (propulsion obtained by the beating of wings)
- In-flight equilibrium manouvers in the presence of wind



Biomimetics as formal scientific field

TRENDS IN BIOMIMETICS


A search of the more than 25,000 papers in biomimicry shows the rising interest in the field over the past decade, but studies are mainly restricted to the physical sciences.



Data obtained by searching the Web of Science Core Collection with the term "biomim*" or "bioinspir*".


©nature

In the latter half of the 20th century researchers began to study biological systems in more detail, using advances in technology to better understand how natural systems work and how they can be replicated in man-made materials.





Biomimetics as formal scientific field

Documents by year



In the latter half of the 20th century researchers began to study biological systems in more detail, using advances in technology to better understand how natural systems work and how they can be replicated in man-made materials.

Documents by subject area



Biomimetics: smart solutions from Nature

Nevertheless... Natural selection is not Engineering

Organisms that are capable of surviving are **not necessarily optimal** for their technical performance. They need to survive long enough to reproduce. Models are never complete or correct: need to interpret with caution.




"We think blind copying is exactly what you don't want to do," says Robert Full, a biologist at the University of Berkeley, California. "You will fail miserably, because nature way is too complex."

One cannot simply copy Nature, but rather carefully choose Nature's behavior of interest, and extract the underlying **key principle** at a level of description that is actually possible to implement.



Biomimetics and Bioinspiration



Vincent, J. V. F.; Pellegrino, S. (Ed.) Stealing ideas from Nature in *Deployable structures* Springer, Vienna, 2001, 51-58



Bioinspiration design process (application-driven)

Methodology for applying bioinspiration to design challenges

1. **Define the Problem.** This involves identifying the desired outcome and any constraints or limitations that need to be considered. By clearly defining the problem, the designer can focus their research and analysis on finding relevant biological systems that may provide inspiration.
2. **Research and Analyze Biological Systems.** This involves observing and studying the structures, functions, and behaviors of natural systems and identifying any features or processes that may be relevant to the design problem. This step requires a deep understanding of biology and ecology, as well as the ability to observe and analyze complex natural systems.
3. **Synthesize Information.** This involves distilling the insights gained from the natural systems into a set of general design principles that can be applied to the design problem. This step requires creativity and an ability to make connections between seemingly unrelated fields.
4. **Apply Insights to Create a Solution.** This may involve developing new products, technologies, or processes that are inspired by natural systems, or it may involve modifying existing designs to incorporate biomimetic features. This step requires a deep understanding of the design problem and the ability to apply the principles learned from the natural systems in a practical way.




Biomimetics in action – Shinkansen bullet train

The train's designers were faced with the challenge of developing a high-speed train.


1. **Define the Problem.** Develop a high-speed train (more than 300 km/h) that does not create a sonic boom in tunnels and without increasing energy consumption.
2. **Research and Analyze Biological Systems.** Analysis of the anatomy of the kingfisher, a bird that is known for its ability to dive into water without creating a splash. The bird's beak has a unique shape that reduces the turbulence of the water, allowing it to enter the water with minimal disturbance.
3. **Synthesize Information.** Create a new shape for the train front that resembles the beak of a kingfisher, with a sharp, tapered tip and a gently sloping back end. This shape helps to reduce the air pressure in front of the train, reducing the amount of sonic boom it creates.
4. **Apply Insights to Create a Solution.** The new design is applied to the train and tested it in real-world conditions. The new design proved to be highly effective, reducing the sonic boom of the train by as much as 30%.

<https://www.youtube.com/watch?v=YVU6YBPaaB8>




Biomimetics in action – The “BIONIC” car

The **bionic car**: DaimlerChrysler has developed a new high fuel efficiency concept vehicle based on the body shape of the boxfish (*Ostracion meleagris*), a common cube-shaped fish found in tropical marine habitats. The bionic car will offer 20 percent lower fuel consumption and up to 80 percent lower nitrogen oxide emissions according to a release from DaimlerChrysler.




Biomimetics in action – Tour Eiffel

The **Eiffel Tower**: the perfect structure of trabecular struts in the head of the human femur inspired a French engineer at the end of the 19th Century. He was intended to design the highest structure of the world. The name of this engineer is Gustave Eiffel. In 1889 the Tower is completed.



Bioinspiration design process (curiosity-driven)







Mirko Kovač, "The Bioinspiration Design Paradigm: A Perspective for Soft Robotics" Soft Robotics 2014 1:1, 28-37



Biomimetics in action – Lotus Effect

Some leaves of water-repellent plants, such as *Nelumbo nucifera* (lotus) and *Colocasia esculenta*, are known to be superhydrophobic and self-cleaning due to hierarchical roughness (microstructure formed by papillose epidermal cells) and the presence of a hydrophobic coating (epicuticular wax tubules).

1. **Define the Problem.** Developing a non-stick coating that would repel water and other liquids and prevent the adhesion of dirt and other contaminants.
2. **Research and Analyze Biological Systems.** Studied the surface of the lotus leaf, which is known for its ability to repel water and other liquids. They analyzed the structure and chemical composition of the lotus leaf and discovered that its surface is covered by micro- and nano-scale bumps that prevent water droplets from sticking to it.




Bhushan B. Biomimetics: lessons from nature-an overview, Phil. Trans. R. Soc. A 2009 367, 1445-1486



Biomimetics in action – Lotus Effect

Some leaves of water-repellent plants, such as *Nelumbo nucifera* (lotus) and *Colocasia esculenta*, are known to be superhydrophobic and self-cleaning due to hierarchical roughness (microstructure formed by papillose epidermal cells) and the presence of a hydrophobic coating (epicuticular wax tubules).


3. **Synthesize Information.** developed a coating that mimicked the lotus leaf's structure and composition. They used a combination of silicone and fluorine to create a surface that was both water-repellent and non-stick.
4. **Apply Insights to Create a Solution.** Tested the coating on various surfaces and found that it was highly effective at repelling water and other liquids. The coating was able to prevent the adhesion of dirt and other contaminants, making it a highly useful solution for a wide range of applications.



Biomimetics in action – VELCRO





Velcro was invented by George de Mestral, a Swiss engineer, who was inspired by the way that burdock seeds stuck to his clothing and his dog's fur during a walk in the woods.

1. **Define the Problem.** De Mestral observed the way that burdock seeds attached themselves to fabric and fur and identified this as a potential solution for fastening materials together.
2. **Research and Analyze Biological Systems.** He studied the structure of the burdock seed, which has tiny hooks that attach to loops of fabric or fur. He then applied this concept to the design of a new type of fastener, using synthetic hooks and loops that would attach to each other when pressed together.
3. **Synthesize Information.** He tested his new fastener design and found that it was more durable and efficient than traditional fastening methods such as buttons and zippers.
4. **Apply Insights to Create a Solution.** de Mestral Finally patented his invention and began marketing it under the name "Velcro", which is a combination of the French words velours (velvet) and crochet (hook).




Biomimetics in action – GECKO

The **gecko tape and robot**: a gecko is the largest animal that can produce (dry) adhesion to support its weight. The gecko foot comprises a complex hierarchical structure of lamellae, setae, branches, and spatula.



Biomimetics pioneers

Application-driven



Curiosity-driven

Broekhoven, C., du, A., Escaping the Labyrinth of Bioinspiration: Biodiversity as Key to Successful Product Innovation. *Adv. Funct. Mater.* 2022, 32, 2110235.




Modern view of biomimicry

Biomimetic robotics:

- developing robots for real-world applications
- studying biological systems by robotic platforms

Unified approach to the study of living organisms and robots



B.Webb, "What does robotics offer animal behaviour?," *Animal Behaviour*, vol. 60, no. 5, pp. 545 – 558, 2000.




Modern view of biomimicry

Biomimetic robotics:

- developing robots for real-world applications
- studying biological systems by robotic platforms

Unified approach to the study of living organisms and robots



B.Webb, "What does robotics offer animal behaviour?," *Animal Behaviour*, vol. 60, no. 5, pp. 545 – 558, 2000.



The OCTOPUS case study



What is special in the octopus (in the eyes of a roboticist)

Octopus vulgaris (phylum *Mollusca*, class *Cephalopoda*)

- No rigid structures:
 - Virtually infinite number of DOF
 - All-direction bending
 - Capability to squeeze into small apertures
(same size of their brain capsule – Ex: 1-inch hole)



Why the octopus

The octopus shows strength and unexpected manipulation capabilities

Variable and controllable stiffness



Video courtesy of Binyamin Hochner



Video recorded at The BioRobotics Institute




Octopus arm morphology

Longitudinal Muscles


Transverse Muscles

Oblique Muscles




Muscular Hydrostat:
Constant volume
during contractions

The muscular system serves as a modifiable skeleton and allows the transformation of force into motion




Octopus arm morphology

ELONGATION



■ CONTRACTED



■ RELAXED



Octopus arm morphology


ELONGATION

SHORTENING



CONTRACTED

RELAXED





Octopus arm morphology

ELONGATION


SHORTENING

STIFFENING



CONTRACTED

RELAXED






Octopus arm morphology

ELONGATION

SHORTENING


STIFFENING



TORSION

CONTRACTED

RELAXED






Octopus arm morphology

ELONGATION

SHORTENING

STIFFENING




TORSION

BENDING

CONTRACTED

RELAXED



From biology to technology



Biologists and roboticists working together



Characterization of the octopus arm for biomimetics



Need for quantitative data on the octopus anatomy and biomechanics, to set the specifications for the design of the octopus-like robot

Anatomy:


- Ultrasound imaging
- Histological analysis

Biomechanics:

- In vivo biomechanical measurements of arm capabilities

**Mechatronic structure
of artificial muscular
hydrostat**

**Artificial muscular
hydrostat
performance**



Methods

Anatomical Study





Ecography

- ✓ 12 anesthetized *Octopus vulgaris* in a rectangular tank
- ✓ Esaote S.p.a. MyLab™Five VET
- ✓ Linear transducer LA435 (at 18 MHz)
Axial-lateral resolution: 0.085-0.104 mm
- ✓ Scanning of the Transverse, Sagittal and Horizontal planes
- ✓ Direct measurement of anatomical structures dimensions
- ✓ Measures of the tissues density:


Echo Intensity signal (EI)

Histology

Ultrasound imaging and histology are applied to investigate arm morphology along the three planes





Arm Horizontal sections




Methods

Biomechanical Measurements


- 24 octopuses (*O. vulgaris*)
 - ✓ 24 animals from Naples
 - ✓ Different sex (8 Female, 16 Male)
 - ✓ Different Weight (140 ÷ 560g)
- Training Phase
 - ✓ 2 ÷ 5 sessions
 - ✓ One arm performances
 - ✓ Bait position from proximal to distal
- In vivo Measurements
 - ✓ Arm reference length
 - ✓ Elongation
 - ✓ Force
- Measurement in anesthesia
 - ✓ Mantle, Arms, Total Length



Design of transverse actuators inspired by the octopus muscles arrangement




Transverse
EI: 29.3 ± 1.5





- Radial net configuration with straight interweaving of transverse muscle fibers
- Key-role of the trabeculae in maintaining circular the transverse section during contraction

4 arcs configuration:

- too simplistic
- not shape preserving
- lower efficiency



Radial
configuration



More efficiency in the reduction of the diameter





Design of longitudinal actuators inspired by the octopus muscles arrangement



- Muscles insertions along the arm allow multiple point bending

Longitudinal Muscles: **longitudinal actuators** with insertion points along the arm allow multiple point bending





- The arm prototype rely on additional cables from the base of the arm and fitted to several points along the arm length, thus improving bending capability



Results on Octopus Biomechanics

Arm Elongation :

70% of arms mean elongation
corresponding to
23% of diameter reduction



Arm Force :

Max Pulling Force
49.8 N @ 400 mm
(m=1600g)
28.6 N @ 200 mm
(m=476g)

Mean Pulling Force
40N with arm
length 400 mm


**Grasp Point
Position**
0.75 of total
arm length

**Contraction
Time**
1-2 sec

Measurements of the pulling force applied by the octopus arm vs artificial arm performance

Longitudinal Muscles: longitudinal cables + sheaths



- Results of the force measurements (40 N mean, 1-2 sec contraction time) are used as specification in setting the longitudinal actuators of the robotic arm prototypes
- Cables have been covered with sheaths to reduce friction and avoid silicone damages
- The grasp point position at a 0.75 of total length has been used to allow grasping during the arm prototype pulling tests



Fabrication of muscular hydrostat mock-ups

Longi-transverse cables mock-up

n° 9 'longi-transversal' Rigid Elements







- 20 mm stroke for every section
- 30 N needed to reach the deformation
- 40 cables actuated by 13 motors
- cables diameter: 0.1 mm
- cables breaking load: 50 N





Fabrication of muscular hydrostat mock-ups

Longi-transverse cables mock-up



Structural design specifications from octopus nerve cord arrangement



- Nervous tissue of the arm nerve cord has a sinusoidal arrangement at the arm rest length while is extended during elongation




**Nerve cord: electrical cables
unstretchable components**

- Large elongations can be achieved using a sinusoidal arrangement for cables



Material elasticity




Silicones




Instron
L=2 cm
D=2 cm

Experimental setup



Experimental measurements of stress – stretch curves

Natural tentacle



Elastic module of interpolating curves

	p1	p2	p3	p4	arsquare	rmse
fit1	2,64	-7,65	7,441	-2,436	0,99114	0,0022
fit2	2,533	-7,42	7,337	-2,452	0,99478	0,0016
fit3	1,819	-5,46	5,515	-1,877	0,99249	0,0019
fit4	1,774	-5,4	5,56	-1,936	0,99641	0,0013

$$E_m(\lambda) = 3 \cdot p1 \cdot \lambda^2 + 2 \cdot p2 \cdot \lambda + p3$$





Material density


1.022 kg/m³ (seawater density)




1.042 kg/m³ (arm density)

1.04 kg/m³ (used silicones)



From biology to robotics

Longitudinal muscles			Transverse muscles	
Mechanical performances			Design arrangement	Mechanical performances
Max Pulling Force	Mean Pulling Force	Time to contract	 Longitudinal arrangement	 Radial arrangement
49.8N@400mm (m=1600g) 26.8N@200mm (M=467g)	40N with arm length 400mm (100g)	1-2s		
			70% of arm elongation corresponding to 23% of diameter reduction	

Nerve cord arrangement	Connective tissue	Arm shape
 Sinusoidal arrangement at the arm rest length	 Helicoidally braided arrangement	

Margheri et al., *Bioinspiration & Biomimetics*, 2012 & Mazzolai et al., *Bioinspiration & Biomimetics*, 2012.



From biology to robotics

Design and development of an artificial muscular hydrostat

octopus

Nervous system

Transverse muscles

Longitudinal muscles

Connective tissue

OCTOPUS


Local processing, wires

Transverse actuation system

Longitudinal actuation system

Embedding material / skin

Mechanical interface / containment



Laschi et al., *Bioinspir. Biomim.*, 2009.

Cianchetti et al., *Materials Science and Engineering: C*, 2011.




Design of an actuator for the artificial muscular hydrostat (ElectroActive Polymer)





Soft materials

Passive deformation capability

Relatively 'fast' response time





$$F = -\frac{dU}{dz} = \frac{\epsilon_r \epsilon_0 V^2}{z^2} A$$



Design of an actuator for the artificial muscular hydrostat (Shape Memory Alloys)

Pros:

- lightweight
- flexible
- high work density
- high possibility of miniaturization
- simple electronic drivers




Cons:


- low strain (5-8%)
- low efficiency
- relatively high current
- low bandwidths
- non linear behaviour
- wide hysteresis



Spring shape
(more than 300%)





Well studied
cooling system
All – nothing activation
and antagonistic
arrangement



The artificial muscular hydrostat

Transverse actuators – single element




SMA spring with a PTFE sheath **in water**
coupled with an elastomeric material that
provides a restoring force

- About 1Hz of working frequency
- 1.2A of operating current
- PWM frequency: 100Hz
- PWM duty cycle: 25%
- $A_{\max}=2.4A$



The artificial muscular hydrostat

Braided structure



Octopus Arm Connective Tissue
(Kier and Stella, 2007)

20% of diameter reduction





89% of elongation

It provides a mechanical support





It transforms transverse contraction in elongation and propagates the deformation longitudinally

Sample of the PET braided sleeve used as artificial connective tissue



The artificial muscular hydrostat

Modular unit






PET braided sleeve:
External diameter relaxed: 30mm
External diameter contracted: 20mm


Actuator:
8 SMA springs
0.2 mm SmartFlex® wire diameter
Spring internal diameter: 1 mm



OCTOPUS arm prototype v1




OCTOPUS arm prototype v1




**Design and development of a
soft robotic octopus arm
exploiting embodied intelligence**


M. Cianchetti, M. Follador, B. Mazzolai, P. Dario, C. Laschi




OCTOPUS arm prototype v2



View of the external part of the arm



View of the internal part of the arm



No cables, but longitudinal SMA springs

SMA spring actuators directly linked to braided sheath without rigid parts

Electrical cable interlaced with the yarns of the braided sheath

Laschi et al., *Advanced Robotics*, 2012



OCTOPUS arm prototype v2



Rest length



Elongation




Shortening



Bending



Multi – Bending



OCTOPUS arm prototype v3



Rest length



Elongation



Shortening





Bending



Multi – Bending

11 transverse and 12 longitudinal SMA springs, 4 longitudinal cables



The OCTOPUS robot



C. Laschi, B. Mazzolai, M. Cianchetti, L. Margheri, M. Follador, P. Dario, "A Soft Robot Arm Inspired by the Octopus", *Advanced Robotics*, Vol.26, No.7, 2012.
M. Calisti, M. Giorelli, G. Levy, B. Mazzolai, B. Hochner, C. Laschi, P. Dario, "An octopus-bioinspired solution to movement and manipulation for soft robots", *Bioinspiration & Biomimetics*, Vol.6, No.3, 2011, 10 pp.
C. Laschi, B. Mazzolai, V. Mattoli, M. Cianchetti, P. Dario, "Design of a biomimetic robotic octopus arm", *Bioinspiration&Biomimetics*, Vol.4, No.1, 2009.

Bioinspiration and biomimetics

Advantages

- **Novel Solutions:** Natural systems have evolved over millions of years to be highly efficient and effective, and bioinspiration and biomimetics offer a way to tap into this vast source of knowledge to develop new solutions to complex problems.
- **Sustainability:** Bioinspired and biomimetic technologies can be designed to use sustainable and renewable resources, and to minimize negative impacts on local ecosystems and the wider environment.
- **Cost-Effective:** Biomimetic designs can also be cost-effective, as they often make use of existing natural structures and materials that are readily available in the environment.
- **Efficiency:** Natural systems are often highly efficient, and biomimetic designs can help to improve the efficiency of many different technologies, from transportation to energy production to manufacturing.
- **Interdisciplinarity:** Bioinspiration and biomimetics involve the integration of knowledge from many different disciplines, including biology, physics, materials science, and engineering. This interdisciplinary approach can lead to new insights and breakthroughs that might not be possible with a narrower focus.



Bioinspiration and biomimetics

Limitations

- **Lack of Understanding:** While natural systems are highly effective, we still have much to learn about how they work and how they can be translated into practical designs. This lack of understanding can make it challenging to develop effective biomimetic technologies.
- **Complexity:** Natural systems are often highly complex and difficult to replicate, which can make it challenging to translate biomimetic designs into practical technologies.
- **Compatibility:** Biomimetic designs may not be compatible with existing manufacturing processes or materials, which can make it difficult to bring them to market in a cost-effective way.
- **Patentability:** In some cases, biomimetic designs may not be patentable, as they may be seen as direct copies of natural systems. This can limit the potential for commercialization and may make it difficult to attract investment.



How to leave the cage?

