INTERNSHIP WEEKLY REPORT

Week 01 : Reconnaissance & Passive Information Gathering

Intern Name	Manahil Fayyaz
Roll No.	CSI-B1-200
Supervisor / Mentor	Umar Niaz
Submission Date	March 8 , 2026
Target Scope	Hackthissite.org (Authorized)

Executive Summary

This report documents the reconnaissance and passive information gathering activities conducted during Week 01 of the cybersecurity internship program. All tasks were performed within the authorized scope of a public bug bounty program and strictly adhere to responsible disclosure practices.

The primary objective of this week was to build a comprehensive external attack surface map of the target organization by identifying subdomains, profiling infrastructure technologies, conducting credential leak research, and filtering live assets for further analysis.

Weekly Objectives Completed:

- Task 01 — Subdomain Enumeration & Discovery
- Task 02 — Infrastructure & Technology Profiling
- Task 03 — GitHub Dorking & Credential Leak Investigation
- Task 04 — Live Asset Filtering & Visual Reconnaissance

TASK 01: Subdomain Enumeration & Discovery

Perform comprehensive subdomain discovery using automated tools and passive sources

1.1 Objective

The goal of this task was to identify as many subdomains belonging to the target organization as possible using a combination of active enumeration tools and passive certificate transparency sources. A broader subdomain list expands the attack surface and reveals forgotten or misconfigured assets that may be vulnerable.

1.2 Tools Used

- Subfinder — Fast passive subdomain discovery via multiple data sources
- Assetfinder — Lightweight subdomain enumeration tool by TomNomNom
- Amass — Advanced OSINT-based subdomain enumeration
- DNSDumpster — Web-based DNS reconnaissance tool
- CRT.sh — SSL/TLS certificate transparency log search

1.3 Process

Step 1 — Subfinder

Subfinder was executed against the target domain to passively enumerate subdomains using its built-in data source integrations including VirusTotal, Shodan, and others.

```
subfinder -d robinhood.com -o robinsub.txt
```

Figure 1.1 — Subfinder executing subdomain enumeration against target domain

Step 2 — Assetfinder

Assetfinder was used as a complementary tool to retrieve additional subdomains from different passive data sources, ensuring broader coverage.

```
assetfinder --subs-only robinhood.com > robinasset.txt
```

```
┌──(kali㉿kali)-[~/Desktop/Week1 Task1]
└─$ assetfinder --subs-only hackthissite.org > assethack.txt

┌──(kali㉿kali)-[~/Desktop/Week1 Task1]
└─$ cat assethack.txt
hackthissite.org
www.hackthissite.org
api.hackthissite.org
ctf.hackthissite.org
email.hackthissite.org
forums.hackthissite.org
git.hackthissite.org
h5ai.hackthissite.org
hp.hackthissite.org
irc.hackthissite.org
irc-hub.hackthissite.org
irc-www.hackthissite.org
lille.irc.hackthissite.org
wolf.irc.hackthissite.org
www.irc.hackthissite.org
legal.hackthissite.org
mirror.hackthissite.org
psrp.hackthissite.org
qdb.hackthissite.org
stats.hackthissite.org
status.hackthissite.org
irc.hackthissite.org
irc-v6.hackthissite.org
```

Figure 1.2 — Assetfinder results for target domain

Step 3 — Amass

Amass was run for deeper OSINT-based enumeration. Its output was saved for later merging with other tool results.

```
amass enum -passive -d robinhood.com -o robinamass.txt
```

```
┌──(kali㉿kali)-[~/Desktop/Week1 Task1]
└─$ cat amasshack.txt
hackthissite.org (FQDN) --> mx_record --> aspmx2.googlemail.com (FQDN)
hackthissite.org (FQDN) --> mx_record --> alt2.aspmx.l.google.com (FQDN)
hackthissite.org (FQDN) --> mx_record --> aspmx.l.google.com (FQDN)
hackthissite.org (FQDN) --> mx_record --> alt1.aspmx.l.google.com (FQDN)
hackthissite.org (FQDN) --> mx_record --> aspmx3.googlemail.com (FQDN)
hackthissite.org (FQDN) --> mx_record --> aspmx4.googlemail.com (FQDN)
hackthissite.org (FQDN) --> mx_record --> aspmx5.googlemail.com (FQDN)
hackthissite.org (FQDN) --> ns_record --> f.ns.buddyns.com (FQDN)
hackthissite.org (FQDN) --> ns_record --> g.ns.buddyns.com (FQDN)
hackthissite.org (FQDN) --> ns_record --> j.ns.buddyns.com (FQDN)
hackthissite.org (FQDN) --> ns_record --> c.ns.buddyns.com (FQDN)
hackthissite.org (FQDN) --> ns_record --> h.ns.buddyns.com (FQDN)
forum.hackthissite.org (FQDN) --> cname_record --> hackthissite.org (FQDN)
1-v3stage-cdn.hackthissite.org (FQDN) --> cname_record --> v3stage-cdn.hackthissite.org (FQDN)
email.hackthissite.org (FQDN) --> cname_record --> email.hackmail.org (FQDN)
v3dev-cdn.hackthissite.org (FQDN) --> cname_record --> v3dev.hackthissite.org (FQDN)
wolf.irc.hackthissite.org (FQDN) --> a_record --> 185.24.222.13 (IPAddress)
wolf.irc.hackthissite.org (FQDN) --> aaaa_record --> 2a02:2770:9:0:21a:4aff:fe68:f705 (IPAddress)
psrp.hackthissite.org (FQDN) --> cname_record --> hackmail.org (FQDN)
h5ai.hackthissite.org (FQDN) --> cname_record --> hackthissite.github.io (FQDN)
185.24.220.0/22 (Netblock) --> contains --> 185.24.222.13 (IPAddress)
2a02:2770::/32 (Netblock) --> contains --> 2a02:2770:9:0:21a:4aff:fe68:f705 (IPAddress)
196752 (ASN) --> managed_by --> TILAA (RIROrganization)
196752 (ASN) --> announces --> 185.24.220.0/22 (Netblock)
196752 (ASN) --> announces --> 2a02:2770::/32 (Netblock)
```

Figure 1.3 — Amass enumeration in progress

```
File  Edit  View  Search  Terminal  Help
┌──(root㉿kali)-[~/Week1 Task1]
└─# cat amass.txt
hackthisite.org (FQDN) --> ns_record --> sk.s7.ans2.ns147.klczy.com (FQDN)
hackthisite.org (FQDN) --> ns_record --> sk.s7.ans1.ns147.klczy.com (FQDN)

┌──(root㉿kali)-[~/Week1 Task1]
└─# amass enum -passive -d hackthisite.org -o amass.txt
hackthisite.org (FQDN) --> ns_record --> sk.s7.ans2.ns147.klczy.com (FQDN)
hackthisite.org (FQDN) --> ns_record --> sk.s7.ans1.ns147.klczy.com (FQDN)
ww9.hackthisite.org (FQDN) --> cname_record --> g49361626.c.giantpanda.com (FQDN)
www1.hackthisite.org (FQDN) --> cname_record --> 593664.parkingcrew.net (FQDN)
ww6.hackthisite.org (FQDN) --> cname_record --> 72655.bodis.com (FQDN)
ww5.admin.hackthisite.org (FQDN) --> cname_record --> 743701.parkingcrew.net (FQDN)
sk.s7.ans2.ns147.klczy.com (FQDN) --> a_record --> 199.79.60.152 (IPAddress)
199.79.60.0/23 (Netblock) --> contains --> 199.79.60.152 (IPAddress)
40034 (ASN) --> managed_by --> CONFLUENCE-NETWORK-INC - Confluence Networks Inc (RIROrganization)
40034 (ASN) --> announces --> 199.79.60.0/23 (Netblock)
ww3.hackthisite.org (FQDN) --> cname_record --> sedoparking.com (FQDN)
ww5.hackthisite.org (FQDN) --> cname_record --> 743701.parkingcrew.net (FQDN)
ww5.karmai.hackthisite.org (FQDN) --> cname_record --> 743701.parkingcrew.net (FQDN)

The enumeration has finished

┌──(root㉿kali)-[~/Week1 Task1]
└─#
```

Figure 1.4 — Verifying Amass output file content

Step 4 — Merging & Deduplication

All tool outputs were merged into a single master file and deduplicated using sort -u to ensure only unique subdomains were retained for downstream processing.

```
cat robinsub.txt robinasset.txt robinamass.txt crt_robin.txt | sort -u >
master_subdomains.txt
```

```
┌──(kali㉿kali)-[~/Desktop/Week1 Task1]
└─$ cat subhack.txt assethack.txt amasshack.txt | sort -u > master_subdomains.txt

┌──(kali㉿kali)-[~/Desktop/Week1 Task1]
└─$ ls
amasshack.txt  assethack.txt  master_subdomains.txt  subhack.txt

┌──(kali㉿kali)-[~/Desktop/Week1 Task1]
└─$ cat master_subdomains.txt
0.0.1.0.7.8.1.0.4.7.0.0.7.3.1.0.8.d.c.c.8.0.0.0.0.0.d.1.4.1.0.0.2.ip6.arpa (FQDN) ──> ptr_record ──> hackthissite.org (FQDN)
0 (ASN) ──> announces ──> 2406:d500:7::/48 (Netblock)
0 (ASN) ──> announces ──> 5.220.0.0/14 (Netblock)
0 (ASN) ──> announces ──> 89.106.200.0/21 (Netblock)
0 (ASN) ──> managed_by ──> Not routed (RIROrganization)
0-v3stage-cdn.hackthissite.org (FQDN) ──> cname_record ──> v3stage-cdn.hackthissite.org (FQDN)
100.187.74.137.in-addr.arpa (FQDN) ──> ptr_record ──> hackthissite.org (FQDN)
1.0.1.0.7.8.1.0.4.7.0.0.7.3.1.0.8.d.c.c.8.0.0.0.0.0.d.1.4.1.0.0.2.ip6.arpa (FQDN) ──> ptr_record ──> hackthissite.org (FQDN)
103.187.74.137.in-addr.arpa (FQDN) ──> ptr_record ──> hackthissite.org (FQDN)
103.25.56.0/22 (Netblock) ──> contains ──> 103.25.56.55 (IPAddress)
108.177.123.0/24 (Netblock) ──> contains ──> 108.177.123.26 (IPAddress)
115.187.74.137.in-addr.arpa (FQDN) ──> ptr_record ──> api.hackthissite.org (FQDN)
118.187.74.137.in-addr.arpa (FQDN) ──> ptr_record ──> api.hackthissite.org (FQDN)
133.187.74.137.in-addr.arpa (FQDN) ──> ptr_record ──> mirror.hackthissite.org (FQDN)
134.187.74.137.in-addr.arpa (FQDN) ──> ptr_record ──> mirror.hackthissite.org (FQDN)
135.187.74.137.in-addr.arpa (FQDN) ──> ptr_record ──> stats.hackthissite.org (FQDN)
136.187.74.137.in-addr.arpa (FQDN) ──> ptr_record ──> stats.hackthissite.org (FQDN)
136557 (ASN) ──> announces ──> 103.25.56.0/22 (Netblock)
136557 (ASN) ──> announces ──> 2406:d500:2::/48 (Netblock)
```

Figure 1.5 — Merging all tool outputs into master subdomain list

Figure 1.6 — Total count of unique subdomains discovered

```
File  Actions  Edit  View  Help
qdb.hackthissite.org
stats.hackthissite.org
status.hackthissite.org
status-new.hackthissite.org
wolf.irc.hackthissite.org
wolf.irc-v6.hackthissite.org
www.hackthissite.org
www.irc.hackthissite.org

┌──(kali㉿kali)-[~/Week1]
└─$ wc -l master_subdomains.txt
301 master_subdomains.txt

┌──(kali㉿kali)-[~/Week1]
└─$ sort subhack.txt assethack.txt amasshack.txt | uniq -c | sort -nr | head
      9 irc.hackthissite.org
      8 wolf.irc.hackthissite.org
      6 new-irc.hackthissite.org
      6 lille.irc.hackthissite.org
      6 hackthissite.org
      5 irc-wolf.hackthissite.org
      3 www.hackthissite.org
      3 mail.hackthissite.org
      3 lille.irc-v6.hackthissite.org
      3 irc-v6.hackthissite.org

┌──(kali㉿kali)-[~/Week1]
└─$
```

Figure 1.7 — Overlap analysis showing subdomain frequency across tools

Step 5 — DNSDumpster & CRT.sh (Passive/Historical Sources)

DNSDumpster was used via its web interface to retrieve DNS records and historical subdomain data. The results were exported as an XLSX file, converted to CSV, and then parsed with grep to extract all hackthissite subdomains.

CRT.sh was queried via curl to extract subdomains from SSL certificate transparency logs — a valuable source for discovering assets that may not appear in standard enumeration.

```
┌──(kali㉿kali)-[~/Desktop/Week1 Task1/crt.sh]
└─$ curl -s https://crt.sh/?q=%25.hackthissite.org| grep -oE "[a-zA-Z0-9._-]\.hackthissite\.org" | sort -u > crt_hack.txt

┌──(kali㉿kali)-[~/Desktop/Week1 Task1/crt.sh]
└─$ cat crt_hack.txt
6.hackthissite.org
c.hackthissite.org
f.hackthissite.org
i.hackthissite.org
l.hackthissite.org
p.hackthissite.org
s.hackthissite.org
w.hackthissite.org

┌──(kali㉿kali)-[~/Desktop/Week1 Task1/crt.sh]
└─$ ls
crt_hack.txt  crthack.txt  crt_result.txt  crt.sh  crt_v2.sh  output  README.md  Screenshot

┌──(kali㉿kali)-[~/Desktop/Week1 Task1/crt.sh]
└─$ rm crt_result.txt
```

Figure 1.8 — CRT.sh query output showing certificate-based subdomai



Figure 1.9 — DNSDumpster web interface showing DNS records



Figure 1.10 — DNSDumpster data

The XLSX export from DNSDumpster was converted to CSV and then parsed to extract domain names:

```
┌──(kali㉿kali)-[~/Desktop/Week1 Task1]
└─$ cat dnsdumpster.txt
b.hackthissite.org
c.hackthissite.org
f.hackthissite.org
i.hackthissite.org
l.hackthissite.org
p.hackthissite.org
r.hackthissite.org
s.hackthissite.org
t.hackthissite.org
w.hackthissite.org

┌──(kali㉿kali)-[~/Desktop/Week1 Task1]
└─$ cat dnsdumpster.txt master_subdomains.txt crthack.txt | sort -u > combined.txt

┌──(kali㉿kali)-[~/Desktop/Week1 Task1]
└─$ cat combined.txt
0.0.1.0.7.8.1.0.4.7.0.0.7.3.1.0.8.d.c.c.8.0.0.0.0.d.1.4.1.0.0.2.ip6.arpa (FQDN) ──> ptr_record ──> hackthissite.org (FQDN)
0 (ASN) ──> announces ──> 2406:d500:7::/48 (Netblock)
0 (ASN) ──> announces ──> 5.220.0.0/14 (Netblock)
0 (ASN) ──> announces ──> 89.106.200.0/21 (Netblock)
0 (ASN) ──> managed_by ──> Not routed (RIROrganization)
0-v3stage-cdn.hackthissite.org (FQDN) ──> cname_record ──> v3stage-cdn.hackthissite.org (FQDN)
100.187.74.137.in-addr.arpa (FQDN) ──> ptr_record ──> hackthissite.org (FQDN)
1.0.1.0.7.8.1.0.4.7.0.0.7.3.1.0.8.d.c.c.8.0.0.0.0.d.1.4.1.0.0.2.ip6.arpa (FQDN) ──> ptr_record ──> hackthissite.org (FQDN)
103.187.74.137.in-addr.arpa (FQDN) ──> ptr_record ──> hackthissite.org (FQDN)
```

Figure 1.11 — Final combined subdomain master list

1.4 Results Summary

The multi-tool approach successfully generated a comprehensive subdomain list. The overlap analysis confirmed that no single tool captured all subdomains, validating the use of multiple data sources. All results were deduplicated and stored for use in Task 04.

TASK 02: Infrastructure & Technology Profiling

Identify the technologies and infrastructure components powering the target's web assets

2.1 Objective

This task focused on profiling the technology stack of the target organization's web properties. Understanding what frameworks, CMS platforms, web servers, and CDN providers are in use allows a security researcher to narrow focus toward known vulnerabilities associated with those technologies.

2.2 Tools Used

- Wappalyzer CLI — Browser extension / CLI tool for technology fingerprinting
- WhatWeb — Command-line web technology fingerprinter
- WHOIS — Domain registration and ownership lookup
- NSLookup — DNS record query tool
- Google Dorking — Advanced search operators to find exposed sensitive files

2.3 Step-by-Step Process

Step 1 — Wappalyzer

Wappalyzer was used to identify the technology stack of the target's primary domain, revealing information about frontend frameworks, analytics tools, CDN providers, and server technologies.



Figure 2.1 — Wappalyzer technology fingerprinting results

Step 2 — WHOIS Lookup

A WHOIS query was performed on the target domain to gather registration information, name servers, and registrar details. This assists in mapping the organizational infrastructure and identifying hosting providers.

```
whois hackthissite.org
```

```
┌──(kali㉿kali)-[~/Week1 Task2]
└─$ whois hackthissite.org
Domain Name: hackthissite.org
Registry Domain ID: REDACTED
Registrar WHOIS Server: http://whois.porkbun.com
Registrar URL: https://porkbun.com
Updated Date: 2025-07-15T23:08:30Z
Creation Date: 2003-08-10T15:01:25Z
Registry Expiry Date: 2026-08-10T15:01:25Z
Registrar: Porkbun LLC
Registrar IANA ID: 1861
Registrar Abuse Contact Email: abuse@porkbun.com
Registrar Abuse Contact Phone: +1.8557675286
Domain Status: clientDeleteProhibited https://icann.org/epp#clientDeleteProhibited
Domain Status: clientTransferProhibited https://icann.org/epp#clientTransferProhibited
Name Server: c.ns.buddyns.com
Name Server: f.ns.buddyns.com
Name Server: g.ns.buddyns.com
Name Server: h.ns.buddyns.com
Name Server: j.ns.buddyns.com
DNSSEC: unsigned
URL of the ICANN Whois Inaccuracy Complaint Form: https://icann.org/wicf/
>>> Last update of WHOIS database: 2026-03-06T21:01:31Z <<<

For more information on Whois status codes, please visit https://icann.org/epp

Terms of Use: Access to Public Interest Registry WHOIS information is provided to assist persons in determining the contents of a domain
```

Figure 2.2 — WHOIS lookup results for target domain

Step 3 — NSLookup / DNS Records

NSLookup was used to retrieve DNS A, MX, and NS records for the target, helping to identify IP ranges, mail servers, and authoritative nameservers that may reveal third-party service providers.

```
nslookup hackthissite.org
```

```
┌──(kali㉿kali)-[~/Week1 Task2]
└─$ nslookup hackthissite.org
Server:         39.39.39.39
Address:        39.39.39.39#53

Non-authoritative answer:
Name:   hackthissite.org
Address: 137.74.187.100
Name:   hackthissite.org
Address: 137.74.187.101
Name:   hackthissite.org
Address: 137.74.187.104
Name:   hackthissite.org
Address: 137.74.187.102
Name:   hackthissite.org
Address: 137.74.187.103

┌──(kali㉿kali)-[~/Week1 Task2]
└─$
```

Figure 2.3 — NSLookup DNS record enumeration

Step 4 — WhatWeb

WhatWeb was run from the command line to perform automated technology detection across the target domain, providing a detailed report of identified components including server headers, CMS, JavaScript libraries, and security headers.

Figure 2.4 — WhatWeb technology detection output

Step 5 — Advanced Google Dorking

Google Dork queries were crafted to search for publicly accessible sensitive files or misconfigured directories on the target domain. This is a passive technique that relies entirely on publicly indexed data.

Dorks Executed:

```
site:hackthissite.org inurl:phpinfo.php
site:hackthissite.org intitle:"phpinfo()"
site:hackthissite.org ext:env
site:hackthissite.org ext:bak | ext:zip | ext:old
site:hackthissite.org inurl:robots.txt
```

These queries were designed to surface potential exposures such as PHP configuration pages revealing server internals, unprotected environment configuration files, backup archives, and directory listing pages.



Figure 2.5 — Google Dorking for phpinfo() exposure



Figure 2.6 — Google Dorking for environment and backup files



Figure 2.7 — Google Dorking for additional sensitive file patterns

2.4 Results Summary

Technology profiling successfully identified the primary infrastructure components. WHOIS and DNS analysis mapped the organizational IP ranges and third-party service dependencies. Google Dorking queries were executed responsibly, and any sensitive findings would be handled according to the program's responsible disclosure policy.

TASK 03: GitHub Dorking & Credential Leak Investigation

Search public code repositories for accidentally committed sensitive data

3.1 Objective

This task involved searching public code repositories — primarily GitHub — for accidentally committed sensitive data associated with the target organization. Developers sometimes inadvertently push API keys, database credentials, internal hostnames, or configuration files to public repositories, creating significant security risks.

3.2 Tools & Techniques Used

- GitHub Advanced Search — Using search operators to find sensitive keywords
- GitHub Dork Queries — org:, filename:, path:, and content-based searches
- Manual review of search results for false positive elimination

3.3 Step-by-Step Process

Step 1 — GitHub Dork Query Construction

Targeted search queries were constructed using GitHub's advanced search syntax to find repositories containing references to the target organization's domain, internal tooling names, or sensitive configuration patterns.

Step 2 — Search Execution & Review

Each query was executed and results were carefully reviewed. Findings were assessed for relevance and potential impact. Any genuine credential exposure would require immediate responsible disclosure before being documented in this report.



Figure 3.1 — GitHub search results for target organization credentials



Figure 3.2 — GitHub Dorking query execution and result analysis

```
┌──(kali㉿kali)-[~]
└─$ githacker --url https://hackthissite.org/.git/  --output-folder GitHacker_result
2026-03-07 16:24:55 INFO 1 urls to be exploited
2026-03-07 16:24:55 INFO Exploiting https://hackthissite.org/.git/ into GitHacker_result/9e4a65ca36471fcf6a75bd9b111ffccf
/usr/lib/python3/dist-packages/urllib3/connectionpool.py:1062: InsecureRequestWarning: Unverified HTTPS request is being made to host 'ha
ckthissite.org'. Adding certificate verification is strongly advised. See: https://urllib3.readthedocs.io/en/1.26.x/advanced-usage.html#s
sl-warnings
  warnings.warn(
/usr/lib/python3/dist-packages/urllib3/connectionpool.py:1062: InsecureRequestWarning: Unverified HTTPS request is being made to host 'ww
w.hackthissite.org'. Adding certificate verification is strongly advised. See: https://urllib3.readthedocs.io/en/1.26.x/advanced-usage.ht
ml#ssl-warnings
  warnings.warn(
/usr/lib/python3/dist-packages/urllib3/connectionpool.py:1062: InsecureRequestWarning: Unverified HTTPS request is being made to host 'ha
ckthissite.org'. Adding certificate verification is strongly advised. See: https://urllib3.readthedocs.io/en/1.26.x/advanced-usage.html#s
sl-warnings
  warnings.warn(
/usr/lib/python3/dist-packages/urllib3/connectionpool.py:1062: InsecureRequestWarning: Unverified HTTPS request is being made to host 'ww
w.hackthissite.org'. Adding certificate verification is strongly advised. See: https://urllib3.readthedocs.io/en/1.26.x/advanced-usage.ht
ml#ssl-warnings
  warnings.warn(
/usr/lib/python3/dist-packages/urllib3/connectionpool.py:1062: InsecureRequestWarning: Unverified HTTPS request is being made to host 'ha
ckthissite.org'. Adding certificate verification is strongly advised. See: https://urllib3.readthedocs.io/en/1.26.x/advanced-usage.html#s
sl-warnings
  warnings.warn(
2026-03-07 16:25:01 ERROR The target url(https://hackthissite.org/) is not a valid git repository, `.git/HEAD` not exists
2026-03-07 16:25:01 INFO 0 / 1 were exploited successfully
```

Figure 3.3 — Further investigation of repository search results

3.4 Results Summary

No active credential leaks or sensitive data exposures were identified in public repositories for the target organization during this review period. The search returned no repositories with confirmed sensitive material. This is a positive security indicator, though ongoing monitoring of public code repositories is recommended as part of a continuous security program.

Note: *Had any active credentials been discovered, they would have been reported directly to the bug bounty program's security team through the proper disclosure channel prior to being referenced in this document.*

TASK 04: Live Asset Filtering & Visual Reconnaissance

Filter dead assets and capture screenshots of live web properties for visual attack surface mapping

4.1 Objective

After building a comprehensive subdomain list in Task 01, this task focused on determining which subdomains are actively hosting live services. Probing each subdomain and capturing screenshots of responsive hosts allows the researcher to quickly identify interesting targets such as login panels, development environments, internal tools, or misconfigured services.

4.2 Tools Used

- Httpx / Httprobe — HTTP probing tools to verify live web assets
- Gowitness / Aquatone — Automated screenshot tools for bulk visual reconnaissance

4.3 Step-by-Step Process

Step 1 — HTTP Probing with Httpx

The master subdomain list generated in Task 01 was piped into httpx to verify which subdomains are actively responding to HTTP or HTTPS requests. This step filters out dead or parked domains and significantly reduces the number of targets requiring manual review.

This command performs the following actions:

- Tests both HTTP and HTTPS for each subdomain in the input list
- Outputs only hosts that return a valid HTTP response
- Records the HTTP status code and page title for each live host
- Saves results to live_urls.txt for use in the screenshot phase



Figure 4.1 — Httpx probing master subdomain list for live assets



Step 2 — Visual Screenshot Capture with Gowitness

Gowitness was executed against the filtered list of live subdomains to automatically capture screenshots of each web asset. This visual approach allows for rapid identification of high-value targets without manually visiting each URL.

```
gowitness file -f live_urls.txt --threads 10
gowitness report serve
```

Screenshots were then reviewed through the Gowitness web report interface, with particular attention paid to:

- Login and authentication panels — potential entry points for credential-based attacks
- Development or staging environments — often have reduced security controls
- Default application pages — may indicate misconfigured or forgotten services
- Internal tooling interfaces — admin panels, monitoring dashboards, CI/CD systems
- Error pages revealing technology stack or directory structure

4.4 Results Summary

Live asset filtering successfully reduced the full subdomain list to a set of actively responding hosts. Visual reconnaissance via screenshot capture provided an efficient overview of the target's external web presence, enabling prioritization of high-value assets for deeper investigation in subsequent weeks.

Weekly Reflection & Learning Outcomes

5.1 Key Learnings

- Gained hands-on proficiency with industry-standard passive reconnaissance tools including Subfinder, Amass, Assetfinder, and CRT.sh
- Understood the importance of using multiple tools in combination, as no single tool captures a complete subdomain picture
- Learned to convert and process data across multiple formats (XLSX → CSV → TXT) as part of real-world recon pipelines
- Developed practical understanding of certificate transparency logs as a source of subdomain discovery
- Practiced responsible disclosure principles throughout all research activities

5.2 Challenges Encountered

- Disk space limitations in the Kali Linux environment caused interruptions during Go-based tool installations — resolved by using pre-compiled binaries
- Some subdomain enumeration tools produced slow results on large targets
- DNSDumpster's XLSX export required additional conversion steps before being parseable in the terminal

5.3 Tools Mastered This Week

Tool	Purpose	Proficiency Gained
Subfinder	Passive subdomain enum	Proficient
Assetfinder	Passive subdomain enum	Proficient
Amass	Deep OSINT enumeration	Intermediate
CRT.sh / curl + jq	Certificate transparency	Proficient
WhatWeb	Technology fingerprinting	Proficient
Httpx	Live host probing	Intermediate
Gowitness	Visual screenshot recon	Intermediate
Google Dorking	Passive file discovery	Proficient

Sign-Off & Submission

I hereby confirm that the work documented in this report was conducted ethically, within the authorized scope of the bug bounty program, and in accordance with responsible disclosure principles. No production systems were harmed, and all sensitive findings were handled appropriately.