

Python 2.7.17 (v2.7.17:c2f86d86e6, Oct 19 2019, 20:49:36) [MSC v.1500 32 bit (Intel)] on win32

Type "help", "copyright", "credits" or "license()" for more information.

>>>

RESTART: F:\M.Sc IT Practical\M.Sc IT Practical DS\Practical 1 Cassandra\Cassandra\apache-cassandra-3.11.4\bin\cqqlsh.py

WARNING: console codepage must be set to cp65001 to support utf-8 encoding on Windows platforms.

If you experience encoding problems, change your console codepage with 'chcp 65001' before starting cqqlsh.

Connected to Test Cluster at 127.0.0.1:9042.

[cqqlsh 5.0.1 | Cassandra 3.11.4 | CQL spec 3.4.4 | Native protocol v4]

Use HELP for help.

WARNING: pyreadline dependency missing. Install to enable tab completion.

Create Key space:

```
cqqlsh> CREATE KEYSPACE college
```

```
WITH replication = {
```

```
    'class': 'SimpleStrategy',
```

```
    'replication_factor': 1
```

```
};
```

Create Table:

```
Cassandracqqlsh> USE college;
```

```
cqqlsh:college> CREATE TABLE students (
```

```
    stud_id int PRIMARY KEY,
```

```
    stud_name text,
```

```
    stud_phone varint
```

```
);
```

```
cqqlsh:college> SELECT * FROM students;
```

stud_id	stud_name	stud_phone
---------	-----------	------------

--	--	--

(0 rows)

Creating Data in a Table:

```
cqlsh:college> INSERT INTO students (stud_id, stud_name, stud_phone)
```

```
VALUES (1, 'Joey', 9876543210);
```

```
... cqlsh:college> INSERT INTO students (stud_id, stud_name, stud_phone)
```

```
VALUES (2, 'Ross', 9856321470);
```

```
... cqlsh:college> INSERT INTO students (stud_id, stud_name, stud_phone)
```

```
VALUES (3, 'Chandler', 1258963470);
```

```
... cqlsh:college> SELECT * FROM students;
```

stud_id	stud_name	stud_phone
---------	-----------	------------

--	--	--

1	Joey	9876543210
---	------	------------

2	Ross	9856321470
---	------	------------

3	Chandler	1258963470
---	----------	------------

(3 rows)

Update data in table:

```
cqlsh:college> UPDATE students
```

```
SET stud_name = 'Mike'
```

```
WHERE stud_id = 1;
```

```
cqlsh:college> SELECT * FROM students;
```

```
stud_id | stud_name | stud_phone
```

```
-----+-----+-----
```

```
1 | Mike | 9876543210
2 | Ross | 9856321470
3 | Chandler | 1258963470
```

(3 rows)

Delete data from table:

```
cqlsh:college> DELETE stud_phone
```

```
FROM students
```

```
WHERE stud_id = 2;
```

```
cqlsh:college> SELECT * FROM students;
```

```
stud_id | stud_name | stud_phone
```

```
-----+-----+-----
```

```
1 | Mike | 9876543210
2 | Ross | null
3 | Chandler | 1258963470
```

(3 rows)

Alter Table 1. Adding a column:

```
cqlsh:college> ALTER TABLE students
```

```
ADD stud_add text;
```

```
cqlsh:college> SELECT * FROM students;
```

```
stud_id | stud_add | stud_name | stud_phone
```

```
-----+-----+-----+-----
```

```
1 | null | Mike | 9876543210
```

```
2 | null | Ross | null
```

```
3 | null | Chandler | 1258963470
```

(3 rows)

2. Dropping a column:

```
cqlsh:college> ALTER TABLE students
```

```
DROP stud_add;
```

```
cqlsh:college> SELECT * FROM students;
```

```
stud_id | stud_name | stud_phone
```

```
-----+-----+-----
```

```
1 | Mike | 9876543210
```

```
2 | Ross | null
```

```
3 | Chandler | 1258963470
```

(3 rows)

Drop Table:

```
cqlsh:college> DROP TABLE students;
```

```
cqlsh:college> DESCRIBE TABLES;
```

<empty>

Drop Keyspace:

```
cqlsh:college> DROP KEYSPACE college;
```

```
cqlsh:college> DESCRIBE KEYSPACES;
```

system_schema system_auth system system_distributed system_traces

```
cqlsh:college>
```