

Note.kt

@Composable

```
fun NotesApp(viewModel: NotesViewModel = viewModel()) {
```

```
    val notes by viewModel.notes.collectAsState()
```

```
    Scaffold(
```

```
        topBar = {
```

```
            TopAppBar(
```

```
                title = { Text("My Notes") }
```

```
            )
```

```
        },
```

```
        floatingActionButton = {
```

```
            FloatingActionButton(
```

```
                onClick = { /* open dialog to add note */ }
```

```
            ) {
```

```
                Icon(
```

```
                    Icons.Default.Add,
```

```
                    contentDescription = "Add"
```

```
                )
```

```
            }
```

```
        }
```

```
    ) { padding ->
```

```
        LazyColumn(
```

```
            contentPadding = padding
```

```
        ) {
```

```
            items(notes) { note ->
```

```
Card(
    modifier = Modifier
        .fillMaxWidth()
        .padding(8.dp)
) {

    Column(
        modifier = Modifier.padding(12.dp)
    ) {

        Text(
            note.title,
            fontWeight = FontWeight.Bold
        )

        Spacer(
            modifier = Modifier.height(6.dp)
        )

        Text(
            note.body,
            maxLines = 2,
            overflow = TextOverflow.Ellipsis
        )
    }
}
}
```

```
}
```

Kotlin

```
data class Note(
```

```
    val id: Long = System.currentTimeMillis(),
```

```
    val title: String,
```

```
    val body: String
```

```
)
```

NotesViewModel.kt

Kotlin

```
class NotesViewModel : ViewModel() {
```

```
    private val _notes = MutableStateFlow<List<Note>>(emptyList())
```

```
    val notes: StateFlow<List<Note>> = _notes
```

```
    fun addNote(title: String, body: String) {
```

```
        val new = Note(title = title, body = body)
```

```
        _notes.value = listOf(new) + _notes.value
```

```
    }
```

```
}
```

MainActivity.kt (Compose part)

Kotlin

Note.kt

```
@Composable
```

```
fun NotesApp(viewModel: NotesViewModel = viewModel()) {
```

```
val notes by viewModel.notes.collectAsState()
```

Scaffold(

```
topBar = {
```

TopAppBar(

```
title = { Text("My Notes") }
```

)

 $\},$

floatingActionButton = {

FloatingActionButton()

```
onClick = { /* open dialog to add note */ }
```

$$)\{$$

Icon(

Icons.Default.Add,

```
contentDescription = "Add"
```

)

}

}

) { padding ->

LazyColumn(

```
contentPadding = padding
```

 $) \{$

```
items(notes) { note ->
```

Card(

```
modifier = Modifier
```

```
.fillMaxWidth()
```

```
.padding(8.dp)
```

$$)\{$$

Column(

```
modifier = Modifier.padding(12.dp)
```



```
val notes: StateFlow<List<Note>> = _notes  
fun addNote(title: String, body: String) {  
    val new = Note(title = title, body = body)  
    _notes.value = listOf(new) + _notes.value  
}  
}
```

MainActivity.kt (Compose part)

Kotlin