



Search tutorials and examples

[www.domain-name.com](http://www.domain-name.com)

# Python time Module

In this article, we will explore time module in detail. We will learn to use different time-related functions defined in the time module with the help of examples.

Python has a module named `time` to handle time-related tasks. To use functions defined in the module, we need to import the module first. Here's how:

```
import time
```

Here are commonly used time-related functions.

## Python `time.time()`

The `time()` function returns the number of seconds passed since epoch.

For Unix system, `January 1, 1970, 00:00:00` at **UTC** is epoch (the point where time begins).



[Get Python  
App](#)

×

[https://www.programiz.com/learn-python?utm\\_campaign=programiz-homepage&utm\\_source=programiz-website-python-app-popup](https://www.programiz.com/learn-python?utm_campaign=programiz-homepage&utm_source=programiz-website-python-app-popup)



Search tutorials and examples

[www.domain-name.com](http://www.domain-name.com)

## Python `time.ctime()`

The `time.ctime()` function takes seconds passed since epoch as an argument and returns a string representing local time.

```
import time

# seconds passed since epoch
seconds = 1545925769.9618232
local_time = time.ctime(seconds)
print("Local time:", local_time)
```

If you run the program, the output will be something like:

```
Local time: Thu Dec 27 15:49:29 2018
```



[Get Python  
App](#)

([https://www.programiz.com/learn-python?utm\\_campaign=programiz-homepage&utm\\_source=programiz-website-python-app-popup](https://www.programiz.com/learn-python?utm_campaign=programiz-homepage&utm_source=programiz-website-python-app-popup)).

given number of seconds.



Search tutorials and examples

[www.domain-name.com](http://www.domain-name.com)

To learn more, visit: [Python sleep\(\)](https://python-programming/time/sleep/) (/python-programming/time/sleep).

Before we talk about other time-related functions, let's explore `time.struct_time` class in brief.

## time.struct\_time Class

Several functions in the `time` module such as `gmtime()`, `asctime()` etc. either take `time.struct_time` object as an argument or return it.

Here's an example of `time.struct_time` object.

```
time.struct_time(tm_year=2018, tm_mon=12, tm_mday=27,  
                 tm_hour=6, tm_min=35, tm_sec=17,  
                 tm_wday=3, tm_yday=361, tm_isdst=0)
```



[Get Python  
App](#)

([https://www.programiz.com/learn-python?utm\\_campaign=programiz-homepage&utm\\_source=programiz-website-python-app-popup](https://www.programiz.com/learn-python?utm_campaign=programiz-homepage&utm_source=programiz-website-python-app-popup))



Search tutorials and examples

[www.domain-name.com](http://www.domain-name.com)

2	<code>tm_mday</code>	1, 2, ..., 31
3	<code>tm_hour</code>	0, 1, ..., 23
4	<code>tm_min</code>	0, 1, ..., 59
5	<code>tm_sec</code>	0, 1, ..., 61
6	<code>tm_wday</code>	0, 1, ..., 6; Monday is 0
7	<code>tm_yday</code>	1, 2, ..., 366
8	<code>tm_isdst</code>	0, 1 or -1

The values (elements) of the `time.struct_time` object are accessible using both indices and attributes.

### Python time.localtime()



[Get Python  
App](#)

([https://www.programiz.com/learn-python?utm\\_campaign=programiz-homepage&utm\\_source=programiz-website-python-app-popup](https://www.programiz.com/learn-python?utm_campaign=programiz-homepage&utm_source=programiz-website-python-app-popup))



Search tutorials and examples

[www.domain-name.com](http://www.domain-name.com)

```
print("tm_hour:", result.tm_hour)
```

When you run the program, the output will be something like:

```
result: time.struct_time(tm_year=2018, tm_mon=12, tm_mday=27, tm_hour=15, tm_min=15, tm_sec=0, tm_wday=3, tm_yday=360, tm_isdst=0)
year: 2018
tm_hour: 15
```

If no argument or `None` is passed to `localtime()`, the value returned by `time()` is used.

## Python `time.gmtime()`

The `gmtime()` function takes the number of seconds passed since epoch as an argument and returns `struct_time` in **UTC**.



[Get Python  
App](#)

[https://www.programiz.com/learn-python?utm\\_campaign=programiz-homepage&utm\\_source=programiz-website-python-app-popup](https://www.programiz.com/learn-python?utm_campaign=programiz-homepage&utm_source=programiz-website-python-app-popup)



Search tutorials and examples

[www.domain-name.com](http://www.domain-name.com)

```
print("tm_hour:", result.tm_hour)
```

When you run the program, the output will be:

```
result = time.struct_time(tm_year=2018, tm_mon=12, tm_mday=28, tm_hour=8, tm_min=0, tm_sec=0, tm_wday=0, tm_yday=360, tm_isdst=0)

year = 2018
tm_hour = 8
```

If no argument or `None` is passed to `gmtime()`, the value returned by `time()` is used.

## Python time.mktime()

The `mktime()` function takes `struct_time` (or a tuple containing 9 elements corresponding to `struct_time`) as an argument and returns the seconds passed since epoch in local time. Basically, it's the inverse function of `localtime()`.



[Get Python  
App](#)

[https://www.programiz.com/learn-python?utm\\_campaign=programiz-homepage&utm\\_source=programiz-website-python-app-popup](https://www.programiz.com/learn-python?utm_campaign=programiz-homepage&utm_source=programiz-website-python-app-popup)



Search tutorials and examples

[www.domain-name.com](http://www.domain-name.com)

```
print("Local time:", local_time)
```

The example below shows how `mktime()` and `localtime()` are related.

```
import time

seconds = 1545925769

# returns struct_time
t = time.localtime(seconds)
print("t1: ", t)

# returns seconds from struct_time
s = time.mktime(t)
print("\s:", seconds)
```

When you run the program, the output will be something like:

```
t1: time.struct_time(tm_year=2018, tm_mon=12, tm_mday=27, tm_hour=15, tm_min=49
```



[Get Python  
App](#)

([https://www.programiz.com/learn-python?utm\\_campaign=programiz-homepage&utm\\_source=programiz-website-python-app-popup](https://www.programiz.com/learn-python?utm_campaign=programiz-homepage&utm_source=programiz-website-python-app-popup))



Search tutorials and examples

[www.domain-name.com](http://www.domain-name.com)

```
import time

t = (2018, 12, 28, 8, 44, 4, 4, 362, 0)

result = time.asctime(t)
print("Result:", result)
```

When you run the program, the output will be:

```
Result: Fri Dec 28 08:44:04 2018
```

## Python time.strptime()

The `strptime()` function takes `struct_time` (or tuple corresponding to it) as an argument and returns a string representing it based on the format code used. For example,



[Get Python  
App](#)

([https://www.programiz.com/learn-python?utm\\_campaign=programiz-homepage&utm\\_source=programiz-website-python-app-popup](https://www.programiz.com/learn-python?utm_campaign=programiz-homepage&utm_source=programiz-website-python-app-popup))





Search tutorials and examples

[www.domain-name.com](http://www.domain-name.com)

```
print(time_string)
```

When you run the program, the output will be something like:

```
12/28/2018, 09:47:41
```

Here, `%Y`, `%m`, `%d`, `%H` etc. are format codes.

- `%Y` - year [0001,..., 2018, 2019,..., 9999]
- `%m` - month [01, 02, ..., 11, 12]
- `%d` - day [01, 02, ..., 30, 31]
- `%H` - hour [00, 01, ..., 22, 23]
- `%M` - minutes [00, 01, ..., 58, 59]
- `%S` - second [00, 01, ..., 58, 61]

To learn more, visit: [time.strftime\(\)](https://docs.python.org/3/library/time.html#time.strftime).

(<https://docs.python.org/3/library/time.html#time.strftime>).



[Get Python  
App](#)

([https://www.programiz.com/learn-python?utm\\_campaign=programiz-homepage&utm\\_source=programiz-website-python-app-popup](https://www.programiz.com/learn-python?utm_campaign=programiz-homepage&utm_source=programiz-website-python-app-popup)).



Search tutorials and examples

[www.domain-name.com](http://www.domain-name.com)

```
import time

time_string = "21 June, 2018"
result = time.strptime(time_string, "%d %B, %Y")

print(result)
```

When you run the program, the output will be:

```
time.struct_time(tm_year=2018, tm_mon=6, tm_mday=21, tm_hour=0, tm_min=0, tm_sec=0)
```

[Previous Tutorial:](#)  
[Timestamp to datetime](#)  
[\(/python-programming/datetime/timestamp-datetime\)](#)

Next Tutorial:  
[Python time.sleep\(\)](#)  
[\(/python-programming/time/sleep\)](#)



[Get Python App](#)

[https://www.programiz.com/learn-python?utm\\_campaign=programiz-homepage&utm\\_source=programiz-website-python-app-popup](https://www.programiz.com/learn-python?utm_campaign=programiz-homepage&utm_source=programiz-website-python-app-popup)



<https://www.facebook.com/sharer/sharer.php?>



<https://twitter.com/intent/tweet?>



Search tutorials and examples

[www.domain-name.com](http://www.domain-name.com)



## Related Tutorials

[Python Tutorial](#)

[Python sleep\(\)](#)

[\(/python-programming/time/sleep\)](#)

[Python Tutorial](#)

[Python Get Current time](#)

[Python Tutorial](#)

[Python datetime](#)

[\(/python-programming/datetime\)](#)

[Python Tutorial](#)

[Python strftime\(\)](#)



[Get Python  
App](#)

[https://www.programiz.com/learn-python?utm\\_campaign=programiz-homepage&utm\\_source=programiz-website-python-app-popup](https://www.programiz.com/learn-python?utm_campaign=programiz-homepage&utm_source=programiz-website-python-app-popup)

Thank you for printing our content at [www.domain-name.com](http://www.domain-name.com). Please check back soon for new contents.



Search tutorials and examples

[www.domain-name.com](http://www.domain-name.com)



[Get Python  
App](#)

[https://www.programiz.com/learn-python?utm\\_campaign=programiz-homepage&utm\\_source=programiz-website-python-app-popup](https://www.programiz.com/learn-python?utm_campaign=programiz-homepage&utm_source=programiz-website-python-app-popup)