CARL Presentation — Full Study Guide

Slide-by-slide talking points, novelty framing, and tough-panel Q&A prep

Manas Sadashiv

Contents

How to use this document **1**

Why CARL is novel — read this before the intro **1**
- The core novelty claim, one sentence . . . 1
- How CARL differs from traditional autonomous robots . . . 2
- How CARL differs from other learning-based / "autonomous" robots . . . 2
- The one-line version if you're pressed for time in Q&A . . . 2

Slide-by-slide explanations **3**
- Slide 1 — Title . . . 3
- Slide 2 — Introduction . . . 3
- Slide 3 — Objectives . . . 3
- Slides 4–7 — Literature Review . . . 3
- Slide 8 — Literature Summary . . . 4
- Slide 9 — Research Gap / Proposed Gap . . . 4
- Slides 10–11 — References . . . 4
- Slide 12 — Thank you . . . 5

Q&A bank — likely tough panel questions **5**

Final reminders **6**

How to use this document

Read the **Novelty section** first — it's the thing most likely to get probed hard and isn't fully spelled out on your slides. Then skim each slide section once. Then read the **Q&A bank** — those are the questions a tough panel is most likely to throw at a proposal like this, with answers you can say almost verbatim.

Why CARL is novel — read this before the intro

You will very likely be asked "what's actually new here?" Have this ready cold.

The core novelty claim, one sentence

CARL's novelty is integration, not invention. No single mechanism in CARL is new — LSMs, STDP, neuromodulation, hippocampal navigation, and free-energy inference all exist

independently in the literature (that's exactly what your 13 references show). What doesn't exist is a **single architecture that runs all five together, in one real-time control loop, on one embodied platform.**

How CARL differs from traditional autonomous robots

Traditional autonomous robot stacks (industrial arms, most mobile robots, even most "AI" robots you'll see in industry) are built as a **pipeline of separate modules**: a perception module (vision/SLAM) feeds a planning module, which feeds a control module, which feeds actuators. Each module is engineered and tuned independently, often by different teams, using different techniques (CV for perception, classical control theory for actuation, sometimes RL bolted on for one piece).

Problems with this: - **Brittleness at the boundaries.** If perception's output format or noise characteristics drift even slightly, planning breaks — because the modules don't share a common internal representation. - **No unified learning signal.** Each module optimizes its own local objective; there's no single principle explaining why the whole system behaves the way it does. - **No graceful degradation.** When one module fails, there's usually no fallback except hard stops or safety interlocks — the system doesn't "adapt," it halts.

How CARL differs from other learning-based / "autonomous" robots

Even robots that do use learning (RL-trained locomotion, end-to-end vision-to-action policies) typically optimize **one thing** — usually a single reward function via a single algorithm (e.g., PPO end-to-end). That's powerful but narrow: it gives you a policy, not a nervous system. It doesn't explain *why* the robot should explore vs. exploit, doesn't regulate its own internal state (energy, stress, arousal), and has no separate fast-reflex vs. slow-deliberation split.

CARL is different in three specific ways:

1. **Multiple coupled subsystems replicate different biological control loops, not one flat policy.** LSM reservoir (fast reactive dynamics) + STDP (unsupervised structural learning) + neuromodulation (global gain/mode control) + hippocampal navigation (spatial memory) + free-energy inference (unified action selection) — each does a different *kind* of computation, the way a real nervous system has spinal reflexes, limbic modulation, hippocampal memory, and cortical planning as distinct but coupled layers. Most "autonomous" robots collapse all of this into one neural network trained end-to-end on one loss.
2. **Neuromodulation gives CARL a global internal state that changes its own behavior mode** — dopamine/serotonin/norepinephrine/acetylcholine act as gain knobs that shift exploration vs. exploitation, attention, and learning rate, dynamically, based on internal and external conditions. Traditional and most learning-based robots have a fixed policy or fixed hyperparameters — they don't have anything analogous to "mood" or "arousal" that reshapes behavior in real time.
3. **A single free-energy objective, instead of one reward function per task.** Active inference gives CARL one unifying principle — minimize prediction error / surprise — that in principle covers perception, action, and exploration together, rather than requiring a hand-designed reward for every new task.

The one-line version if you're pressed for time in Q&A

> "Traditional autonomous robots are pipelines of independently-tuned modules with no shared internal state. Most learning-based robots optimize one policy against

one reward. CARL is novel because it couples five distinct biological control mechanisms — fast reservoir dynamics, unsupervised synaptic plasticity, global neuromodulatory state, spatial memory, and free-energy-based action selection — into a single closed real-time loop, so behavior emerges from the interaction of these systems rather than being the output of one trained function."

Slide-by-slide explanations

Slide 1 — Title

Nothing to defend here. Know your own registration details and department cold in case asked to repeat them.

Slide 2 — Introduction

What it says: Rigid controllers fail under real-world noise and variability; biology solves this with coupled multi-scale feedback loops; CARL is proposed to replicate this via five specific mechanisms (LSM, neuromodulation, STDP, hippocampal navigation, free-energy inference), inside MuJoCo.

Why it's structured this way: This slide exists to establish the *problem* (brittleness of traditional control) before the *solution* (CARL), which is standard proposal structure. If asked "why MuJoCo specifically," the honest answer: MuJoCo is a high-fidelity, differentiable-friendly rigid-body physics engine widely used in robotics RL research (see Makoviychuk/Isaac Gym paper reference — MuJoCo and Isaac Gym are the two dominant simulators cited in that literature), so it's a standard, credible choice for this kind of digital twin work, not a novel contribution itself.

Slide 3 — Objectives

Six objectives, each maps 1:1 onto one of the five mechanisms plus a validation objective. If asked "which objective is hardest," the honest answer is usually **integrating neuromodulation with the LSM reservoir in real time** — because unlike STDP (well-established, local, and self-contained) or free-energy inference (well-defined mathematically), coupling a global 4-factor neuromodulatory state to a reservoir's dynamics in a way that's stable and doesn't destroy the reservoir's echo-state property is the least standardized part of the literature (reflected in the Research Gap slide).

Slides 4–7 — Literature Review

Don't read the table cell-by-cell. Point at each row and say the mapping below — paper, what it did, what CARL takes from it.

Slide 4 (papers 1–4): - "Zang et al., 2024 — a hybrid MPC plus reinforcement-learning controller for unstable robots. This grounds CARL's emergency recovery controller — the fallback that engages short-horizon MPC when the learned policy alone can't stabilize the system." - "Hafner et al., 2023, DreamerV3 — learns a latent world model from experience and trains a policy purely through imagined rollouts inside that model. This grounds CARL's holographic memory and latent-imagination planning." - "Rahimi et al., 2023 — hyperdimensional computing, high-dimensional bipolar vector representations for state and memory encoding. This grounds CARL's holographic memory encoding." - "Mazzaglia et al., 2022 —

a formal derivation of an expected-free-energy objective for embodied agents. This grounds CARL's action-selection engine — minimizing expected free energy."

Slide 5 (papers 5–7): - "Schuman et al., 2022 — a review of neuromorphic computing and spiking neural network hardware. This grounds CARL's rationale for using spiking, event-based, energy-efficient computation." - "Zenke and Vogels, 2021 — homeostatic synaptic scaling that prevents runaway excitation in spiking networks. This grounds the stability of CARL's STDP plasticity — without it, synaptic weights could grow unbounded." - "Makoviychuk et al., 2021, Isaac Gym — GPU-parallelized rigid-body physics for fast, contact-rich simulation. This grounds CARL's MuJoCo digital-twin simulation substrate."

Slide 6 (papers 8–10): - "Hasani et al., 2021, Liquid Time-Constant Networks — continuous-time neurons with adaptive, input-dependent time constants. This grounds CARL's continuous motor dynamics model." - "Sterling, 2020 — allostasis, the theory that brains regulate predictively rather than just reactively. This grounds CARL's predictive drive and energy regulation." - "Whittington et al., 2020, the Tolman-Eichenbaum Machine — a shared entorhinal-hippocampal code that generalizes spatial and relational structure. This grounds CARL's hippocampal grid-cell and place-cell spatial navigation."

Slide 7 (papers 11–13): - "Howard et al., 2019, MobileNetV3 — a hardware-aware, depthwise-separable CNN architecture for fast, low-power inference. This grounds CARL's real-time edge visual perception pipeline." - "Rusu et al. and Tobin et al., 2018 — domain randomization, training control policies across randomized physics parameters so they transfer to the real world. This grounds CARL's sim-to-real transfer strategy." - "Schulman et al., 2017, PPO — a clipped surrogate objective for stable, sample-efficient policy-gradient training. This grounds CARL's motor policy training algorithm, if reinforcement learning is incorporated."

If the panel drills into any *one* paper's methodology beyond this, it's fine to say: "That's a level of detail I'd want to revisit the paper for — my read on it for this project was [the mapping above]." That's an acceptable answer for a proposal-stage minor project.

Slide 8 — Literature Summary

This slide's function is to prove **coverage**, not depth — it shows every subsystem of CARL has literature backing. If asked "is there a single paper that does what you're doing," the correct answer is **no, and that's the point** — see the Novelty section above.

Slide 9 — Research Gap / Proposed Gap

This is the slide most likely to get the toughest questions, because it's the strongest claim in the deck. Three specific gaps are named: 1. No architecture couples full connectionist deep learning with spiking simulation in one real-time loop. 2. Multi-factor neuromodulation + LSM reservoirs together is underexplored. 3. Hippocampal grid cells directly coupled to real-time physics-based motor control hasn't been directly demonstrated.

Be ready to admit: these are gaps *as best as this literature review found* — not an exhaustive systematic review. If pushed ("did you do a systematic literature search?") the honest answer: "This is a targeted review of 13 representative papers across the relevant subfields for a minor project, not an exhaustive systematic review — a full survey would be a reasonable next step."

Slides 10–11 — References

Know the two unverified ones if asked directly (see Q&A bank below).

Slide 12 — Thank you

N/A.

Q&A bank — likely tough panel questions

Q: What is your independent variable / dependent variable? What are you actually measuring? A: The independent variables are the environmental conditions the digital twin is exposed to (terrain, obstacles, task type). The dependent variables are the ones named in the objectives: adaptive behavior emergence, energy homeostasis (stability of the neuromodulatory/metabolic state), and spatial navigation accuracy. Concrete metrics (e.g., path efficiency, time-to-recovery after perturbation, synaptic weight stability) would be defined during implementation.

Q: This looks like it's scope for a PhD, not a minor project. How will you actually finish this? A: Fair — the full architecture is ambitious. The minor project scope is to implement and validate a subset first (typically: LSM + STDP + one neuromodulator loop + basic navigation) inside the MuJoCo digital twin, and treat the remaining mechanisms as the extension/future-work path. (Adjust this to whatever your actual planned scope is — be ready to say concretely what you will have working, not the full five-mechanism system, unless you actually intend to build all of it.)

Q: What's your validation metric — how do you know CARL is "working"? A: Three planned measures, matching the objectives: behavioral adaptivity (does it recover from novel perturbations without being explicitly re-trained), energy/homeostatic stability (do neuromodulator levels stay bounded rather than diverging), and navigation accuracy against ground-truth position in the simulated environment.

Q: Why not just use a standard deep RL policy — why all this biological complexity? A: A standard end-to-end RL policy optimizes one reward for one task well, but doesn't generalize its "reasoning" across tasks and typically needs retraining for each new scenario. The biologically-inspired approach aims for a system that adapts online, without full retraining, by having separate fast (reflexive), slow (deliberative), and modulatory (state-based) subsystems the way real nervous systems do — trading some initial engineering simplicity for long-run adaptability and sample efficiency.

Q: Which optimization technique are you using — why not Taguchi / Genetic Algorithm / Grey Relational Analysis? A: (Use the exact answer already worked out.) "We don't use classical DOE optimization because there's no fixed parameter set to tune offline — the system is meant to adapt continuously while running. Optimization is distributed across subsystems: STDP optimizes synaptic weights locally and gradient-free, free-energy minimization optimizes action selection, and PPO would optimize policy parameters if reinforcement learning is incorporated. At this proposal stage these are the planned mechanisms, not yet implemented results."

Q: Isn't "emergent behavior" just a way of saying you can't predict or control what your robot will do? How is that acceptable in an engineering context? A: Emergence here means behavior isn't explicitly hand-coded for every scenario, not that it's unconstrained or unsafe. The system is still bounded — neuromodulator levels, synaptic weights, and physical actuator limits are all constrained within defined ranges, and MuJoCo's digital twin lets these bounds be tested extensively in simulation before any physical deployment. Validation (Objective 6) exists specifically to characterize what the emergent behavior actually looks like before trusting it.

Q: X et al. (2024) and Y et al. (2023) in your references — can you tell me more about their methodology? *(the two unverified citations — Zang 2024 and Rahimi 2023)* A: Be straight about this if pressed hard: "I'd want to revisit those two sources directly to speak to methodology detail beyond what's summarized in the table — I don't have that at the level of the other eleven." Don't invent detail here. It's a much smaller problem to admit a gap than to be caught fabricating specifics on the spot.

Q: What's the difference between STDP and standard backpropagation-based learning? A: STDP is a local, unsupervised, gradient-free rule: synapses strengthen or weaken based only on the relative timing of pre- and post-synaptic spikes, using information available at that synapse — no global error signal or backward pass required. Backpropagation requires a global loss function and propagates error gradients backward through the whole network. STDP is biologically plausible and works online/continuously; backprop is what's used to train most conventional deep networks, including, e.g., PPO's policy network if that's incorporated.

Q: What does "free-energy minimization" actually mean in plain terms? A: The system maintains an internal generative model that predicts its sensory inputs. "Free energy" is (roughly) the gap between what the model predicts and what's actually sensed, plus a complexity penalty. Minimizing it means the system acts to make the world match its predictions (or updates its predictions to match the world) — which naturally produces both perception (updating beliefs) and action (changing the world to reduce surprise) from one objective, instead of needing separate hand-designed rules for each.

Q: Why MuJoCo instead of a real robot or another simulator (Gazebo, Isaac Sim)? A: MuJoCo is a well-validated, high-fidelity rigid-body physics engine widely used in robotics learning research (referenced directly in the Makoviychuk/Isaac Gym literature). For a minor project, simulation-first is standard practice — it allows safe, fast, repeatable testing of a system whose behavior is not fully predictable in advance, before any physical deployment is considered.

Q: How is this different from a Kalman filter / classical state estimator doing "prediction error minimization" — hasn't that existed for decades? A: Good catch, and yes — prediction-error minimization as a general principle isn't new; Kalman filtering is a classical instance of it for linear-Gaussian state estimation. What's different here is the scope: active inference applies the same prediction-error-minimization principle to *action selection* as well as state estimation, unifying perception and behavior under one objective, and it's implemented over a nonlinear, learned generative model rather than a hand-specified linear one.

Q: Realistically, what's built right now versus what's still just proposed? A: Be honest and specific to your actual status — don't let the panel catch a gap between what's implied and what's real. If nothing is implemented yet, say so plainly: "At this stage this is a design and literature-grounded proposal — the next phase is implementing and validating a first subset of this architecture in MuJoCo." Panels respect a precise honest boundary far more than a vague answer that sounds like it's covering something up.

Final reminders

- If you don't know something, say so and say what you *do* know that's adjacent — don't guess out loud.
- Every mechanism-based question can be answered by naming what it optimizes and how (see the optimization table logic from earlier prep) — that structure covers most "how does X work" questions even under pressure.

- Breathe before answering; a two-second pause before a hard question reads as thoughtful, not unprepared.