



Vidyavardhini's College of Engineering & Technology

Department of Artificial Intelligence and Data Science

Experiment No.3
To install and configure MongoDB to execute NoSQL Commands
Date of Performance:
Date of Submission:



Vidyavardhini's College of Engineering & Technology

Department of Artificial Intelligence and Data Science

AIM: To install and configure MongoDB/ Cassandra/ HBase/ Hypertable and to execute NoSQL commands.

THEORY:

MongoDB can be downloaded from <https://www.mongodb.com/try/download/community2>

Now open command prompt and run the following command

```
C:\>move mongodb-win64-* mongodb  
  
1 dir(s) moved.
```

MongoDB requires a data folder to store its files. The default location for the MongoDB data directory is c:\data\db. So create the folder using the Command Prompt. Execute the following command sequence.

```
C:\>md data  
  
C:\>md data\db
```

In case mongodb is stored in some other location, navigate to that folder.

In command prompt navigate to the bin directory present into the mongodb installation folder. Suppose the installation folder is D:\set up\mongodb

```
C:\Users\XYZ>d:  
  
D:\>cd "set up"  
  
D:\set up>cd mongodb  
  
D:\set up\mongodb>cd bin  
  
D:\set up\mongodb\bin>mongod.exe --dbpath "d:\set up\mongodb\data"
```

Now to run the mongodb, open another command prompt and issue the following command:



Vidyavardhini's College of Engineering & Technology

Department of Artificial Intelligence and Data Science

```
D:\set up\mongodb\bin>mongo.exe

MongoDB shell version: 2.4.6

connecting to: test

>db.test.save( { a: 1 } )

>db.test.find()

{ "_id" : ObjectId("5879b0f65a56a454"), "a" : 1 }

>
```

The use Command

MongoDB use DATABASE_NAME is used to create database. The command will create a new database, if it doesn't exist otherwise it will return the existing database

Syntax:

use DATABASE_NAME

The dropDatabase () Method

MongoDB db.dropDatabase () command is used to drop an existing database.

Syntax:

db.dropDatabase()

The createCollection() Method

MongoDB db.createCollection(name, options) is used to create collection.

Syntax:

db.createCollection(name, options)

Insert Document

To insert data into MongoDB collection, you need to use MongoDB's insert() or save() method

Syntax

>db.COLLECTION_NAME.insert(document)



Vidyavardhini's College of Engineering & Technology

Department of Artificial Intelligence and Data Science

Example:

```
>db.post.insert([
{
  title: 'MongoDB Overview',
  description: 'MongoDB is no sql database',
  tags: ['mongodb', 'database', 'NoSQL'],
  likes: 100
},
{
  title: 'NoSQL Database',
  description: 'NoSQL database doesn't have
tables', tags: ['mongodb', 'database', 'NoSQL'],
  likes: 20,
  comments: [
    {
      user:'user1',
      message: 'My first comment',
      dateCreated: new Date(2022,11,10,2,35),
      like: 0
    }
  ]
}]
```

Creating sample document:**Example**

Suppose a client needs a database design for his blog website. Website has the following requirements.



Vidyavardhini's College of Engineering & Technology

Department of Artificial Intelligence and Data Science

- ☐ Every post has the unique title, description and
- ☐ url. Every post can have one or more tags.
- ☐ Every post has the name of its publisher and total number of likes.
- ☐ Every Post have comments given by users along with their name, message, data-time and likes.
- ☐ On each post there can be zero or more comments.

Document:

```
{
  _id: POST_ID
  title: TITLE_OF_POST,
  description: POST_DESCRIPTION,
  by: POST_BY,
  url: URL_OF_POST,
  tags: [TAG1, TAG2, TAG3],
  likes: TOTAL_LIKES,
  comments: [
    {
      user:'COMMENT_BY',
      message: TEXT,
      dateCreated: DATE_TIME,

      like: LIKES
    },
    {
      user:'COMMENT_BY',
      message: TEXT,
      dateCreated: DATE_TIME,
      like: LIKES
    }
  ]
}
```



Vidyavardhini's College of Engineering & Technology

Department of Artificial Intelligence and Data Science

}

]

}

CONCLUSION:

Successfully installed mongodb in our system. learned some commands to execute it. such as drop database, create collection , insert document, etc