



Date: 08/10/24

① Solve - 8 puzzle problem.

Pseudocode:

class Node:

function - init - (state, parent, action, path-cost = 0):

set self.state = state

set self.parent = parent

set self.action = action

set self.path-cost = path-cost

function expand():

create children

set row, col = find-blank()

create possible-actions

if row > 0 then add 'up' to possible-actions

if row < 2 then add 'down' to possible-actions

if col > 0 then add 'left' to possible-actions

if col < 2 then add 'right' to possible-actions

for action in possible-actions:

create new-state as a copy of self.state

if action == 'up' then swap new-state[row]

[col] with new-state[row+1][col]

else if action == 'down' then swap

new-state[row][col] with new-state[row-1][col]

else if action == 'left' then swap new-state

[row][col] with new-state[row][col-1]

else if action == 'right' then swap

new-state[row][col] with new-state[row]

[col+1]

append new Node (new-state, self, action, self.path-cost+1)

to children

return children.


```

function find-blank();
from row from 0 to 2:
  for col from 0 to 2:
    if self.state[row][col] == 0 then
      return row, col

```

```

function depth-first-search(initial-state, goal-state):
  set frontier = [Node(initial-state)]

```

```

  set explored = empty set

```

```

  while frontier is not empty:

```

```

    set node = frontier.pop()

```

```

    if node.state == goal-state then

```

```

      return node

```

```

  add tuple of node.state to explored

```

```

  for child in node.expand():

```

```

    if tuple of child.state not in

```

```

      explored then append child to frontier

```

```

  return none

```

```

function print-solution(node):

```

```

  create path

```

```

  while node is not none:

```

```

    append (node.action, node.state)

```

```

    to path

```

```

    set node = node.parent

```

```

  return path

```

```

  for (action, state) in path:

```

```

    if action is not none then print

```

```

      "action:", action

```

```

      print state

```

```

      print " "

```


set initial-state = $[[1, 2, 3], [0, 4, 6], [7, 5, 8]]$

set goal-state = $[[1, 4, 3], [4, 5, 6], [7, 8, 10]]$

set solution = depth-first-search(initial-state, goal-state)

if solution is not none then

print "solution found:"

call print-solution(solution)

else

print "solution not found".

② Implement iterative deepening search algorithm.

→ function iterative-deepening-search(initial-state, goal-state, max-depth):

for depth from 0 to max-depth:

set result = depth-limited-search(initial-state, goal-state, depth)

if result is not none then

return result

return none

function depth-limited-search(node, goal-state, limit):

if node.state == goal-state then

return node

if node.depth >= limit then

return none

for each child in expand(node):

set result = depth-limited-search(child, goal-state, limit)

if result is not none then

return result

return none

set initial-state, goal-state, max-depth

set solution = iterative-deepening-search(initial-state, goal-state, max-depth)

if solution is not none then print solution

else print "no solution found".

(#). State space tree (8-puzzle problem):

