

VISVESVARAYA TECHNOLOGICAL UNIVERSITY

“JnanaSangama”, Belgaum -590014, Karnataka.



LAB REPORT On

ARTIFICIAL INTELLIGENCE

Submitted by:

MANAV TAKE (1BM21CS102)

Under the Guidance of
Sneha Bagalkot
Assistant Professor, BMSCE

**in partial fulfillment for the award of the degree of
BACHELOR OF ENGINEERING
in
COMPUTER SCIENCE AND ENGINEERING**



B.M.S. COLLEGE OF ENGINEERING
(Autonomous Institution under VTU)
BENGALURU-560019
Oct 2023-Feb 2024

B. M. S. College of Engineering,
Bull Temple Road, Bangalore 560019
(Affiliated To Visvesvaraya Technological University, Belgaum)
Department of Computer Science and Engineering



CERTIFICATE

This is to certify that the Lab work entitled “**ARTIFICIAL INTELLIGENCE**” carried out by **MANAV TAKE (1BM21CS102)**, who is bonafide student of **B. M. S. College of Engineering**. It is in partial fulfillment for the award of **Bachelor of Engineering in Computer Science and Engineering** of the Visvesvaraya Technological University, Belgaum during the year 2023-24. The Lab report has been approved as it satisfies the academic requirements in respect of Artificial Intelligence Lab - (**22CS5PCAIN**) work prescribed for the said degree.

Sneha Bagalkot
Assistant Professor
Department of CSE
BMSCE, Bengaluru

Dr. Jyothi S Nayak
Professor and Head
Department of CSE
BMSCE, Bengaluru

Table of Contents

Sl. No.	Experiment Title	Page No.
1	Tic Tac Toe	1
2	8 Puzzle Breadth First Search Algorithm	6
3	8 Puzzle Iterative Deepening Search Algorithm	8
4	8 Puzzle A* Search Algorithm	10
5	Vacuum Cleaner	14
6	Knowledge Base Entailment	17
7	Knowledge Base Resolution	18
8	Unification	21
9	FOL to CNF	25
10	Forward Reasoning	28

1. Implement Tic –Tac –Toe Game

```
tic=[]
import random
def board(tic):
    for i in range(0,9,3):
        print("+"+"-"*29+"+")
        print("|"+" "*9+"|"+" "*9+"|"+" "*9+"|")
        print("|"+" "*3,tic[0+i]," "*3+"|"+" "*3,tic[1+i]," "*3+"|"+" "*3,tic[2+i],"
"*3+"|")
        print("|"+" "*9+"|"+" "*9+"|"+" "*9+"|")
        print("+"+"-"*29+"+")
```

```
def update_comp():
    global tic,num
    for i in range(9):
        if tic[i]==i+1:
            num=i+1
            tic[num-1]='X'
            if winner(num-1)==False:
                #reverse the change
                tic[num-1]=num
            else:
                return
    for i in range(9):
        if tic[i]==i+1:
            num=i+1
            tic[num-1]='O'
            if winner(num-1)==True:
                tic[num-1]='X'
                return
            else:
                tic[num-1]=num
    num=random.randint(1,9)
    while num not in tic:
        num=random.randint(1,9)
    else:
        tic[num-1]='X'
```

```
def update_user():
    global tic,num
```

```

num=int(input("enter a number on the board :"))
while num not in tic:
    num=int(input("enter a number on the board :"))
else:
    tic[num-1]='O'

def winner(num):
    if tic[0]==tic[4] and tic[4]==tic[8] or tic[2]==tic[4] and tic[4]==tic[6]:
        return True
    if tic[num]==tic[num-3] and tic[num-3]==tic[num-6]:
        return True
    if tic[num//3*3]==tic[num//3*3+1] and tic[num//3*3+1]==tic[num//3*3+2]:
        return True
    return False

try:
    for i in range(1,10):
        tic.append(i)
    count=0
    #print(tic)
    board(tic)
    while count!=9:
        if count%2==0:
            print("computer's turn :")
            update_comp()
            board(tic)
            count+=1
        else:
            print("Your turn :")
            update_user()
            board(tic)
            count+=1
        if count>=5:
            if winner(num-1):
                print("winner is ",tic[num-1])
                break
            else:
                continue
except:
    print("\nerror\n")

```

Output:

1	2	3
4	5	6
7	8	9

computer's turn :

1	2	3
4	5	6
X	8	9

Your turn :

enter a number on the board :2

1	0	3
4	5	6
X	8	9

1	0	3
4	5	X
X	8	9

Your turn :

enter a number on the board :5

1	0	3
4	0	X
X	8	9

computer's turn :

1	0	3
4	0	X
X	X	9

Your turn :

enter a number on the board :9

1	0	3
4	0	X
X	X	0

computer's turn :

X	0	3
4	0	X
X	X	0

Your turn :

enter a number on the board :4

X	0	3
0	0	X
X	X	0

X	0	X
0	0	X
X	X	0

2. 8 Puzzle Breadth First Search Algorithm

```
def bfs(src,target):
    queue=[]
    queue.append(src)
    exp=[]
    while len(queue)>0:
        source=queue.pop(0)
        #print("queue",queue)
        exp.append(source)

        print(source[0],',',source[1],',',source[2])
        print(source[3],',',source[4],',',source[5])
        print(source[6],',',source[7],',',source[8])
        print(".....")
        if source==target:
            print("Success")
            return
        poss_moves_to_do=[]
        poss_moves_to_do=possible_moves(source,exp)
        #print("possible moves",poss_moves_to_do)
        for move in poss_moves_to_do:
            if move not in exp and move not in queue:
                #print("move",move)
                queue.append(move)

def possible_moves(state,visited_states):
    b=state.index(0)

    #direction array
    d=[]
    if b not in [0,1,2]:
        d.append('u')
    if b not in [6,7,8]:
        d.append('d')
    if b not in [0,3,6]:
        d.append('l')
    if b not in [2,5,8]:
        d.append('r')

    pos_moves_it_can=[]

    for i in d:
        pos_moves_it_can.append(gen(state,i,b))
```

```

    return [move_it_can for move_it_can in pos_moves_it_can if move_it_can not in
visited_states]

```

```

def gen(state,m,b):
    temp=state.copy()
    if m=='d':
        temp[b+3],temp[b]=temp[b],temp[b+3]
    if m=='u':
        temp[b-3],temp[b]=temp[b],temp[b-3]
    if m=='l':
        temp[b-1],temp[b]=temp[b],temp[b-1]
    if m=='r':
        temp[b+1],temp[b]=temp[b],temp[b+1]
    return temp

```

```

src=[1,2,3,4,5,6,0,7,8]
target=[1,2,3,4,5,6,7,8,0]
bfs(src,target)

```

Output:

```

1 | 2 | 3
4 | 5 | 6
0 | 7 | 8
-----
1 | 2 | 3
0 | 5 | 6
4 | 7 | 8
-----
1 | 2 | 3
4 | 5 | 6
7 | 0 | 8
-----
0 | 2 | 3
1 | 5 | 6
4 | 7 | 8
-----
1 | 2 | 3
5 | 0 | 6
4 | 7 | 8
-----
1 | 2 | 3
4 | 0 | 6
7 | 5 | 8
-----
1 | 2 | 3
4 | 5 | 6
7 | 8 | 0
-----
Success

```

3. 8 Puzzle Iterative Deepening Search Algorithm

```
def id_dfs(puzzle, goal, get_moves):
    import itertools
    #get_moves -> possible_moves
    def dfs(route, depth):
        if depth == 0:
            return
        if route[-1] == goal:
            return route
        for move in get_moves(route[-1]):
            if move not in route:
                next_route = dfs(route + [move], depth - 1)
                if next_route:
                    return next_route

    for depth in itertools.count():
        route = dfs([puzzle], depth)
        if route:
            return route

def possible_moves(state):
    b = state.index(0) # ) indicates White space -> so b has index of it.
    d = [] # direction

    if b not in [0, 1, 2]:
        d.append('u')
    if b not in [6, 7, 8]:
        d.append('d')
    if b not in [0, 3, 6]:
        d.append('l')
    if b not in [2, 5, 8]:
        d.append('r')

    pos_moves = []
    for i in d:
        pos_moves.append(generate(state, i, b))
    return pos_moves

def generate(state, m, b):
    temp = state.copy()
```

```

if m == 'd':
    temp[b + 3], temp[b] = temp[b], temp[b + 3]
if m == 'u':
    temp[b - 3], temp[b] = temp[b], temp[b - 3]
if m == 'l':
    temp[b - 1], temp[b] = temp[b], temp[b - 1]
if m == 'r':
    temp[b + 1], temp[b] = temp[b], temp[b + 1]

return temp

```

calling ID-DFS

```
initial = [1, 2, 3, 0, 4, 6, 7, 5, 8]
```

```
goal = [1, 2, 3, 4, 5, 6, 7, 8, 0]
```

```
route = id_dfs(initial, goal, possible_moves)
```

```
if route:
```

```
    print("Success!! It is possible to solve 8 Puzzle problem")
```

```
    print("Path:", route)
```

```
else:
```

```
    print("Failed to find a solution")
```

Output:

```
Success!! It is possible to solve 8 Puzzle problem
```

```
Path: [[1, 2, 3, 0, 4, 6, 7, 5, 8], [1, 2, 3, 4, 0, 6, 7, 5, 8], [1, 2, 3, 4, 5, 6, 7, 0, 8], [1, 2, 3, 4, 5, 6, 7, 8, 0]]
```

4. 8 Puzzle A* search algorithm

```

class Node:
    def __init__(self,data,level,fval):
        """ Initialize the node with the data, level of the node and the calculated fvalue """
        self.data = data
        self.level = level
        self.fval = fval

    def generate_child(self):
        """ Generate child nodes from the given node by moving the blank space
            either in the four directions {up,down,left,right} """
        x,y = self.find(self.data,'_')
        """ val_list contains position values for moving the blank space in either of
            the 4 directions [up,down,left,right] respectively. """
        val_list = [[x,y-1],[x,y+1],[x-1,y],[x+1,y]]
        children = []
        for i in val_list:
            child = self.shuffle(self.data,x,y,i[0],i[1])
            if child is not None:
                child_node = Node(child,self.level+1,0)
                children.append(child_node)
        return children

    def shuffle(self,puz,x1,y1,x2,y2):
        """ Move the blank space in the given direction and if the position value are out
            of limits the return None """
        if x2 >= 0 and x2 < len(self.data) and y2 >= 0 and y2 < len(self.data):
            temp_puz = []
            temp_puz = self.copy(puz)
            temp = temp_puz[x2][y2]
            temp_puz[x2][y2] = temp_puz[x1][y1]
            temp_puz[x1][y1] = temp
            return temp_puz
        else:
            return None

    def copy(self,root):
        """ Copy function to create a similar matrix of the given node"""
        temp = []
        for i in root:
            t = []
            for j in i:

```

```

        t.append(j)
        temp.append(t)
    return temp

def find(self,puz,x):
    """ Specifically used to find the position of the blank space """
    for i in range(0,len(self.data)):
        for j in range(0,len(self.data)):
            if puz[i][j] == x:
                return i,j

class Puzzle:
    def __init__(self,size):
        """ Initialize the puzzle size by the specified size,open and closed lists to empty """
        self.n = size
        self.open = []
        self.closed = []

    def accept(self):
        """ Accepts the puzzle from the user """
        puz = []
        for i in range(0,self.n):
            temp = input().split(" ")
            puz.append(temp)
        return puz

    def f(self,start,goal):
        """ Heuristic Function to calculate hueristic value  $f(x) = h(x) + g(x)$  """
        return self.h(start.data,goal)+start.level

    def h(self,start,goal):
        """ Calculates the different between the given puzzles """
        temp = 0
        for i in range(0,self.n):
            for j in range(0,self.n):
                if start[i][j] != goal[i][j] and start[i][j] != '_':
                    temp += 1
        return temp

    def process(self):
        """ Accept Start and Goal Puzzle state"""

```

```

print("Enter the start state matrix \n")
start = self.accept()
print("Enter the goal state matrix \n")
goal = self.accept()

start = Node(start,0,0)
start.fval = self.f(start,goal)
""" Put the start node in the open list"""
self.open.append(start)
print("\n\n")
while True:
    cur = self.open[0]
    print("")
    print(" | ")
    print(" | ")
    print(" \\/ \n")
    for i in cur.data:
        for j in i:
            print(j,end=" ")
        print("")
    """ If the difference between current and goal node is 0 we have reached the
goal node"""
    if(self.h(cur.data,goal) == 0):
        break
    for i in cur.generate_child():
        i.fval = self.f(i,goal)
        self.open.append(i)
    self.closed.append(cur)
    del self.open[0]

    """ sort the opne list based on f value """
    self.open.sort(key = lambda x:x.fval,reverse=False)

puz = Puzzle(3)
puz.process()

```

Output:

```
Enter the start state matrix
```

```
1 2 3
```

```
4 5 6
```

```
_ 7 8
```

```
Enter the goal state matrix
```

```
1 2 3
```

```
4 5 6
```

```
7 8 _
```

```
  |  
  |  
\'/
```

```
1 2 3
```

```
4 5 6
```

```
_ 7 8
```

```
  |  
  |  
\'/
```

```
1 2 3
```

```
4 5 6
```

```
7 _ 8
```

```
  |  
  |  
\'/
```

```
1 2 3
```

```
4 5 6
```

```
7 8 _
```


5. Vacuum Cleaner

```
def vacuum_world():
    # 0 indicates Clean and 1 indicates Dirty
    goal_state = {'A': '0', 'B': '0'}
    cost = 0

    location_input = input("Enter Location of Vacuum")
    status_input = input("Enter status of " + location_input)
    status_input_complement = input("Enter status of other room")

    if location_input == 'A':
        # Location A is Dirty.
        print("Vacuum is placed in Location A")
        if status_input == '1':
            print("Location A is Dirty.")
            # suck the dirt and mark it as clean
            cost += 1          #cost for suck
            print("Cost for CLEANING A " + str(cost))
            print("Location A has been Cleaned.")

        if status_input_complement == '1':
            # if B is Dirty
            print("Location    B    is    Dirty.")
            print("Moving right to the Location B. ")
            cost += 1          #cost for moving right
            print("COST for moving RIGHT" + str(cost))
            # suck the dirt and mark it as clean
            cost += 1          #cost for suck
            print("COST for SUCK " + str(cost))
            print("Location B has been Cleaned. ")
        else:
            print("No action" + str(cost))
            # suck and mark clean
            print("Location B is already clean.")

    if status_input == '0':
        print("Location A is already clean ")
        if status_input_complement == '1': # if B is Dirty
            print("Location B is Dirty.")
            print("Moving RIGHT to the Location B. ")
            cost += 1          #cost for moving right
            print("COST for moving RIGHT " + str(cost))
            # suck the dirt and mark it as clean
```

```

        cost += 1                #cost for suck
        print("Cost for SUCK" + str(cost))
        print("Location B has been Cleaned. ")
    else:
        print("No action " + str(cost))
        print(cost)
        # suck and mark clean
        print("Location B is already clean.")

else:
    print("Vacuum is placed in location B")
    # Location B is Dirty.
    if status_input == '1':
        print("Location B is Dirty.")
        # suck the dirt and mark it as clean
        cost += 1 # cost for suck
        print("COST for CLEANING " + str(cost))
        print("Location B has been Cleaned.")

    if status_input_complement == '1':
        # if A is Dirty
        print("Location A is Dirty.")
        print("Moving LEFT to the Location A. ")
        cost += 1 # cost for moving right
        print("COST for moving LEFT" + str(cost))
        # suck the dirt and mark it as clean
        cost += 1 # cost for suck
        print("COST for SUCK " + str(cost))
        print("Location A has been Cleaned.")

else:
    print(cost)
    # suck and mark clean
    print("Location B is already clean.")

    if status_input_complement == '1': # if A is Dirty
        print("Location A is Dirty.")
        print("Moving LEFT to the Location A. ")
        cost += 1 # cost for moving right
        print("COST for moving LEFT " + str(cost))
        # suck the dirt and mark it as clean
        cost += 1 # cost for suck
        print("Cost for SUCK " + str(cost))
        print("Location A has been Cleaned. ")

```

```

else:
    print("No action " + str(cost))
    # suck and mark clean
    print("Location A is already clean.")

# done cleaning
print("GOAL STATE: ")
print(goal_state)
print("Performance Measurement: " + str(cost))

print("0 indicates clean and 1 indicates dirty")
vacuum_world()

```

Output:

```

0 indicates clean and 1 indicates dirty
Enter Location of Vacuum b
Enter status of b 1
Enter status of other room 1
Vacuum is placed in location B
Location B is Dirty.
COST for CLEANING 1
Location B has been Cleaned.
Location A is Dirty.
Moving LEFT to the Location A.
COST for moving LEFT 2
COST for SUCK 3
Location A has been Cleaned.
GOAL STATE:
{'A': '0', 'B': '0'}
Performance Measurement: 3

```

6. Create a knowledge base using propositional logic and show that the given query entails the knowledge base or not .

from sympy import symbols, And, Not, Implies, satisfiable

```
def create_knowledge_base():
```

```
    # Define propositional symbols
```

```
    p = symbols('p')
```

```
    q = symbols('q')
```

```
    r = symbols('r')
```

```
    # Define knowledge base using logical statements
```

```
    knowledge_base = And(
```

```
        Implies(p, q),    # If p then q
```

```
        Implies(q, r),    # If q then r
```

```
        Not(r)            # Not r
```

```
    )
```

```
    return knowledge_base
```

```
def query_entails(knowledge_base, query):
```

```
    # Check if the knowledge base entails the query
```

```
    entailment = satisfiable(And(knowledge_base, Not(query)))
```

```
    # If there is no satisfying assignment, then the query is entailed
```

```
    return not entailment
```

```
if __name__ == "__main__":
```

```
    # Create the knowledge base
```

```
    kb = create_knowledge_base()
```

```
    # Define a query
```

```
    query = symbols('p')
```

```
    # Check if the query entails the knowledge base
```

```
    result = query_entails(kb, query)
```

```
    # Display the results
```

```
    print("Knowledge Base:", kb)
```

```
    print("Query:", query)
```

```
    print("Query entails Knowledge Base:", result)
```

Output:

```
Knowledge Base: ~r & (Implies(p, q)) & (Implies(q, r))
```

```
Query: p
```

```
Query entails Knowledge Base: False
```

7. Create a knowledge base using propositional logic and prove the given query using resolution

```
import re

def main(rules, goal):
    rules = rules.split(' ')
    steps = resolve(rules, goal)
    print('\nStep\t|Clause\t|Derivation\t')
    print('-' * 30)
    i = 1
    for step in steps:
        print(f' {i}.\t| {step}\t| {steps[step]}\t')
        i += 1
def negate(term):
    return f'~{term}' if term[0] != '~' else term[1]

def reverse(clause):
    if len(clause) > 2:
        t = split_terms(clause)
        return f'{t[1]}v{t[0]}'
    return ""
def split_terms(rule):
    exp = '(~*[PQRS])'
    terms = re.findall(exp, rule)
    return terms

split_terms('~PvR')

def contradiction(goal, clause):
    contradictions = [ f'{goal}v{negate(goal)}', f'{negate(goal)}v{goal}']
    return clause in contradictions or reverse(clause) in contradictions

def resolve(rules, goal):
    temp = rules.copy()
    temp += [negate(goal)]
    steps = dict()
    for rule in temp:
        steps[rule] = 'Given.'
    steps[negate(goal)] = 'Negated conclusion.'
    i = 0
    while i < len(temp):
        n = len(temp)
        j = (i + 1) % n
```

```

clauses = []
while j != i:
    terms1 = split_terms(temp[i])
    terms2 = split_terms(temp[j])
    for c in terms1:
        if negate(c) in terms2:
            t1 = [t for t in terms1 if t != c]
            t2 = [t for t in terms2 if t != negate(c)]
            gen = t1 + t2
            if len(gen) == 2:
                if gen[0] != negate(gen[1]):
                    clauses += [f'{gen[0]}v{gen[1]}']
                else:
                    if contradiction(goal,f'{gen[0]}v{gen[1]}'):
                        temp.append(f'{gen[0]}v{gen[1]}')
                        steps[""] = f'Resolved {temp[i]} and {temp[j]} to {temp[-1]},
which is in turn null. \
                        \nA contradiction is found when {negate(goal)} is assumed as
true. Hence, {goal} is true."
                    return steps
            elif len(gen) == 1:
                clauses += [f'{gen[0]}']
            else:
                if contradiction(goal,f'{terms1[0]}v{terms2[0]}'):
                    temp.append(f'{terms1[0]}v{terms2[0]}')
                    steps[""] = f'Resolved {temp[i]} and {temp[j]} to {temp[-1]}, which
is in turn null. \
                    \nA contradiction is found when {negate(goal)} is assumed as true.
Hence, {goal} is true."
                return steps
    for clause in clauses:
        if clause not in temp and clause != reverse(clause) and reverse(clause) not in
temp:
            temp.append(clause)
            steps[clause] = f'Resolved from {temp[i]} and {temp[j]}.'
    j = (j + 1) % n
    i += 1
return steps

```

Output:

```

rules = 'PvQ PvR ~PvR RvS Rv~Q ~Sv~Q' # (P=>Q)=>Q, (P=>P)=>R, (R=>S)=>~(S=>Q)
main(rules, 'R')

```

Step	Clause	Derivation

1.	PvQ	Given.
2.	PvR	Given.
3.	~PvR	Given.
4.	RvS	Given.
5.	Rv~Q	Given.
6.	~Sv~Q	Given.
7.	~R	Negated conclusion.
8.	QvR	Resolved from PvQ and ~PvR.
9.	Pv~S	Resolved from PvQ and ~Sv~Q.
10.	P	Resolved from PvR and ~R.
11.	~P	Resolved from ~PvR and ~R.
12.	Rv~S	Resolved from ~PvR and Pv~S.
13.	R	Resolved from ~PvR and P.
14.	S	Resolved from RvS and ~R.
15.	~Q	Resolved from Rv~Q and ~R.
16.	Q	Resolved from ~R and QvR.
17.	~S	Resolved from ~R and Rv~S.
18.		Resolved ~R and R to ~RvR, which is in turn null.

A contradiction is found when ~R is assumed as true. Hence, R is true.

8. Implement unification in first order logic

```
import re

def getAttributes(expression):
    expression = expression.split("(")[1:]
    expression = ").".join(expression)
    expression = expression[:-1]
    expression = re.split("(?<!(.),(?!\\.))", expression)
    return expression

def getInitialPredicate(expression):
    return expression.split("(")[0]

def isConstant(char):
    return char.isupper() and len(char) == 1

def isVariable(char):
    return char.islower() and len(char) == 1

def replaceAttributes(exp, old, new):
    attributes = getAttributes(exp)
    for index, val in enumerate(attributes):
        if val == old:
            attributes[index] = new
    predicate = getInitialPredicate(exp)
    return predicate + "(" + ",".join(attributes) + ")"

def apply(exp, substitutions):
    for substitution in substitutions:
        new, old = substitution
        exp = replaceAttributes(exp, old, new)
    return exp

def checkOccurs(var, exp):
    if exp.find(var) == -1:
        return False
    return True

def getFirstPart(expression):
    attributes = getAttributes(expression)
    return attributes[0]

def getRemainingPart(expression):
    predicate = getInitialPredicate(expression)
```



```

attributes = getAttributes(expression)
newExpression = predicate + "(" + ",".join(attributes[1:]) + ")"
return newExpression
def unify(exp1, exp2):
    if exp1 == exp2:
        return []

    if isConstant(exp1) and isConstant(exp2):
        if exp1 != exp2:
            return False

    if isConstant(exp1):
        return [(exp1, exp2)]

    if isConstant(exp2):
        return [(exp2, exp1)]

    if isVariable(exp1):
        if checkOccurs(exp1, exp2):
            return False
        else:
            return [(exp2, exp1)]

    if isVariable(exp2):
        if checkOccurs(exp2, exp1):
            return False
        else:
            return [(exp1, exp2)]

    if getInitialPredicate(exp1) != getInitialPredicate(exp2):
        print("Predicates do not match. Cannot be unified")
        return False

    attributeCount1 = len(getAttributes(exp1))
    attributeCount2 = len(getAttributes(exp2))
    if attributeCount1 != attributeCount2:
        return False

    head1 = getFirstPart(exp1)
    head2 = getFirstPart(exp2)
    initialSubstitution = unify(head1, head2)
    if not initialSubstitution:
        return False
    if attributeCount1 == 1:

```

```

    return initialSubstitution

tail1 = getRemainingPart(exp1)
tail2 = getRemainingPart(exp2)

if initialSubstitution != []:
    tail1 = apply(tail1, initialSubstitution)
    tail2 = apply(tail2, initialSubstitution)

remainingSubstitution = unify(tail1, tail2)
if not remainingSubstitution:
    return False

initialSubstitution.extend(remainingSubstitution)
return initialSubstitution

```

Output:

```

[9] exp1 = "knows(x)"
    exp2 = "knows(Richard)"
    substitutions = unify(exp1, exp2)
    print("Substitutions:")
    print(substitutions)

```

```

Substitutions:
[('Richard', 'x')]

```

```

[7] exp1 = "knows(A,x)"
    exp2 = "k(y,mother(y))"
    substitutions = unify(exp1, exp2)
    print("Substitutions:")
    print(substitutions)

```

```

Predicates do not match. Cannot be unified
Substitutions:
False

```

```
exp1 = "knows(A,x)"
exp2 = "knows(y,mother(y))"
substitutions = unify(exp1, exp2)
print("Substitutions:")
print(substitutions)
```

Substitutions:
[('A', 'y'), ('mother(y)', 'x')]

```
exp1 = "knows(A,x)"
exp2 = "knows(y)"
substitutions = unify(exp1, exp2)
print("Substitutions:")
print(substitutions)
```

Substitutions:
False

9. Convert a given first order logic statement into Conjunctive Normal Form (CNF).

```
def getAttributes(string):
    expr = '\([^)]+\)'
    matches = re.findall(expr, string)
    return [m for m in str(matches) if m.isalpha()]

def getPredicates(string):
    expr = '[a-z~]+\([A-Za-z,]+\)'
    return re.findall(expr, string)

def DeMorgan(sentence):
    string = ".join(list(sentence).copy())
    string = string.replace('~','')
    flag = '[' in string
    string = string.replace('~','')
    string = string.strip('[')
    for predicate in getPredicates(string):
        string = string.replace(predicate, f'~{predicate}')
    s = list(string)
    for i, c in enumerate(string):
        if c == '|':
            s[i] = '&'
        elif c == '&':
            s[i] = '|'
    string = ".join(s)
    string = string.replace('~','')
    return f'[{string}]' if flag else string

def Skolemization(sentence):
    SKOLEM_CONSTANTS = [f'{chr(c)}' for c in range(ord('A'), ord('Z')+1)]
    statement = ".join(list(sentence).copy())
    matches = re.findall('[\forall\exists].', statement)
    for match in matches[::-1]:
        statement = statement.replace(match, "")
        statements = re.findall("\[[^\]]+\]", statement)
        for s in statements:
            statement = statement.replace(s, s[1:-1])
        for predicate in getPredicates(statement):
            attributes = getAttributes(predicate)
            if ".join(attributes).islower():
                statement = statement.replace(match[1],SKOLEM_CONSTANTS.pop(0))
            else:
                aL = [a for a in attributes if a.islower()]
```

```

        aU = [a for a in attributes if not a.islower()][0]
        statement = statement.replace(aU,
f'{SKOLEM_CONSTANTS.pop(0)}'({aL[0] if len(aL) else match[1]}))
        return statement
import re

def fol_to_cnf(fol):

    statement = fol.replace("<=>", "_")
    while '_' in statement:
        i = statement.index('_')
        new_statement = '[' + statement[:i] + '=>' + statement[i+1:] + ']&[' +
statement[i+1:] + '=>' + statement[:i] + ']'
        statement = new_statement
    statement = statement.replace("=>", "-")
    expr = '\([^\)]+\)'
    statements = re.findall(expr, statement)
    for i, s in enumerate(statements):
        if '[' in s and ']' not in s:
            statements[i] += ']'
    for s in statements:
        statement = statement.replace(s, fol_to_cnf(s))
    while '-' in statement:
        i = statement.index('-')
        br = statement.index('[') if '[' in statement else 0
        new_statement = '~' + statement[br:i] + '|' + statement[i+1:]
        statement = statement[:br] + new_statement if br > 0 else new_statement
    while '~∀' in statement:
        i = statement.index('~∀')
        statement = list(statement)
        statement[i], statement[i+1], statement[i+2] = '∃', statement[i+2], '~'
        statement = ''.join(statement)
    while '~∃' in statement:
        i = statement.index('~∃')
        s = list(statement)
        s[i], s[i+1], s[i+2] = '∀', s[i+2], '~'
        statement = ''.join(s)
    statement = statement.replace('~[∀','[~∀')
    statement = statement.replace('~[∃','[~∃')
    expr = '(~[∀|∃].)'
    statements = re.findall(expr, statement)
    for s in statements:
        statement = statement.replace(s, fol_to_cnf(s))

```

```

expr = '~\[[^\]]+\]'
statements = re.findall(expr, statement)
for s in statements:
    statement = statement.replace(s, DeMorgan(s))
return statement

```

Output:

```

print(Skolemization(fol_to_cnf("animal(y)<=>loves(x,y)")))
print(Skolemization(fol_to_cnf("∀x[∀y[animal(y)=>loves(x,y)]]=>[∃z[loves(z,x)]]")))
print(fol_to_cnf("[american(x)&weapon(y)&sells(x,y,z)&hostile(z)]=>criminal(x)"))

```

```

[~animal(y)|loves(x,y)]&[~loves(x,y)|animal(y)]
[animal(G(x))&~loves(x,G(x))]|[loves(F(x),x)]
[~american(x)|~weapon(y)|~sells(x,y,z)|~hostile(z)]|criminal(x)

```

10. Create a knowledge base consisting of first order logic statements and prove the given query using forward reasoning.

```
import re

def isVariable(x):
    return len(x) == 1 and x.islower() and x.isalpha()

def getAttributes(string):
    expr = '\([^)]+\)'
    matches = re.findall(expr, string)
    return matches

def getPredicates(string):
    expr = '([a-z~+])\([^&|]+\)'
    return re.findall(expr, string)

class Fact:
    def __init__(self, expression):
        self.expression = expression
        predicate, params = self.splitExpression(expression)
        self.predicate = predicate
        self.params = params
        self.result = any(self.getConstants())

    def splitExpression(self, expression):
        predicate = getPredicates(expression)[0]
        params = getAttributes(expression)[0].strip('(').split(',')
        return [predicate, params]

    def getResult(self):
        return self.result

    def getConstants(self):
        return [None if isVariable(c) else c for c in self.params]

    def getVariables(self):
        return [v if isVariable(v) else None for v in self.params]

    def substitute(self, constants):
        c = constants.copy()
        f = f"{self.predicate}({'.'.join([constants.pop(0) if isVariable(p) else p for p in self.params])})"
        return Fact(f)
```

```

class Implication:
    def __init__(self, expression):
        self.expression = expression
        l = expression.split('=>')
        self.lhs = [Fact(f) for f in l[0].split('&')]
        self.rhs = Fact(l[1])

    def evaluate(self, facts):
        constants = { }
        new_lhs = []
        for fact in facts:
            for val in self.lhs:
                if val.predicate == fact.predicate:
                    for i, v in enumerate(val.getVariables()):
                        if v:
                            constants[v] = fact.getConstants()[i]
            new_lhs.append(fact)
        predicate, attributes = getPredicates(self.rhs.expression)[0],
str(getAttributes(self.rhs.expression)[0])
        for key in constants:
            if constants[key]:
                attributes = attributes.replace(key, constants[key])
        expr = f'{predicate} {attributes}'
        return Fact(expr) if len(new_lhs) and all([f.getResult() for f in new_lhs]) else
None

```

```

class KB:
    def __init__(self):
        self.facts = set()
        self.implications = set()

    def tell(self, e):
        if '=>' in e:
            self.implications.add(Implication(e))
        else:
            self.facts.add(Fact(e))
        for i in self.implications:
            res = i.evaluate(self.facts)
            if res:
                self.facts.add(res)

    def query(self, e):
        facts = set([f.expression for f in self.facts])
        i = 1

```



```

print(f'Querying {e}:')
for f in facts:
    if Fact(f).predicate == Fact(e).predicate:
        print(f'\t{i}. {f}')
        i += 1

def display(self):
    print("All facts: ")
    for i, f in enumerate(set([f.expression for f in self.facts])):
        print(f'\t{i+1}. {f}')

```

Output:

```

kb = KB()
kb.tell('missile(x)=>weapon(x)')
kb.tell('missile(M1)')
kb.tell('enemy(x,America)=>hostile(x)')
kb.tell('american(West)')
kb.tell('enemy(Nono,America)')
kb.tell('owns(Nono,M1)')
kb.tell('missile(x)&owns(Nono,x)=>sells(West,x,Nono)')
kb.tell('american(x)&weapon(y)&sells(x,y,z)&hostile(z)=>criminal(x)')
kb.query('criminal(x)')
kb.display()

```

```

Querying criminal(x):
  1. criminal(West)
All facts:
  1. enemy(Nono,America)
  2. hostile(Nono)
  3. sells(West,M1,Nono)
  4. criminal(West)
  5. owns(Nono,M1)
  6. weapon(M1)
  7. american(West)
  8. missile(M1)

```

```

kb_ = KB()
kb_.tell('king(x)&greedy(x)=>evil(x)')
kb_.tell('king(John)')
kb_.tell('greedy(John)')
kb_.tell('king(Richard)')
kb_.query('evil(x)')

```

```

Querying evil(x):
  1. evil(John)

```