

Inferring the perturbation time from biological time course data –DEtime package

Jing Yang

09/03/2015

Abstract

Time course data is often used to study the dynamics in a biological process after perturbation at certain time. Inferring the perturbation time under different scenarios in a biological process allows us to identify these critical moments and focus on any following activities in the process, which is of critical importance in understanding likely causal relationships. In DEtime package, we propose a Bayesian method to infer the perturbation time from a control and perturbed system. A non-parametric Gaussian Process regression is applied in deriving the posterior distribution of the perturbation point. This vignette explains how to use the package. For further exposition of the algorithm, please refer to our paper (Jing Yang and Rattray)

Description

This package implements the Gaussian regression framework for perturbation time point inference in a two sample case. The package contains one main function: **DEtime**.

The package works on the time course data from a wild-type and a perturbed system. Acting upon pre-defined testing perturbation time, the package goes over these perturbation time candidates and derives their likelihoods. From Bayes' theory, under a uniform prior assumption, the posterior distribution of the tested perturbation time is derived from their corresponding likelihoods. *Maximum a posterior (MAP)*, *mean* or *median* of the posterior distribution can be taken as the solution to the estimated perturbation time point.

Details

Package: DEtime
Type: Package
Version: 1.0
Date: 2015-03-09
License: GPL-3

Author(s)

Jing Yang

Maintainer

Jing Yang yynjing@gmail.com

Functionss

DEtime - Perturbation time inference

Description

DEtime is the main function in DEtime Package, which applies a mixedGP kernel to time course data under control and perturbed conditions. It returns the posterior distribution of these predefined perturbation time candidates and relevant statistical estimations of the inferred perturbation time point.

Usage

DEtime(times, ControlData, PerturbedData, replicate_no, gene_no, times_test=times, gene_ID=NULL)

Arguments

- **times**: experimental time points at which the control and perturbed time course data are measured;
- **times_list**: perturbation time points which will be evaluated by **DEtime** function. **times_list** has to be in the range of times and evenly spaced. If this data is missing, **times** will be used as **times_list** ;
- **gene_no**: the number of genes studied in this algorithm.
- **replicate_no**: the replicate number provided in experiments.
- **ControlData**: The measured time course data under control condtion. The data is a matrix where each row represents the time course data for one particular gene.
- **PerturbedData**: The measured time course data under perturbed condtion. The data is a matrix where each row represents the time course data for one particular gene. The columns for both **ControlData** and **PerturbedData** are ordered by the time sequencing followed by replicates, as shown in the Table below (the geneIDs are used for illustration purpose only, they are not included in the mearument data):

geneIDs	replicate 1	replicate 2
gene 1	$t_1 \ t_2 \ \dots \ t_n$	$t_1 \ t_2 \ \dots \ t_n$
gene 2	$t_1 \ t_2 \ \dots \ t_n$	$t_1 \ t_2 \ \dots \ t_n$

- **gene_ID**: The ID of each gene investigated in the algorithm. If this value is missing, 1, 2, 3, ... will be used instead.

Returns

The function will return a **DEtimeOutput** object which contains:

- **\$result**: statistical estimations for the inferred perturbation time, which includes:
 - **\$MAP**: *maximum a posterior* solution to the inferred perturbation time
 - **\$mean**: mean of the posterior distribution of the inferred perturbation time
 - **\$median**: median of the posterior distribution of the inferred perturbation time
 - **\$ptl5**: 5 percentile of the posterior distribution of the inferred perturbation time
 - **\$ptl95**: 95 percentile of the posterior distribution of the inferred perturbation time
- **\$posterior**: posterior distribution of the tested perturbation time points

- **\$model**: optimized GP model which will be used for later GP regression work
- **\$best_param** : optimized hyperparameter for the optimized GP model
- **\$originaltimes**: original experimental time points which will be used for future print or plot functions
- **\$originaldata**: original measured time course data which will be used for future print or plot functions
- **\$times_test**: tested perturbation time points
- **\$gene_ID**: the ID of genes for the data

Details

Both control and perturbed data have to be measured at the same time points with the same number of replicates. Replicates are required to be obtained across all time points.

Examples

```
## read simulated example data
library("DEtime")
data(SimulatedData)
res <- DEtime(times = times, ControlData = ControlData, PerturbedData=PerturbedData,
              replicate_no=replicate_no, gene_no=gene_no, times_test=times,
              gene_ID=gene_ID)
```

print_DEtime - print the results from DEtime function

Description

The function prints the results returned from **DEtime** function, which will show the **gene_ID** associated with **MAP**, **mean**, **median**, **ptl5** (lower 5 percentile) and **ptl95** (upper 5 percentile) of the posterior distribution of inferred perturbation time points.

Usage

```
print_DEtime(DEtimeOutput)
```

Argument

- **DEtimeOutput**: the returned value from **DEtime** function

Example

```
library("DEtime")
## read simulated example data
data(SimulatedData)
res <- DEtime(times = times, ControlData = ControlData, PerturbedData=PerturbedData,
              replicate_no=replicate_no, gene_no=gene_no, times_test=times,
              gene_ID=gene_ID)
print_DEtime(res)
```

```
## Perturbation point inference results from DEtime package:
```

```
## =====
##   gene_ID  MAP  mean median pt15 pt195
## 1   gene1 4.00 3.929   4.00 3.00  5.00
## 2   gene2 4.00 2.762   3.00 0.00  5.00
## 3   gene3 5.00 4.726   5.00 2.00  6.00
## =====
```

plot_DEtime - plot the results of DEtime function

Description

plot_DEtime plots the results returned from **DEtime** function. The produced figures show the the posterior distribution of inferred perturbation time points on the upper panel and Gaussian Regression of the original data on the lower panel. Please note that the MAP solution of the perturbation point is taken as the optimized estimate to the perturbation point and Gaussian Regression is derived based upon this estimated perturbation point.

Usage


```
plot_DEtime(DEtimeOutput, plot_gene_ID=NULL)
```

Argument

- **DEtimeOutput**: the returned value from **DEtime** function
- **plot_gene_ID**: the gene_IDs of those genes whose GP regression and posterior distribution of the perturbation time points will be plotted. If not supplied, all the genes will be plotted.

Example

```
library("DEtime")
## read simulated example data
data(SimulatedData)
res <- DEtime(times = times, ControlData = ControlData, PerturbedData=PerturbedData,
              replicate_no=replicate_no, gene_no=gene_no, times_test=times_test,
              gene_ID=gene_ID)
plot_DEtime(res,plot_gene_ID='gene1')
```



Running the package on the real data used in our paper

Descriptions

In this experiment, the aim is to study the transcriptional change occurring in Arabidopsis following inoculation with *P. syringae* pv. tomato DC3000 (PtoDC3000) versus the disarmed strain Pto DC3000hrpA

The data contain three different time series:

- a control time series comprising challenge with 10 mM MgCl₂ (control condition)
- infection of Arabidopsis with virulent *Pseudomonas syringae* pv. tomato DC3000, which leads to disease development (perturbed condition 1);
- infection of Arabidopsis with the disarmed strain DC3000hrpA (perturbed condition 2)

In this example, the perturbation time between perturbed condition 1 and perturbed condition 2 is inferred.

```
library("DEtime")
## Original experimental time points
times <- matrix(c(0,2,3,4,6,7,8,10,11,12,14,16,17.5), ncol=1)
## number of replicates
replicate_no <- 4
## number of genes that will be studied in this example
gene_no <- 4
## read data from file
data(RealData)
## PerturbedData <- data.matrix(Data[1:gene_no,
##                                (2*length(times)*replicate_no+2):dim(Data)[2]])
```

```

## ControlData <- data.matrix(Data[1:gene_no,
##                               (length(times)*replicate_no+2):(2*length(times)*replicate_no+1)])
## define the perturbation time point candidates
times_test <- seq(min(times),max(times),by=(max(times)-min(times))/(4*length(times)))
## gene_ID
## gene_ID <- Data[1:gene_no,1]
## inferring the perturbation time point
res <- DEtime(times = times, ControlData = ControlData[1:gene_no,], PerturbedData=PerturbedData[1:gene_no,],
              replicate_no=replicate_no, gene_no=gene_no, times_test=times_test,
              gene_ID=gene_ID[1:gene_no])
## Print a summary of the results
print_DEtime(res)

```

Perturbation point inference results from DEtime package:

```


## =====
##   gene_ID  MAP  mean median   pt15  pt195
## 1  Probe1 3.365 2.681  3.029 0.0000  4.712
## 2  Probe2 3.029 2.640  2.692 1.0096  3.365
## 3  Probe3 3.029 3.008  3.029 1.6827  3.365
## 4  Probe4 6.058 6.118  6.058 1.6827 10.433
## 5  Probe5 7.067 7.270  7.067 3.3654  9.423
## 6  Probe6 9.087 9.387  9.087 4.7115 15.817
## 7  Probe7 4.038 4.191  4.038 3.0288  5.048
## 8  Probe8 9.087 8.122  8.413 4.3750 10.433
## 9  Probe9 3.702 2.653  3.029 0.3365  4.038
## 10 Probe10 2.019 1.566  1.683 0.3365  2.019
## =====

```

```

## plot the first data
plot_DEtime(res, plot_gene_ID='Probe1')

```



References

Jing Yang, Murray R. Grant, Christopher A. Penfold, and Magnus Rattray. “Inferring the Perturbation Time from Biological Time Course Data.” *Bioinformatics*.