{Learn, Create, Innovate};

ROS

Visualisation Tools








What is RVIZ?

- RVIZ (ROS Visualization)
- Is a 3D visualisation environment
- Made to simplify debugging using visual tools.
- RVIZ allows the user to see what the robot is seeing, thinking and doing.


"See the world through the robot's eyes."







- There are two main ways of putting data into RVIZ.
 - Via messages, where it understands sensors and state information, like laser scans, point clouds, cameras, and coordinate frames.
 - They have specialised displays to let the user configure how to view that information.
 - Information markers, letting the user send cubes, arrows and lines coloured however you want.
- The combination of sensor data and custom visualisation markers makes RVIZ a powerful tool for robotic development.







Quick Start (USB camera)


- Download the rospackage usb_cam
 sudo apt install ros-<\$DISTRO>-usb-cam
- Run the node
 ros2 run usb_cam usb_cam_node_exe
- Check that the topics are being published
 ros2 topic list

Start RVIZ

ros2 run rviz2 rviz2


- Press the "add" button
- Go to the tab "By topic"
- Add the topic Camera, located under the topics
 /usb_cam -> /image_raw





RVIZ

Markers




{Learn, Create, Innovate};





What are markers?

- One of the key features of RViz is the ability to visualize markers.
- Markers are graphical objects that represent different types of data in the 3D space.
- They can display points, lines, meshes, text, and more.
- Markers are typically published as ROS messages and can be subscribed to by RViz for visualisation.
- RViz provides a user-friendly interface for adding, configuring, and visualizing markers.








Type of markers?

- There are different types of markers that help us to visualise information in RViz.
- The basic markers are points, cubes, spheres, arrows, and lines.
- The user can set up and define its own markers and make them move.





string mesh resource

bool mesh use embedded materials



• Markers are defined as ROS messages (composed of submessages) in which the user inputs the type of marker, configuration and characteristics. More information here and here

```
uint8 ARROW=0, uint8 CUBE=1, uint8 SPHERE=2, uint8 CYLINDER=3, uint8 LINE STRIP=4
uint8 LINE LIST=5, uint8 CUBE LIST=6, uint8 SPHERE LIST=7, uint8 POINTS=8, uint8 TEXT VIEW FACING=9, uint8 MESH RESOURCE=10,
uint8 TRIANGLE LIST=11
uint8 ADD=0, uint8 MODIFY=0, uint8 DELETE=2,
uint8 DELETEALL=3
Header header
                                     # header for time/frame information
                                     # Namespace to place this object in... used in conjunction with id to create a unique name for the object
string ns
                                   # object ID useful in conjunction with the namespace for manipulating and deleting the object later
int32 id
int32 type
                                   # Type of object
                                    # 0 add/modify an object, 1 (deprecated), 2 deletes an object, 3 deletes all objects
int32 action
                                        # Pose of the object
geometry msqs/Pose pose
geometry msqs/Vector3 scale
                                        # Scale of the object 1,1,1 means default (usually 1 meter square)
std msgs/ColorRGBA color
                                     # Color [0.0-1.0]
                                     # How long the object should last before being automatically deleted. O means forever
duration lifetime
                                     # If this marker should be frame-locked, i.e. retransformed into its frame every timestep
bool frame locked
#Only used if the type specified has some use for them (eq. POINTS, LINE STRIP, ...)
geometry msgs/Point[] points
#Only used if the type specified has some use for them (eq. POINTS, LINE STRIP, ...)
#number of colors must either be 0 or equal to the number of points
#NOTE: alpha is not yet used
std msgs/ColorRGBA[] colors
# NOTE: only used for text markers
string text
# NOTE: only used for MESH RESOURCE markers
```





Key Aspects

 When using Markers three key aspects must be taken into consideration

Header

- <u>Header Message</u>: in this section the user define the marker frame and the time stamp.
- Markers must be attached to a frame of reference!

Header header # header for time/frame information

```
chassis = Marker()
chassis.header.frame_id = "base_link"
chassis.header.stamp = self.get_clock().now().to_msg()
```

Pose

 Pose Message, in this section the user define the pose (position and orientation) of the marker with respect to the frame of reference stated on the Header ("base_link"). The position is given by a point and the orientation by a quaternion.

geometry msgs/Pose pose # Pose of the object

```
chassis.pose.position.x = 0.205/2
chassis.pose.position.y = 0.0
chassis.pose.position.z = 0.0
chassis.pose.orientation.x = 0.0
chassis.pose.orientation.y = 0.0
chassis.pose.orientation.z = 0.0
chassis.pose.orientation.w = 1.0
```





Key Aspects

 When using Markers three key aspects must be taken into consideration

Header

- <u>Header Message</u>: in this section the user define the marker frame and the time stamp.
- Markers must be attached to a frame of reference!

Header header # header for time/frame information

```
chassis = Marker()

chassis.header.frame_id = "base_link"

chassis.header.stamp = self.get_clock().now().to_msg()
```

Pose

- Pose Message, in this section the user define the pose (position and orientation) of the marker with respect to the frame of reference stated on the Header ("base_link"). The position is given by a point and the orientation by a quaternion.
- If the pose varies through time, it will be done w.r.t the header's frame of reference.

geometry msgs/Pose pose # Pose of the object

```
chassis.pose.position.x = 0.205/2
chassis.pose.position.y = 0.0
chassis.pose.position.z = 0.0
chassis.pose.orientation.x = 0.0
chassis.pose.orientation.y = 0.0
chassis.pose.orientation.z = 0.0
chassis.pose.orientation.w = 1.0
```



Markers




Scale

• <u>Vector3 message</u> in this section the user defines the Scale/Size of the object in each of its dimension's x,y,z.


geometry_msgs/Vector3 scale # Scale of the object
1,1,1 means default (usually 1 meter square)

```
chassis.scale.x = 0.205
chassis.scale.y = 0.41
chassis.scale.z = 0.2
```



Activity 1

Markers



{Learn, Create, Innovate};





Declaring a Static Transform from Launch File

- Make a package called "markers" and a node called "markers.py" with the following dependencies:
 - geometry_msgs, python3-numpy, rclpy, tf2_ros_py, ros2launch, std_msgs python3-transforms3d visualization_msgs

\$ ros2 pkg create --build-type ament_python markers --license
Apache-2.0 --node-name markers --dependencies geometry_msgs
python3-numpy rclpy tf2_ros_py ros2launch std_msgs python3transforms3d visualization_msgs --description TF2_Examples -maintainer-name "Mario Martinez" --maintainer-email
mario.mtz@manchester-robotics.com

 Do not forget to give executable permissions to the newly created files

```
$ chmod +x markers/markers/*
```

```
markers/
— LICENSE
— markers
— __init__.py
— markers.py
— package.xml
— resource
— markers
— setup.cfg
— setup.py
— test
— test_copyright.py
— test_flake8.py
— test_pep257.py
```





 Make a launch folder and a launch file called "simple_marker_launch.py"

```
#replace "YOUR_WS" with the name of tour workspace

$ cd ~/<YOUR_WS>/src/markers
$ mkdir launch
$ touch simple_marker_launch.py
$ chmod +x markers/launch/*
```

Change the "setup.py" to find the launch files

```
rom setuptools import find packages, setup
from glob import glob
package name = 'tf examples'
setup(
    name=package name,
    version='0.0.0',
    packages=find packages(exclude=['test
        ('share/ament index/resource index/packages',
            ['resource/' + package name]),
        ('share/' + package name, ['package.xml']),
        (os.path.join('share', package name, 'launch'), glob(os.path.join('launch', '*launch.[pxy][yma]*'))),
    install_requires=['setuptools'],
    zip safe=True,
    maintainer='Mario Martinez',
    maintainer email='mario.mtz@manchester-robotics.com',
    description='TF2 Examples',
    license='Apache-2.0',
    tests require=['pytest'],
    entry_points={
         'console scripts': [
```





- Open the file markers.py
- Define a new marker called marker in the constructor

```
# Message Declaration
self.marker = Marker()
```

• Define its publisher

```
self.publisher = self.create_publisher(Marker, '/marker', 10)
```

- Initialise the marker (if needed) on the constructor
 - For this exercise the marker is defined w.r.t "map" frame.
- Define a timer to update the marker pose (next slide)
- Publish the marker

```
#Variables to be used
       self.omega = 0.5
       self.intial pos x = 0.0
       self.intial pos y = 0.0
        self.intial pos z = 1.0
       #initialise the marker(the pose and orientation will be
changed on the callback function)
       self.marker = Marker()
       self.marker.header.frame id = "map"
        self.marker.header.stamp = self.get clock().now().to msg()
        self.marker.id = 0
       self.marker.type = Marker.CUBE
        self.marker.action = Marker.ADD
        self.marker.pose.position.x = self.intial pos x
        self.marker.pose.position.y = self.intial pos y
        self.marker.pose.position.z = self.intial pos z
        self.marker.pose.orientation.x = 0.0
        self.marker.pose.orientation.y = 0.0
        self.marker.pose.orientation.z = 0.0
        self.marker.pose.orientation.w = 1.0
        self.marker.scale.x = 0.2
       self.marker.scale.y = 0.5
       self.marker.scale.z = 0.2
       self.marker.color.r = 1.0
       self.marker.color.g = 1.0
       self.marker.color.b = 0.0
       self.marker.color.a = 1.0
```

```
import rclpv
from rclpy.node import Node
from visualization_msgs.msg import Marker
import transforms3d
import numpy as np
from rclpy.duration import Duration
class MarkersPublisher(Node):
    def __init__(self):
        super(). init ('marker publisher')
        self.publisher = self.create publisher(Marker, '/marker', 10)
        #Variables to be used
        self.omega = 0.5
        self.intial_pos_x = 0.0
        self.intial pos y = 0.0
        self.intial pos z = 1.0
       #initialise the marker
        self.marker = Marker()
        self.marker.header.frame id = "map"
        self.marker.header.stamp = self.get clock().now().to msg()
        self.marker.id = 0
        self.marker.type = Marker.CUBE
        self.marker.action = Marker.ADD
        self.marker.pose.position.x = self.intial pos x
        self.marker.pose.position.y = self.intial pos y
        self.marker.pose.position.z = self.intial pos z
        self.marker.pose.orientation.x = 0.0
        self.marker.pose.orientation.y = 0.0
        self.marker.pose.orientation.z = 0.0
        self.marker.pose.orientation.w = 1.0
        self.marker.scale.x = 0.2
        self.marker.scale.y = 0.5
        self.marker.scale.z = 0.2
        self.marker.color.r = 1.0
        self.marker.color.g = 1.0
        self.marker.color.b = 0.0
        self.marker.color.a = 1.0
```

```
timer period = 0.1 #seconds
       self.timer = self.create_timer(timer_period, self.timer_cb)
       self.i = 0
    #Timer Callback
    def timer_cb(self):
       time = self.get clock().now().nanoseconds/1e9
       q = transforms3d.euler.euler2quat(0, 1.57, self.omega*time)
       self.marker.header.stamp = self.get clock().now().to msg()
        self.marker.pose.position.x = self.intial pos x + 0.5*np.sin(self.omega*time)
       self.marker.pose.position.y = self.intial_pos_y + 0.5*np.cos(self.omega*time)
       self.marker.pose.position.z = self.intial_pos_z
       self.marker.pose.orientation.x = q[1]
       self.marker.pose.orientation.y = q[2]
       self.marker.pose.orientation.z = q[3]
        self.marker.pose.orientation.w = q[0]
        self.publisher.publish(self.marker)
def main(args=None):
    rclpy.init(args=args)
    node = MarkersPublisher()
    try:
       rclpy.spin(node)
    except KeyboardInterrupt:
    finally:
        if rclpy.ok(): # Ensure shutdown is only called once
           rclpy.shutdown()
       node.destroy_node()
if name == ' main ':
   main()
```





• Compile the program

cd ~/<YOUR_WS>

colcon build

source install/setup.bash


Run the node


ros2 run markers markers

• Start RViz

ros2 run rviz2 rviz2

- Add the marker
 - Press Add
 - >>By topic>>/marker>> marker
- Change the fixed frame on top of RViz to "map"
- Visualise the Fixed Frame by adding "Axes" from the "Add" Menu









Markers and Transforms



Scale


- One of the best practices in ROS is to attach markers to frames of reference at their origin.
- The movement of the markers should be performed by the frames of reference rather than by the marker itself.
- In other words, the frame must move while the marker is attached to its centre.
- In the previous example the marker was moving around a frame of reference (not recoomended), better to declare a frame, move the frame and keep the marker attached to its origin.





Activity 2

Multiple Markers




{Learn, Create, Innovate};






- In this activity a simple Puzzle Drone will be modelled.
- To decrease the complexity and decrease computational power, only the basic parts od the Puzzle Drone will be modelled (excl. motors, cables, PCB, etc.)
- The transforms will be set up as follows.
- The markers will be attached to each one of the transforms.
- For this case, a "mesh" type marker will be used.







- The following coordinates will be used to define the Drone as Transforms.
- Once the transforms are defined, the markers will be set up to lay on top of the transforms.
- The user should manipulate/control the transforms only, not the Markers.
- For this exercise, the basic on how to define transforms and markers will be shown.
- For this activity, the full code is on GitHub (too long to be on a ppt.)







• Make a new node called "PuzzleDrone.py" inside the "markers" package developed previously.

```
$ touch ~/<YOUR_WS>/src/markers/markers/PuzzleDrone.py
```

Make a launch file called "puzzledrone_launch.py"

```
$ mkdir ~/<YOUR_WS>/src/markers/launch
$ touch ~/<YOUR WS>/src/markers/launch/puzzledrone_launch.py
```

- Give execution permission to both files
- Modify the previously created "setup.py" as follows





Make a "meshes" directory in the package "markers"

\$ mkdir ~/<YOUR WS>/src/markers/meshes

 Download inside the folder "meshes" the three ".stl" files in GitHub.

```
base_210mm.stl
propeller_ccw_puller_5in.stl
propeller_cw_puller_5in.stl
```

- The folder tree should look as in the image
- Open the "PuzzleDrone.py"
- Type the following code (node initialisation)

```
puzzledrone launch.py
     _init__.py
   markers.py
   PuzzleDrone.py
    base 210mm.stl
    propeller ccw puller 5in.stl
    propeller cw puller 5in.stl
package.xml
└─ markers
 — config.rviz
setup.cfg
setup.py
    test_copyright.py
    test_flake8.py
    test_pep257.py
```





```
import rclpy
from rclpy.node import Node
from tf2 ros import TransformBroadcaster
from geometry_msgs.msg import TransformStamped
from visualization_msgs.msg import Marker
import transforms3d
import numpy as np
class DronePublisher(Node):
   def init (self):
       super(). init ('frame publisher')
       #Drone Initial Pose
       self.intial_pos_x = 1.0
       self.intial pos y = 1.0
       self.intial pos z = 1.0
       self.intial_pos_yaw = np.pi/2
       self.intial pos pitch = 0.0
       self.intial_pos_roll = 0.0
       #Angular velocity for the pose change and propellers
       self.omega = 0.5
       self.omega prop = 100.0
       #Define Transformations
       self.define TF()
       #Define Markers
       self.define markers()
```

```
#Create Transform Boradcasters
        #Create Markers Publishers
        #Create a Timer
        timer period = 0.01 #seconds
        self.timer = self.create_timer(timer_period, self.timer_cb)
    #Timer Callback
    def timer cb(self):
        #Callback to be filled
    def define markers(self):
        #Initialise the markers here
    def define TF(self):
        #Create Trasnform Messages here
def main(args=None):
   rclpy.init(args=args)
   node = DronePublisher()
    try:
        rclpy.spin(node)
    except KeyboardInterrupt:
    finally:
        if rclpy.ok(): # Ensure shutdown is only called once
            rclpy.shutdown()
        node.destroy node()
if name == ' main ':
    main()
```




Transforms



- Each transform will be declared as follows:
- All transforms will be defined inside the function "define TF"

```
def define TF(self):
    #Create Trasnform Messages
    self.base_footprint_tf = TransformStamped()
    self.base footprint tf.header.stamp = self.get clock().now().to msg()
    self.base_footprint_tf.header.frame_id = 'odom'
    self.base footprint tf.child frame id = 'base footprint'
    self.base_footprint_tf.transform.translation.x = self.intial_pos_x
    self.base_footprint_tf.transform.translation.y = self.intial_pos_y
    self.base footprint tf.transform.translation.z = 0.0
    q foot = transforms3d.euler.euler2quat(self.intial pos roll,
self.intial pos pitch, self.intial pos yaw)
    self.base footprint tf.transform.rotation.x = q foot[1]
    self.base_footprint_tf.transform.rotation.y = q_foot[2]
    self.base footprint tf.transform.rotation.z = q foot[3]
    self.base footprint tf.transform.rotation.w = q foot[0]
... #Define the rest of the transforms
```








- The same as with Transforms, the markers must be defined.
- Each marker will be related to a frame and to a mesh (in this case simple marker will not be used)

Marker	Ш	Frame/link to att	ach Mesh to attach
base		base_link	base_210mm.stl
prop1		prop_1	<pre>propeller_ccw_puller_5in.stl</pre>
prop2		prop_2	propeller_cw_puller_5in.stl
prop3		prop_3	<pre>propeller_ccw_puller_5in.stl</pre>
prop4		prop_4	<pre>propeller_cw_puller_5in.stl</pre>








```
def define markers(self):
    #initialise the marker
    self.base = Marker()
    self.base.header.frame id = "base link"
    self.base.header.stamp = self.get clock().now().to msg()
    self.base.id = 0
    self.base.type = Marker.MESH RESOURCE
    self.base.mesh resource = "package://markers/meshes/base 210mm.stl"
    self.base.action = Marker.ADD
    self.base.pose.position.x = 0.0
    self.base.pose.position.y = 0.0
    self.base.pose.position.z = -0.0205
    q base marker = transforms3d.euler.euler2quat(1.57, 0.0, 1.57)
    self.base.pose.orientation.x = q base marker[1]
    self.base.pose.orientation.y = q base marker[2]
    self.base.pose.orientation.z = q base marker[3]
    self.base.pose.orientation.w = q base marker[0]
    self.base.scale.x = 1.0
    self.base.scale.y = 1.0
    self.base.scale.z = 1.0
    self.base.color.r = 1.0
    self.base.color.g = 1.0
    self.base.color.b = 0.0
    self.base.color.a = 1.0
... #Define the rest of the Markers
```

- Some markers requires a small adjustment,
 because the coordinate frame of the .stl file is
 not the same as the coordinate frame in ROS.
- In the example the position and orientations of the markers changed to make the coordinate of the .stl to match with the one defined by ROS standards.





- Update the dynamic transforms and the time stamp of the markers.
- The "TF's" must be updated inside the timer callback.
- For the "markers" only the timestamp must be updated, since they are fixed to a Frame.
- The user must always control the Frames, not the markers.
- If using meshes, the tessellation in the stl files must be as low quality as possible to save computing power for other ROS Tasks (This is just to visualise!)







```
import rclpy
from rclpy.node import Node
from tf2 ros import TransformBroadcaster
from geometry msgs.msg import TransformStamped
from visualization msgs.msg import Marker
import transforms3d
import numpy as np
class DronePublisher(Node):
   def init (self):
        super(). init ('frame publisher')
        #Drone Initial Pose
        self.intial pos x = 1.0
        self.intial pos y = 1.0
        self.intial pos z = 1.0
        self.intial pos yaw = np.pi/2
        self.intial pos pitch = 0.0
        self.intial pos roll = 0.0
        #Angular velocity for the pose change and propellers
        self.omega = 0.5
        self.omega prop = 100.0
        #Define Transformations
        self.define TF()
        #Define Markers
        self.define markers()
        #Create Transform Boradcasters
        self.tf br base = TransformBroadcaster(self)
        ... #Define the other broadcasters for each transform
```

```
#Create Markers Publishers
        self.base marker pub = self.create publisher(Marker, '/base marker', 10)
        ... #Define the other publishers for each marker
        #Create a Timer
        timer period = 0.01 #seconds
        self.timer = self.create timer(timer period, self.timer cb)
   def timer_cb(self):
        time = self.get clock().now().nanoseconds/1e9
        #Update the time stamp of each marker
        self.base.header.stamp = self.get clock().now().to msg()
        #Update the Transforms
        self.base link tf.header.stamp = self.get clock().now().to msg()
        self.base link tf.transform.translation.x = self.intial pos x + 0.5*np.cos(self.omega*time)
        self.base_link_tf.transform.translation.y = self.intial_pos y + 0.5*np.sin(self.omega*time)
        self.base link tf.transform.translation.z = self.intial pos z
        q = transforms3d.euler.euler2quat(self.intial pos roll, self.intial pos pitch,
self.intial_pos_yaw+self.omega*time)
        self.base link tf.transform.rotation.x = q[1]
        self.base link tf.transform.rotation.y = q[2]
        self.base link tf.transform.rotation.z = q[3]
        self.base link tf.transform.rotation.w = q[0]
        self.tf br base.sendTransform(self.base link tf)
        ... #Broadcast the other TF's
        self.base marker pub.publish(self.base)
        ... #Publish the Other Markers
```






- Open the launch file previously done.
- Define two static transforms
 - world -> map (same pose)
 - map \rightarrow odom [x= 2, y=1, z=-0.0, r=0, p=0.0, yaw=0]

- Add the "PuzzleDrone" node to the launch file.
- You can add RVIZ and TF_Tree to verify the transforms.
- Build the package
- Launch the package
- Add the TF's to RVIZ and the Markers




Results





Thank you



T&C

Terms and conditions



{Learn, Create, Innovate};



Terms and conditions



- THE PIECES, IMAGES, VIDEOS, DOCUMENTATION, ETC. SHOWN HERE ARE FOR INFORMATIVE PURPOSES ONLY.

 THE DESIGN IS PROPRIETARY AND CONFIDENTIAL TO MANCHESTER ROBOTICS LTD. (MCR2). THE INFORMATION,

 CODE, SIMULATORS, DRAWINGS, VIDEOS PRESENTATIONS ETC. CONTAINED IN THIS PRESENTATION IS THE SOLE

 PROPERTY OF MANCHESTER ROBOTICS LTD. ANY REPRODUCTION, RESELL, REDISTRIBUTION OR USAGE IN PART

 OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MANCHESTER ROBOTICS LTD. IS STRICTLY PROHIBITED.
- THIS PRESENTATION MAY CONTAIN LINKS TO OTHER WEBSITES OR CONTENT BELONGING TO OR ORIGINATING FROM THIRD PARTIES OR LINKS TO WEBSITES AND FEATURES IN BANNERS OR OTHER ADVERTISING. SUCH EXTERNAL LINKS ARE NOT INVESTIGATED, MONITORED, OR CHECKED FOR ACCURACY, ADEQUACY, VALIDITY, RELIABILITY, AVAILABILITY OR COMPLETENESS BY US.
- WE DO NOT WARRANT, ENDORSE, GUARANTEE, OR ASSUME RESPONSIBILITY FOR THE ACCURACY OR
 RELIABILITY OF ANY INFORMATION OFFERED BY THIRD-PARTY WEBSITES LINKED THROUGH THE SITE OR ANY
 WEBSITE OR FEATURE LINKED IN ANY BANNER OR OTHER ADVERTISING.