

PIPING LINE LIST

Unit 4102 - Debutaniser and Naphtha Splitter Section

Document No.: 4102-LL-002

Revision: 7

Issued: 09 Nov 2023

Prepared By: Design and Projects

1. Drawing Index

Drawing No.	Title	Revision	Sheet
4102-PID-004	Debutaniser feed and preheat	5	1 of 1
4102-PID-005	Debutaniser column and reboiler	6	1 of 2
4102-PID-006	Debutaniser overhead and reflux	4	1 of 1
4102-PID-007	Naphtha splitter column	3	1 of 2
4102-PID-008	LPG treating and storage	2	1 of 1

2. Line Schedule

Line No.	From	To	Size	Material	Design T	Design P	Insulation
6-P-2104	Debutaniser C-2101 ov	Condenser E-2103	6 in	ASTM A106 Gr.B	185 C	14.0 barg	None
4-P-2105	Condenser E-2103	Reflux drum D-21	4 in	ASTM A106 Gr.B	95 C	14.0 barg	None
3-P-2106	Reflux drum D-2101	Reflux pump P-21	3 in	ASTM A106 Gr.B	95 C	14.0 barg	None
8-P-2110	Reboiler E-2105	Debutaniser C-21	8 in	ASTM A335 P11	245 C	16.0 barg	Hot
10-S-3301	Steam header	Reboiler E-2105	10 in	ASTM A106 Gr.B	260 C	18.0 barg	Hot, calcium
2-P-2115	LPG treater V-2110	Storage sphere	2 in	ASTM A106 Gr.B	60 C	20.0 barg	None

Line 6-P-2104 is the debutaniser overhead vapour line, fabricated in ASTM A106 Gr.B seamless pipe to schedule 40, and is shown on drawing 4102-PID-006. It carries the relief connection to PSV-2103.

3. Notes

Insulation marked Hot denotes heat conservation insulation. Calcium silicate is specified for surfaces above 200 degrees C. All insulated carbon steel lines operating between minus 12 and 175 degrees C are within the corrosion under insulation susceptibility range and are included in the CUI inspection programme.