

```

create or replace trigger trig21 instead of insert on empview for each row
begin
    dbms_output.put_line('Instead of trigger');
end;
/
-----
create or replace trigger trig22 instead of delete on stockview for each row
begin
    if :old.qty>0 then
        dbms_output.put_line('Qty still in stock, can not delete');
    else
        delete from stockinhand where itemcd=:old.itemcd;
        dbms_output.put_line('Qty 0, product deleted');
    end if;
end;
/
-----
create or replace trigger trig23 instead of insert on admview for each row
declare
    rseats course_master.rem_seats%type;
begin
    select rem_seats into rseats from course_master where
        ccd=:new.ccd;
    if rseats>0 then
        update course_master set rem_seats=rem_seats-1
        where ccd=:new.ccd;
        insert into adm_master values(:new.admno,:new.name,:new.ccd);
        dbms_output.put_line('Admission Granted !! Seats Updated');
    else
        dbms_output.put_line('No seats left');
    end if;
end;
/
-----
create or replace trigger trig24 instead of insert on insview for each row
declare
    bal number;
    excess number;
begin
    select balance into bal from loan_master where acno=:new.acno;
    if bal>0 then
        if :new.amt>bal then
            update loan_master set balance=0
            where acno=:new.acno;
            excess:=:new.amt-bal;
            dbms_output.put_line('Excess amount ' || excess || '
returned');
        else
            insert into installments values(:new.acno,bal);
            update loan_master set balance=balance-:new.amt

```

```

                where acno=:new.acno;
                insert into installments values(:new.acno,:new.amt);
            end if;
        else
            dbms_output.put_line('Load already paid');
        end if;

```

```

end;
/

```

```

=====
                        SQL CODE
=====

```

SQL*Plus: Release 10.2.0.1.0 - Production on Sat Dec 27 08:36:32 2025

Copyright (c) 1982, 2005, Oracle. All rights reserved.

```

SQL> conct
SP2-0042: unknown command "conct" - rest of line ignored.

```

```

SQL> connect
Enter user-name: prince
Enter password:
Connected.
SQL> ed c:/oracle/trig21

```

```

SQL> @ c:/oracle/trig21
create or replace trigger trig21 instead of insert on emp1 for each row
                                                                *

```

```

ERROR at line 1:
ORA-25002: cannot create INSTEAD OF triggers on tables

```

```

SQL> create view empview as select * from emp1;

```

View created.

```

SQL> select * from empview;

```

EMPNO	NAME	SALARY
1	A	5000

```

SQL> ed c:/oracle/trig21

```

```

SQL> @ c:/oracle/trig21

```

Trigger created.

```

SQL> ed c:/oracle/trig21

```

```

SQL> insert into emp1 values(2,'B',5000);

```

1 row created.

SQL> select * from emp1;

EMPNO	NAME	SALARY
1	A	5000
2	B	5000

SQL> insert into empview values(3,'B',5000);

1 row created.

SQL> select * from emp1;

EMPNO	NAME	SALARY
1	A	5000
2	B	5000

SQL> select * from empview;

EMPNO	NAME	SALARY
1	A	5000
2	B	5000

SQL> ed c:/oracle/trig21

SQL> create table stockinhand(itemcd int,qty int);

Table created.

SQL>

SQL> insert into stockinhand(1,50);

insert into stockinhand(1,50)

*

ERROR at line 1:

ORA-00928: missing SELECT keyword

SQL> insert into stockinhand values(1,50);

1 row created.

SQL> insert into stockinhand values(2,30);

1 row created.

```
SQL> insert into stockinhand values(3,10);
```

```
1 row created.
```

```
SQL> insert into stockinhand values(4,1);
```

```
1 row created.
```

```
SQL> insert into stockinhand values(5,0);
```

```
1 row created.
```

```
SQL> select * from stockinhand;
```

ITEMCD	QTY
1	50
2	30
3	10
4	1
5	0

```
SQL> ed c:/oracle/trig22
```

```
SQL> @ c:/oracle/trig22
```

```
Trigger created.
```

```
SQL> delete from stockinhand where itemcd=1;
```

```
1 row deleted.
```

```
SQL> set serveroutput on
```

```
SQL> delete from stockinhand where itemcd=2;  
Qty still in stock, can not delete
```

```
1 row deleted.
```

```
SQL> select * from stockinhand;
```

ITEMCD	QTY
3	10
4	1
5	0

```
SQL> ed c:/oracle/trig22
```

```
SQL> drop trigger trigg22;  
drop trigger trigg22
```

```
*
ERROR at line 1:
ORA-04080: trigger 'TRIGG22' does not exist
```

```
SQL> drop trigger trig22;
```

Trigger dropped.

```
SQL> ed c:/oracle/trig22
```

```
SQL> create view stockview as select * from stockinhand;
```

View created.

```
SQL> @ c:/oracle/trig22
create or replace trigger trig22 before delete on stockview for each row
*
```

```
ERROR at line 1:
ORA-25001: cannot create this trigger type on views
```

```
SQL> ed c:/oracle/trig22
```

```
SQL> @ c:/oracle/trig22
```

Trigger created.

```
SQL> select * from stockview;
```

ITEMCD	QTY
3	10
4	1
5	0

```
SQL> delete from stockview where itemcd=3;
Qty still in stock, can not delete
```

1 row deleted.

```
SQL> select * from stockinhand;
```

ITEMCD	QTY
3	10
4	1
5	0

```
SQL> delete from stockview where itemcd=5;
```

1 row deleted.

SQL> select * from stockinhand;

ITEMCD	QTY
3	10
4	1
5	0

SQL> ed c:/oracle/trig22

SQL> @ c:/oracle/trig22

Trigger created.

SQL> delete from stockinhand where itemcd=3;

1 row deleted.

SQL> delete from stockview where itemcd=4;
Qty still in stock, can not delete

1 row deleted.

SQL> delete from stockview where itemcd=0;

0 rows deleted.

SQL> delete from stockview where itemcd=1;

0 rows deleted.

SQL> delete from stockview where itemcd=5;
Qty 0, product deleted

1 row deleted.

SQL> select * from stockinhand;

ITEMCD	QTY
4	1

SQL> ed c:/oracle/trig22

SQL> ed c:/oracle/trig22

SQL> grant create view to rahul;

```
grant create view to rahul
*
ERROR at line 1:
ORA-01031: insufficient privileges
```

```
SQL> create table course_master
2 (ccd number,cname varchar(10),total_seats number,rem_seats number);
```

Table created.

```
SQL> insert into course_master values
2 (1,'CS',60,60);
```

1 row created.

```
SQL> insert into course_master values
2 (1,'AI',40,40);
```

1 row created.

```
SQL> insert into course_master values
2 (3,'Mech',30,30);
```

1 row created.

```
SQL> select * from course_master;
```

CCD	CNAME	TOTAL_SEATS	REM_SEATS
1	CS	60	60
1	AI	40	40
3	Mech	30	30

```
SQL> update course_master set ccd=2 where cname='AI';
```

1 row updated.

```
SQL> select * from course_master;
```

CCD	CNAME	TOTAL_SEATS	REM_SEATS
1	CS	60	60
2	AI	40	40
3	Mech	30	30

```
SQL> create table adm_master (admno number, name varchar(10),ccd number);
```

Table created.

```
SQL> ed c:/oracle/trig23
```

```
SQL> create view admview as select * from adm_master;
```

View created.

```
SQL> ed c:/oracle/trig23
```

```
SQL> @ c:/oracle/trig23
```

```
16 /
```

Trigger created.

```
SQL> insert into admview values(101,'A',1);
```

Admission Granted !! Seats Updated

1 row created.

```
SQL> select * from course_master;
```

	CCD	CNAME	TOTAL_SEATS	REM_SEATS
1	CS		60	59
2	AI		40	40
3	Mech		30	30

```
SQL> insert into admview values(102,'A',1);
```

Admission Granted !! Seats Updated

1 row created.

```
SQL> insert into admview values(103,'A',2);
```

Admission Granted !! Seats Updated

1 row created.

```
SQL> select * from course_master;
```

	CCD	CNAME	TOTAL_SEATS	REM_SEATS
1	CS		60	58
2	AI		40	39
3	Mech		30	30

```
SQL> update course_master set rem_seats=1 where ccd=1;
```

1 row updated.

```
SQL> select * from course_master;
```


CCD	CNAME	TOTAL_SEATS	REM_SEATS
1	CS	60	1
2	AI	40	39
3	Mech	30	30

SQL> insert into admview values(103,'A',1);
Admission Granted !! Seats Updated

1 row created.

SQL> select * from course_master;

CCD	CNAME	TOTAL_SEATS	REM_SEATS
1	CS	60	0
2	AI	40	39
3	Mech	30	30

SQL> insert into admview values(103,'A',1);
No seats left

1 row created.

SQL> select * from course_master;

CCD	CNAME	TOTAL_SEATS	REM_SEATS
1	CS	60	0
2	AI	40	39
3	Mech	30	30

SQL> select * from adm_master;

ADMNO	NAME	CCD
101	A	1
102	A	1
103	A	2
103	A	1

SQL> insert into admview values(103,'A',1);
No seats left

1 row created.

SQL> select * from adm_master;

ADMNO	NAME	CCD
-------	------	-----

101 A	1
102 A	1
103 A	2
103 A	1

```
SQL> set feedback off;
SQL> insert into admview values(103,'A',1);
No seats left
SQL> @ c:/oracle/trig23
16 /
SQL> ed c:/oracle/trig23
```

```
SQL> create table loan_master
  2 (acno number, name varchar(10), loan_amt number,balance number);
SQL> set feedback on;
SQL> insert into loan_master values
  2 (1,'A',50000,50000);
```

1 row created.

```
SQL> insert into loan_master values
  2 (2,'B',60000,60000);
```

1 row created.

```
SQL> insert into loan_master values
  2 (3,'C',90000,90000);
```

1 row created.

```
SQL> select * from loan_master;
```

ACNO	NAME	LOAN_AMT	BALANCE
1	A	50000	50000
2	B	60000	60000
3	C	90000	90000

3 rows selected.

```
SQL> create table installments(acno number,amt number);
```

Table created.

```
SQL> ed c:/oracle/trig24
```

```
SQL> ed c:/oracle/trig24
```

```
SQL> @ c:/oracle/trig24
create or replace trigger trig24 instead of insview for each row
```

*

ERROR at line 1:
ORA-04072: invalid trigger type

SQL> create view insview as select * from installments;

View created.

SQL> @ c:/oracle/trig24
create or replace trigger trig24 instead of insview for each row

*

ERROR at line 1:
ORA-04072: invalid trigger type

SQL> ed c:/oracle/trig24

SQL> @ c:/oracle/trig24

Trigger created.

SQL> select * from loan_master;

ACNO	NAME	LOAN_AMT	BALANCE
1	A	50000	50000
2	B	60000	60000
3	C	90000	90000

3 rows selected.

SQL> insert into insview values(2,5000);

1 row created.

SQL> select * from loan_master;

ACNO	NAME	LOAN_AMT	BALANCE
1	A	50000	50000
2	B	60000	55000
3	C	90000	90000

3 rows selected.

SQL> select * from installments;

no rows selected

SQL>

SQL> ed c:/oracle/trig24

SQL> @ c:/oracle/trig24

Trigger created.

SQL> insert into insview values(2,5000);

1 row created.

SQL> select * from loan_master;

ACNO	NAME	LOAN_AMT	BALANCE
1	A	50000	50000
2	B	60000	50000
3	C	90000	90000

3 rows selected.

SQL> select * from installments;

ACNO	AMT
2	5000

1 row selected.

SQL> insert into insview values(2,50000);

1 row created.

SQL> select * from loan_master;

ACNO	NAME	LOAN_AMT	BALANCE
1	A	50000	50000
2	B	60000	0
3	C	90000	90000

3 rows selected.

SQL> select * from installments;

ACNO	AMT
2	5000
2	50000

2 rows selected.

```
SQL> insert into insview values(2,5000);
```

1 row created.

```
SQL> select * from installments;
```

ACNO	AMT
2	5000
2	50000

2 rows selected.

```
SQL> select * from loan_master;
```

ACNO	NAME	LOAN_AMT	BALANCE
1	A	50000	50000
2	B	60000	0
3	C	90000	90000

3 rows selected.

```
SQL> insert into insview values(1,55000);
```

1 row created.

```
SQL> select * from loan_master;
```

ACNO	NAME	LOAN_AMT	BALANCE
1	A	50000	-5000
2	B	60000	0
3	C	90000	90000

3 rows selected.

```
SQL> select * from installments;
```

ACNO	AMT
2	5000
2	50000
1	55000

3 rows selected.

```
SQL> ed c:/oracle/trig24
```

```
SQL> @ c:/oracle/trig24
```

Trigger created.

```
SQL> select * from loan_master;
```

ACNO	NAME	LOAN_AMT	BALANCE
1	A	50000	-5000
2	B	60000	0
3	C	90000	90000

3 rows selected.

```
SQL> select * from installments;
```

ACNO	AMT
2	5000
2	50000
1	55000

3 rows selected.

```
SQL> update loan_master set balance=50000 where acno=1;
```

1 row updated.

```
SQL> update loan_master set balance=60000 where acno=2;
```

1 row updated.

```
SQL> select * from loan_master;
```

ACNO	NAME	LOAN_AMT	BALANCE
1	A	50000	50000
2	B	60000	60000
3	C	90000	90000

3 rows selected.

```
SQL> truncate table installments;
```

Table truncated.

```
SQL> insert into insview values(1,2000);
```

1 row created.

SQL> select * from loan_master;

ACNO	NAME	LOAN_AMT	BALANCE
1	A	50000	48000
2	B	60000	60000
3	C	90000	90000

3 rows selected.

SQL> truncate table installments;

Table truncated.

SQL> update loan_master set balance=60000 where acno=2;

1 row updated.

SQL> select * from loan_master;

ACNO	NAME	LOAN_AMT	BALANCE
1	A	50000	48000
2	B	60000	60000
3	C	90000	90000

3 rows selected.

SQL> insert into insview values(1,5000);

1 row created.

SQL> select * from loan_master;

ACNO	NAME	LOAN_AMT	BALANCE
1	A	50000	43000
2	B	60000	60000
3	C	90000	90000

3 rows selected.

SQL> select * from installments;

ACNO	AMT
1	5000

1 row selected.

```
SQL> insert into insview values(1,43000);
```

1 row created.

```
SQL> select * from loan_master;
```

ACNO	NAME	LOAN_AMT	BALANCE
1	A	50000	0
2	B	60000	60000
3	C	90000	90000

3 rows selected.

```
SQL> select * from installments;
```

ACNO	AMT
1	5000
1	43000

2 rows selected.

```
SQL> insert into insview values(1,5000);
```

1 row created.

```
SQL> select * from loan_master;
```

ACNO	NAME	LOAN_AMT	BALANCE
1	A	50000	0
2	B	60000	60000
3	C	90000	90000

3 rows selected.

```
SQL> select * from installments;
```

ACNO	AMT
1	5000
1	43000

2 rows selected.

```
SQL> insert into insview values(2,70000);
```

Excess amount 10000 returned

1 row created.

SQL> select * from loan_master;

ACNO	NAME	LOAN_AMT	BALANCE
1	A	50000	0
2	B	60000	0
3	C	90000	90000

3 rows selected.

SQL> select * from installments;

ACNO	AMT
1	5000
1	43000
2	60000

3 rows selected.

SQL> ed c:/oracle/trig24

SQL> note